



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 3030

PRODUCT NAME: **POLY D-TAC 570**

USE: Paint booth deflocculant

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: D2B

CHEMICAL FAMILY: Acid

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Aluminum chlorhydrate	10-30	001327-41-9	not available	N/avail.

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: natural rubber or neoprene

Eye: safety glasses

Footwear: not applicable

Respiratory: If mists are generated, use NIOSH approved mask

Other: not applicable

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: not applicable

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): Strong oxidizing agents.

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid freezing.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, water-white liquid

S.G. / BULK DENSITY(g/cc): 1.25

pH: (Concentrate) 3.8

VAPOUR PRESSURE (mmHg): not available

VAPOUR DENSITY (air=1): >1

ODOUR THRESHOLD: not available

BOILING POINT: approx. 100°C

FREEZING POINT: 0°C

PERCENT VOLATILE: 55%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation.

SKIN: May cause irritation.

INGESTION: May cause severe irritation of the digestive tract.

INHALATION: No serious or irreversible effects expected.

LD50 (calculated): Not available

LC50 (calculated): Not applicable

OTHER TOXIC EFFECTS: Aluminum Chlorhydrate TWA 2 mg (Al)/m3	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: None known.	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.
INHALATION:	Remove patient to fresh air.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: not applicable	
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE, °C: N/App.
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: not required.	
HAZARDOUS COMBUSTION PRODUCTS: May decompose to hydrogen chloride in a fire.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: not applicable	
INCOMPATIBILITY (Material to Avoid) : Strong oxidizing agents	
HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen chloride.	
REACTIVITY: not dangerously reactive.	
IX - MSDS PREPARATION	
SOURCES USED: RTECS	PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Industrial Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	