Page 1 of 4 Revised 2/02/04 Replaces 9/04/03

2/03/04

Printed

MSDS ID: 3104278

PD-7661

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PD-7661

Product Descriptor: CONCENTRATED LUBRICANT

MANUFACTURER: JOHNSONDIVERSEY, INC. EMERGENCY PHONE NUMBER: (800)851-7145

3630 E. KEMPER ROAD CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
POTASSIUM TALLATE TRIETHANOLAMINE	61790-44-1 102-71-6	>30% < 1.0 %	None established	MG/M3

#### III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION: May cause eye irritation.

POSSIBLE ROUTES OF ENTRY: Eye contact. Skin contact. Inhalation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: May be moderately irritating to eyes. SKIN: May be mildly ACUTE: irritating to skin. INGESTION: May be irritating to mouth, throat

and stomach. INHALATION: May be irritating to nose, throat and

respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Persons with pre-existing

skin disorders may be more susceptible to irritating effects.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes

IV. FIRST AID MEASURES

Flush immediately with plenty of water. If irritation persists, EYES:

get medical attention.

Flush immediately with plenty of water for at least 15 minutes. SKIN:

Get medical attention immediately.

Immediately drink one cupful of water or milk. Never give INGESTION:

anything by mouth to an unconscious person. Get medical

attention.

INHALATION: If breathing is affected, remove to fresh air. Get medical

attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): NONE FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire. FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure

breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall

hazard.

PD-7661

2 of 4 Page Revised 2/02/04 Replaces 9/04/03

Printed 2/03/04

MSDS ID: 3104278

# VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

### VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing and footwear before reuse. Wash thoroughly after handling. Do not breathe vapors or spray mists. FOR COMMERCIAL & INDUSTRIAL USE ONLY Protect from freezing. Store in a dry, cool and well-ventilated place with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

### VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: No special requirements under normal use conditions. PROTECTIVE GLOVES: No special requirements under normal use conditions. RESPIRATORY PROTECTION: No special protective equipment is required. OTHER PROTECTIVE CLOTHING/EQUIPMENT: No special protective clothing is required.

ENGINEERING CONTROLS:

VENTILATION: No special ventilation requirements. General room ventilation is adequate.

### IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear amber liquid, mild soap odor.

BOILING POINT (DEG F): >200 FREEZING POINT: N/D

SPECIFIC GRAVITY/BULK DENSITY: 1.06

10 pH 1% SOLUTION: 10.77

VOLATILE BY VOLUME: 20.4 SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): N/D at N/D VAPOR DENSITY: N/D

## X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of

carbon

HAZARDOUS POLYMERIZATION: None known.

3 of 4 Page Revised 2/02/04 Replaces 9/04/03 Printed 2/03/04

MSDS ID: 3104278

PD-7661

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Toxicological testing has not been performed on the

product. Listed below is the available toxicology

test data for components of the product.

TOXICITY TEST DATA:

Triethanolamine:

Acute Oral LD50 >4000 mg/kg(rat) Acute Dermal LD50 (rabbit) >2000 mg/kg

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Adjust pH of diluted product and discharge to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container according to product labeling or Federal, State or local regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 21 Lb/Gal VOC: 1.86

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

ACUTE: YES CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

IARC: NO OSHA: NO NTP: NO

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: A

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY: 0 SPECIAL: NONE

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS# 7732-18-5

PROPYLENE GLYCOL - CAS# 57-55-6

POTASSIUM TALLATE - CAS# 61790-44-1

ALCOHOL ETHOXYLATE - CAS 69227-21-0

PD-7661

Page 4 of 4
Revised 2/02/04
Replaces 9/04/03
Printed 2/03/04

MSDS ID: 3104278

XV. REGULATORY INFORMATION (Cont.)

TRIETHANOLAMINE - CAS# 102-71-6 CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

#### XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.