

MATERIAL SAFETY DATA SHEET



MSDS ID: 3109

I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: PERMA-GARD 3028

USE: Phosphatizer

SUPPLIER: **EMERGENCY PHONE:**

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: D1A E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: mineral acid **CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Nitric acid	10-30	007697-37-2	LC50 49 ppm/4H	inh/rat
Phosphoric acid	15-40	007664-38-2	LD50 1530 mg/kg	oral/rat
Nickel Nitrate	1-5	013138-45-9	not available	n/a
Zinc Nitrate	10-30	010196-18-6	not available	n/a
Ammonium bifluoride	0.5-1.5	001341-49-7	LD50 130 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: natural rubber or neoprene Eve: Footwear: safety goggles not required

Respiratory: If mists are generated, use NIOSH approved Other: rubber apron

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. Do not breathe mist, spray or vapours.

VENTILATION REQUIREMENTS: Local exhaust ventilation.

INCOMPATIBILITY (Material to Avoid): Alkaline and chlorinated materials.

17.5

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Neutralize with sodium bicarbonate, sodium

carbonate or lime. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

VAPOUR DENSITY (air=1):

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1760

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Hazy green liquid; Acetic Acid

S.G. / BULK DENSITY(g/cc): (concentrate): < 1.0 VAPOUR PRESSURE (mmHg):

ODOUR THRESHOLD: not available **BOILING POINT:** 100°C

FREEZING POINT: not available PERCENT VOLATILE: 60%

SOLUBILITY IN WATER: soluble **EVAPORATION RATE (water=1):** approx. 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

not available

Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly. INGESTION: INHALATION: Corrosive. Inhalation of spray or mist may cause severe respiratory irritation. LC50 (calculated): LD50 (calculated): 130 mg/kg not available OTHER TOXIC EFFECTS: Breathing vapours may cause delayed lung injury. Phosphoric acid TWA 1 mg/m3, STEL 3 mg/m3; Nitric acid TWA 5 mg/m3, STEL 10 mg/m3 **EFFECTS OF CHRONIC** not available **EXPOSURE TO MATERIAL: VI - FIRST AID MEASURES** EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately. **INHALATION:** Remove patient to fresh air. Get medical attention for any breathing difficulty. VII - FIRE AND EXPLOSION DATA FLAMMABLE: No. Contact with metals forms flammable hydrogen gas. FLASH POINT, °C: not applicable **AUTO IGNITION TEMPERATURE,°C:** N/Ap **EXTINGUISHING MEDIA:** Dry Chemical [x] Carbon Dioxide [x] Water [x] Foam [x] Other [] SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus. HAZARDOUS COMBUSTION PRODUCTS: not applicable. **EXPLOSIVE SENSITIVITY TO:** not applicable VIII - REACTIVITY DATA Unstable [] STABILITY: Stable [x] CONDITIONS TO AVOID: Contact with soft metals. INCOMPATIBILITY (Material to Avoid): Alkaline and chlorinated materials. Aluminium, brass, copper, iron, mild steel. Organic materials. HAZARDOUS DECOMPOSITION PRODUCTS: Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic materials will generate heat. REACTIVITY: not dangerously reactive **IX - MSDS PREPARATION** SOURCES USED: PREPARED BY: RTFCS JohnsonDiversev Canada. Inc. Regulatory Department Industrial Division PREPARATION DATE: April 15, 2003 Phone (905) 829-1200 Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada

assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.