



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 32660

PRODUCT NAME: UC24 HEAVY DUTY FLOOR CLEANER**USE:** Floor Cleaner**SUPPLIER:**JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada**EMERGENCY PHONE:****1-800-668-7171****WHMIS CLASSIFICATION:** D2B**CHEMICAL FAMILY:** Surfactant/Solvent**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Tetrasodium edta	3-7	000064-02-8	LD50 3200 mg/kg	oral/rat
Propylene glycol monomethyl ether	7-13	000107-98-2	LD50 5660 mg/kg	oral/rat
Alkyl polyglycoside	3-7	068515-73-1	LD50 5000 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:**Gloves:** Natural Rubber, Neoprene or Nitrile **Eye:** safety glasses **Footwear:** not required**Respiratory:** not required **Other:** not required**SPECIAL HANDLING PROCEDURES AND EQUIPMENT:** Avoid eye and skin contact.**VENTILATION REQUIREMENTS:** general ventilation**INCOMPATIBILITY (Material to Avoid):** Contact with cationic materials causes inactivation.**SPILL PROCEDURES:** Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.**WASTE DISPOSAL:** Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear dark green liquid**S.G. / BULK DENSITY(g/cc):** 1.04**pH:** 11.2**VAPOUR PRESSURE (mmHg):** not available**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** not available**BOILING POINT:** approx. 100°C**FREEZING POINT:** approx. 0°C**PERCENT VOLATILE:** 74%**SOLUBILITY IN WATER:** soluble**EVAPORATION RATE (water=1):** approx. 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** May cause severe irritation.**SKIN:** Repeated or prolonged contact may result in irritation.**INGESTION:** May cause irritation of the digestive tract.**INHALATION:** No serious or irreversible effects expected.

LD50 (calculated): 23,100 mg/kg		LC50 (calculated): not applicable	
OTHER TOXIC EFFECTS: TLV (Propylene glycol methyl ether): 25 ppm ceiling.			
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: none known			
VI - FIRST AID MEASURES			
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.			
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.			
INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.			
INHALATION: Remove patient to fresh air.			
VII - FIRE AND EXPLOSION DATA			
FLAMMABLE: No			
FLASH POINT, °C: none		AUTO IGNITION TEMPERATURE, °C: N/Ap	
EXTINGUISHING MEDIA: Water [X] Dry Chemical [X] Carbon Dioxide [X] Foam [X] Other []			
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.			
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, nitrogen.			
EXPLOSIVE SENSITIVITY TO: not applicable			
VIII - REACTIVITY DATA			
STABILITY: Stable [X] Unstable []			
CONDITIONS TO AVOID: not applicable			
INCOMPATIBILITY (Material to Avoid) : Oxidizing materials.			
HAZARDOUS DECOMPOSITION PRODUCTS: Heat released on contact with oxidizing materials.			
REACTIVITY: not dangerously reactive			
IX - MSDS PREPARATION			
SOURCES USED: RTECS		PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200	
PREPARATION DATE: May 26, 2003			
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.			