

MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 3409

PRODUCT NAME: DUROCLEAN 1256

USE: Soak Tank Cleaner for Cast Aluminum

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: D2B E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: alkali CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

i e e e e e e e e e e e e e e e e e e e				
HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Sodium metasilicate	5-10	006834-92-0	LD50 1153 mg/kg	oral/rat
Sodium silicate	1-5	001344-09-8	LD50 3300 mg/kg	oral/rat
Sodium nitrilotriacetate	1-5	005064-31-3	LD50 1100 mg/kg	oral/rat
Alcohol ethoxylate	3-7	068439-46-3	LD50 1400 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Natural Rubber or Neoprene Eye: safety glasses Footwear: not required

Respiratory: If mists are generated, use NIOSH approved **Other:** not required

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. Do not breathe mist or spray.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): acidic materials

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.

Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid freezing.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear yellow liquid

S.G. / BULK DENSITY(g/cc): 1.13 pH: (concentrate) 12.8

VAPOUR PRESSURE (mmHg): not available VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: not available BOILING POINT: approx. 100°C

FREEZING POINT: 0°C PERCENT VOLATILE: 70%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

SKIN: Repeated or prolonged contact may result in irritation.

INGESTION: May cause severe irritation of the digestive tract.

INHALATION: Breathing spray or mist may cause respiratory irritation. LC50 (calculated): LD50 (calculated): 7305 mg/kg Not available **OTHER TOXIC EFFECTS:** TLV: Sodium silicate 5 mg/m3; Sodium metasilicate 2 mg/m3. **EFFECTS OF CHRONIC** This product contains NTA. In laboratory tests, rats and mice continuously fed highly exaggerated doses of NTA showed evidence of urinary tract (bladder and kidney) toxicity, including cancer; lower doses showed none of **EXPOSURE TO MATERIAL:** these toxic effects. By ACGIH guidelines, NTA would not be considered an occupational (human) carcinogen of any practical significance. **VI - FIRST AID MEASURES** EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a INHALATION: Remove patient to fresh air. VII - FIRE AND EXPLOSION DATA FLAMMABLE: No FLASH POINT, °C: not applicable **AUTO IGNITION TEMPERATURE,°C:** N/Ap **EXTINGUISHING MEDIA:** Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other [] SPECIAL FIRE FIGHTING PROCEDURES: not required **HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon, nitrogen. **EXPLOSIVE SENSITIVITY TO:** not applicable **VIII - REACTIVITY DATA** STABILITY: Stable [x] Unstable [] **CONDITIONS TO AVOID:** high temperature INCOMPATIBILITY (Material to Avoid): acidic materials Heat released on contact with acids. HAZARDOUS DECOMPOSITION PRODUCTS: REACTIVITY: not dangerously reactive **IX - MSDS PREPARATION** SOURCES USED: **RTECS** PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Industrial Division PREPARATION DATE: April 15, 2003 Phone (905) 829-1200

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.