



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 4702

PRODUCT NAME: **LEVER TECH COLOR SAFE STAIN REMOVER**

USE: Laundry Oxygen Bleach

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: C E F

CHEMICAL FAMILY: Oxidizer

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: Hydrogen peroxide, 35%

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Hydrogen peroxide	15-40	007722-84-1	LD50 2000 mg/kg	oral/ mouse

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: impermeable gloves

Eye: safety goggles and/or face shield

Footwear: rubber footwear

Respiratory: If mists are generated, use NIOSH approved mask

Other: rubber apron

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. If conditions exceed TLV (ppm) NIOSH approved respirator is required.

VENTILATION REQUIREMENTS: general ventilation.

INCOMPATIBILITY (Material to Avoid): Contact with most organic or readily oxidizable materials and combustibles cause fire and explosion. Contact with many metals or their salts causes rapid decomposition with evolution of oxygen and heat.

SPILL PROCEDURES: Remove all sources of ignition. Stop and contain spill. Collect for disposal.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Store away from contaminants and heat sources.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, colourless, liquid with a slightly sharp odour

S.G. / BULK DENSITY(g/cc): 1.132

pH: as is 3.0 - 3.5

VAPOUR PRESSURE (mmHg): 18-24 @30°C

VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: not applicable

BOILING POINT: 108°C

FREEZING POINT: -33°C

PERCENT VOLATILE: 100%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): above 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: Corrosive. The sudden evolution of oxygen may cause injury by acute distention of the esophagus or stomach and may cause internal bleeding.

INHALATION: Breathing mist or vapour may cause respiratory irritation. Toxic. May cause death.

LD50 (calculated): 5714 mg/kg		LC50 (calculated): 1547 ppm - 4 hrs.	
OTHER TOXIC EFFECTS: Severe irritant. May cause corrosive tissue damage.			
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: None known.			
VI - FIRST AID MEASURES			
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.		
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.		
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.		
INHALATION:	Remove patient to fresh air. Get medical attention for any breathing difficulty.		
VII - FIRE AND EXPLOSION DATA			
FLAMMABLE: No			
FLASH POINT, °C: not applicable		AUTO IGNITION TEMPERATURE, °C: N/Ap	
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []			
SPECIAL FIRE FIGHTING PROCEDURES:		Use water to extinguish only if large volumes are available to flood area. Wear self-contained breathing apparatus. Can cause ignition of combustible or oxidizable materials on contact. May decompose violently on contact with metals or their salts, dusts or other contaminants.	
HAZARDOUS COMBUSTION PRODUCTS:		not applicable.	
EXPLOSIVE SENSITIVITY TO: Impact [] Static Discharge [] Heat [x] Other []			
VIII - REACTIVITY DATA			
STABILITY: Stable [] Unstable [x]			
CONDITIONS TO AVOID: High temperature. High temperature may facilitate detonation.			
INCOMPATIBILITY (Material to Avoid) :		Contact with organic or readily oxidizable materials causes fire and explosions. Contact with many metals causes rapid decomposition with evolution of oxygen and heat.	
HAZARDOUS DECOMPOSITION PRODUCTS:		Decomposition causes evolution of oxygen and heat.	
REACTIVITY:		Can cause ignition of combustible or oxidizable materials on contact. May decompose violently on contact with metals or their salts, dusts or other contaminants.	
IX - MSDS PREPARATION			
SOURCES USED: RTECS, MSDS, Hydrogen Peroxide 30%		PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division Phone (905) 829-1200	
PREPARATION DATE: April 15, 2003			
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.			