



## **MATERIAL SAFETY DATA SHEET**



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 57249						
PRODUCT NAME: SUMA SUPER L1						
USE: Mechanical warewashing detergent						
SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada		EMERGENCY PHONE: 1-800-668-7171				
WHMIS CLASSIFICATION:    D2B    E      CHEMICAL FAMILY:    Chlorinated Alkali			TRADE NAME / SYNONYMS:    not applicable      CHEMICAL NAME:    not applicable			
II - HAZARDOUS INGREDIENTS						
HAZARDOUS INGREDIENT	% w/w	1	CAS #	LD50 / LC50	Route / Species	
Potassium hydroxide Sodium hypochlorite	7-13 1-5		001310-58-3 007681-52-9	LD50 365 mg/kg LD50 375 mg/kg	oral/rat oral/rat	
III - HANDLING AND DISPOSAL PROCEDURES						
PERSONAL PROTECTIVE EQUIPMENT:      Gloves:    Natural rubber, neoprene or nitrile    Eye:    Safety goggles    Footwear:    As required      Respiratory:    Not normally required.    Other:    Not normally required.      SPECIAL HANDLING PROCEDURES AND EQUIPMENT:    Avoid eye and skin contact. If mists are generated, use NIOSH approved mask.      VENTILATION REQUIREMENTS:    General ventilation.      INCOMPATIBILITY (Material to Avoid):    Acids, ammonia, urea, amines and soft metals.      SPILL PROCEDURES:    Wear protective clothing. Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.      WASTE DISPOSAL:    Dispose according to municipal, provincial, and federal regulations.      STORAGE / SHIPPING REQUIREMENT:    Store in a cool dry area in a closed container.      UN1814    IV - PHYSICAL PROPERTIES						
APPEARANCE / ODOUR: Clear pale yellow liquid - chlorine odour						
S.G. / BULK DENSITY(g/cc): not available VAPOUR PRESSURE (mmHg): not available ODOUR THRESHOLD: 0.2-0.4 ppm chlorine FREEZING POINT: not available SOLUBILITY IN WATER: soluble		pH:    not available      VAPOUR DENSITY (air=1):    not available      BOILING POINT:    approx. 100°C      PERCENT VOLATILE:    approx. 77%      EVAPORATION RATE (water=1):    1				
V - TOXICOLOGICAL PROPERTIES						
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:      EYES:    Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.      SKIN:    Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.      INGESTION:    Corrosive. May cause severe irritation of the digestive tract. May cause permanent damage if not treated promptly.      INHALATION:    Corrosive. Inhalation of spray or mist may cause severe respiratory irritation.      LD50 (calculated):    3171 mg/kg						

OTHER TOXIC EFFECTS: TLV-CL (potassium hydroxide) 2 mg/m3; TLV-TWA (Cl2) 0.5 ppm, STEL 1 ppm						
EFFECTS OF CHRONIC  none known    EXPOSURE TO MATERIAL:						
VI - FIRST AID MEASURES						
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.						
SKIN: Flush affected area thoroughly with water. If irritation devel	Flush affected area thoroughly with water. If irritation develops, contact a physician.					
<b>INGESTION:</b> Drink large volumes of water . Never give anything by mou physician immediately.						
<b>INHALATION:</b> Remove patient to fresh air. Get medical attention for any breathing difficulty.						
VII - FIRE AND EXPLOSION DATA						
FLAMMABLE: No						
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE,°C: N/Ap					
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []						
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.						
HAZARDOUS COMBUSTION PRODUCTS: Chlorine gas and oxygen released when heated.						
EXPLOSIVE SENSITIVITY TO: not applicable						
VIII - REACTIVITY DATA						
STABILITY: Stable [ ] Unstable [x]						
CONDITIONS TO AVOID: Chlorine loss accelerated at high temperature and when exposed to light.						
INCOMPATIBILITY (Material to Avoid) : Acids, ammonia, urea, amines and soft metals.						
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with acid generates heat and chlorine gas. Contact with ammonia, urea and amines produces nitrogen gas and chloramines. Contact with soft metals forms flammable hydrogen gas.						
REACTIVITY: not dangerously reactive						
IX - MSDS PREPARATION						
SOURCES USED: RTECS, ChemInfo	PREPARED BY: JohnsonDiversey Canada, Inc.					
	Regulatory Department					
PREPARATION DATE: April 15, 2003	Institutional Division Phone (905) 829-1200					
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.						