



MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 57265					
PRODUCT NAME: SUMA GRILL D9					
USE: Oven & grill cleaner					
SUPPLIER: JohnsonDiversey Canada, Inc. 2401 Bristol Circle Oakville Ontario, L6H 6P1, Canada		EMERGENCY PHONE: 1-800-668-7171			
WHMIS CLASSIFICATION: E CHEMICAL FAMILY: Caustic Alkali		TRADE NAME / SYNONYMS: not applicable CHEMICAL NAME: not applicable			
II - HAZARDOUS INGREDIENTS					
HAZARDOUS INGREDIENT	% w/w		CAS #	LD50 / LC50	Route / Species
Sodium hydroxide Dipropylene glycol methyl ether	7-13 3-7		001310-73-2 034590-94-8	LDLo 500 mg/kg LD50 5180 mg/kg	oral/rab oral/rat
III - HANDLING AND DISPOSAL PROCEDURES					
Respiratory: If mists are generated, use NIOSH approved mask SPECIAL HANDLING PROCEDURES AND EQUIPMENT: VENTILATION REQUIREMENTS: General ventilation INCOMPATIBILITY (Material to Avoid): Acids, aluminum of SPILL PROCEDURES: Wear protective clothing. Contain the Mop up or soak up with absorbent of WASTE DISPOSAL:	Avoid eye a r other soft r he spill. Do r clay for disp ial, and fede	Not no nd skin o netals. not allow osal. ral regula	the spilled product to	go to drain. Neutralize w	vith dilute acid.
IV - Pł	HYSICAL	PROP	ERTIES		
APPEARANCE / ODOUR: Dark brown clear liquid S.G. / BULK DENSITY(g/cc): 1.12 VAPOUR PRESSURE (mmHg): not available ODOUR THRESHOLD: not available FREEZING POINT: approx. 0°C SOLUBILITY IN WATER: soluble V - TOXICOL OGIO			pH: >13.0 VAPOUR DENSITY (air=1): not available BOILING POINT: approx. 100°C PERCENT VOLATILE: 85% EVAPORATION RATE (water=1): 1 CAL PROPERTIES 1		
EFFECTS OF ACUTE EXPOSURE TO MATERIAL:					
EYES: Corrosive. May cause severe irritation. May cause SKIN: Corrosive. May cause severe irritation. May cause INGESTION: Corrosive. May cause severe irritation of the dig INHALATION: Breathing vapours or spray may cause respirate	use permane gestive tract.	ent dama May cau	ge if not treated promp	tly.	
LD50 (calculated): 4815 mg/kg		LC50 (calculated): not applicable			

ropylene Glycol Methyl Ether TWA 606 mg/m3, STEL 909 mg/m3 skin						
EFFECTS OF CHRONIC none known EXPOSURE TO MATERIAL:						
VI - FIRST AID MEASURES						
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.						
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.						
INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.						
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.						
VII - FIRE AND EXPLOSION DATA						
AUTO IGNITION TEMPERATURE,°C: N/Ap						
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []						
SPECIAL FIRE FIGHTING PROCEDURES: Wear protective clothing.						
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.						
VIII - REACTIVITY DATA						
STABILITY: Stable [x] Unstable []						
CONDITIONS TO AVOID: not applicable						
INCOMPATIBILITY (Material to Avoid) : Acids, aluminum, zinc.						
HAZARDOUS DECOMPOSITION PRODUCTS: Heat on contact with acids. Contact with metals forms flammable hydrogen gas.						
REACTIVITY: Not dangerously reactive.						
IX - MSDS PREPARATION						
PREPARED BY: JohnsonDiversev Canada. Inc. Regulatory Department						
Institutional Division Phone (905) 829-1200						
specting Controlled Products under the Hazardous Products Act and is d. JohnsonDiversey Canada assumes no responsibility for injury to any ty procedures are not adhered to. In addition, JohnsonDiversey Canada n any abnormal use or theft of the material, even if reasonable safety erial and should review the data and recommendations in the specific						