

MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 57301

PRODUCT NAME: SUMA PREMIUM SOAK K8.1

USE: Silver presoak

SUPPLIER: EMERGENCY PHONE:

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: E TRADE NAME / SYNONYMS: not applicable

CHEMICAL FAMILY: Caustic Alkali CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Sodium hydroxide	1-5	001310-73-2	LDLo 500 mg/kg	oral/rab
Sodium silicate	1-5	001344-09-8	LD50 3300 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Natural rubber, Neoprene or Nitrile Eye: Safety glasses Footwear: As required

Respiratory: If mists are generated, use NIOSH approved **Other:** Not normally required.

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact.

VENTILATION REQUIREMENTS: General ventilation.

INCOMPATIBILITY (Material to Avoid): Acids

SPILL PROCEDURES: Wear protective clothing. Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with

absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN1824

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear liquid

S.G. / BULK DENSITY(g/cc): 1.22 pH: (1% solution): 12.3

VAPOUR PRESSURE (mmHg): not available VAPOUR DENSITY (air=1): not available

ODOUR THRESHOLD: 0.2-0.4 ppm chlorine **BOILING POINT:** approx. 100°C

FREEZING POINT: approx. 0°C PERCENT VOLATILE: approx. 78%

SOLUBILITY IN WATER: soluble EVAPORATION RATE (water=1): approx. 1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause permanent damage if not treated promptly.

INHALATION: Breathing vapours may cause respiratory irritation.

LD50 (calculated): 5247 mg/kg LC50 (calculated): not applicable

OTHER TOXIC EFFECTS: TLV-CL (Sodium hydroxide): 2 mg/m3; TLV (Sodium silicate): 5 mg/m3. EFFECTS OF CHRONIC **EXPOSURE TO MATERIAL:** none known **VI - FIRST AID MEASURES** EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately. SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. INGESTION: Drink large volumes of water. Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately. INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty. VII - FIRE AND EXPLOSION DATA FLAMMABLE: Nο FLASH POINT, °C: **AUTO IGNITION TEMPERATURE,°C:** not applicable N/Ap **EXTINGUISHING MEDIA:** Other [] Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Wear self-contained breathing apparatus. SPECIAL FIRE FIGHTING PROCEDURES: HAZARDOUS COMBUSTION PRODUCTS: None known **EXPLOSIVE SENSITIVITY TO:** not applicable **VIII - REACTIVITY DATA** STABILITY: Unstable [] Stable [x] CONDITIONS TO AVOID: Avoid freezing INCOMPATIBILITY (Material to Avoid) : Acids HAZARDOUS DECOMPOSITION PRODUCTS: Contact with acid generates heat. REACTIVITY: not dangerously reactive IX - MSDS PREPARATION SOURCES USED: PREPARED BY: RTECS, ChemInfo JohnsonDiversey Canada, Inc. Regulatory Department Institutional Division PREPARATION DATE: April 15, 2003 Phone (905) 829-1200 Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.