
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

TRACK CLEAN**MSDS ID: 57307**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: TRACK CLEAN

Product Descriptor: CONVEYOR LUBRICANT

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
ALCOHOL ETHOXYLATE	68131-39-5	5 - 15%	Not Established	
N-ALKYLDIMETHYL BENZYLAMMONIUM CHLORIDE	68391-01-5	1 - 5%	None est.	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Contains chemicals that cause irritation to eyes and skin. May be harmful if swallowed. Wear eye protection, clothing and rubber gloves to prevent prolonged skin contact. Wash after handling.

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe irritation with redness, pain and swelling. SKIN: Irritation with dryness or itching may develop with pain and redness. INGESTION: If swallowed, gastric distress, diarrhea, nausea and vomiting may occur. INHALATION: May cause irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

INGESTION: Do not take internally. If swallowed, drink several glasses of water. Do not induce vomiting. Contact a physician or Poison Control Center. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air and seek medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): None

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: N/E

UEL: N/E

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.

TRACK CLEAN

MSDS ID: 57307

V. FIRE FIGHTING MEASURES (Cont.)

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool dry area. Keep from freezing. If frozen, thaw and mix to make usable. Do not pressurize container to empty. Keep container closed when not in use.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.

PROTECTIVE GLOVES: Liquid proof gloves.

RESPIRATORY PROTECTION: Not normally required.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear to pale yellow liquid, soap odor.

BOILING POINT (DEG F):

FREEZING POINT: 32 F

SPECIFIC GRAVITY/BULK DENSITY: 1.00

pH: 6.0

pH 1% SOLUTION: 6.5

VOLATILE BY VOLUME: 80

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 17.5 at 20 C

VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

HAZARDOUS POLYMERIZATION: None known.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

TRACK CLEAN**MSDS ID: 57307**

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

TOXICITY TEST DATA:

Linear Alcohol Ethoxylate (CAS# 68131-39-5):

Acute Oral LD50 rat 1800 mg/kg

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 1.0 Lb/Gal VOC: 0.08

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

ACUTE:NO CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 1 FIRE: 0 REACTIVITY:0 SPECIAL:None

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

LINEAR ALCOHOL ETHOXYLATE - CAS #68131-39-5

BENZALKONIUM CHLORIDE - CAS #68391-01-5

SODIUM LAURYL SARCOSINATE - CAS #137-16-6

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE - CAS #64-02-8

CALIFORNIA PROPOSITION 65:

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

TRACK CLEAN

MSDS ID: 57307

XV. REGULATORY INFORMATION (Cont.)

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.