



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 57408

PRODUCT NAME: ACIFOAM LP

USE: Acidic foam cleaner-descaler

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: D2B E

CHEMICAL FAMILY: mineral acid

TRADE NAME / SYNONYMS: not applicable

CHEMICAL NAME: not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Sulphuric acid	1-5	007664-93-9	LD50 2140 mg/kg	oral/rat
Phosphoric acid	15-40	007664-38-2	LD50 1530 mg/kg	oral/rat
Linear alcohol ethoxylate	1-5	068002-97-1	LD50 2750 mg/kg	oral/rat
Sodium olefin sulphonate	1-5	068439-57-6	LD50 1266 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: Neoprene, Nitrile

Eye: Safety goggles

Footwear: As required

Respiratory: If mists are generated, use NIOSH approved mask

Other: Rubber apron

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Do not breathe mist, spray or vapours. Avoid eye and skin contact.

VENTILATION REQUIREMENTS: Mechanical exhaust

INCOMPATIBILITY (Material to Avoid): Alkaline and chlorinated materials. Organic materials. Soft metals

SPILL PROCEDURES: Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. UN3264

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, red liquid

S.G. / BULK DENSITY(g/cc): 1.19

pH: < 1.0

VAPOUR PRESSURE (mmHg): not applicable

VAPOUR DENSITY (air=1): not applicable

ODOUR THRESHOLD: not available

BOILING POINT: 100°C

FREEZING POINT: not available

PERCENT VOLATILE: 65%

SOLUBILITY IN WATER: soluble

EVAPORATION RATE (water=1): not applicable

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: Corrosive. May cause severe irritation. May cause permanent damage if not treated promptly.

SKIN: Corrosive. May cause severe irritation. May cause temporary or permanent damage if not treated promptly.

INGESTION: Corrosive. May cause severe irritation of the digestive tract. May cause temporary or permanent damage if not treated promptly.

INHALATION: May cause irritation of respiratory tract.	
LD50 (calculated): 4581mg/kg	LC50 (calculated): not available
OTHER TOXIC EFFECTS: TLV-TWA 1 mg/m3 as Sulphuric Acid. IARC has classified "occupational exposure to strong acid mists containing sulphuric acid" as being carcinogenic to humans. The route of entry is inhalation of these mists that may result in respiratory (laryngeal) cancers. There is no evidence that the liquid is in any way a carcinogen.	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: not available	
VI - FIRST AID MEASURES	
EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician immediately.	
SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.	
INGESTION: Drink large volumes of water. Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.	
INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.	
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: No.	
FLASH POINT, °C: not applicable	AUTO IGNITION TEMPERATURE, °C: N/Ap
EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and sulfur. Hydrogen sulfide.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: not applicable.	
INCOMPATIBILITY (Material to Avoid) : Alkaline and chlorinated materials. Aluminium, brass, copper, iron, mild steel. Organic materials.	
HAZARDOUS DECOMPOSITION PRODUCTS: Contact with chlorinated materials will release chlorine gas. Contact with alkali will generate heat. Contact with soft metals forms flammable hydrogen gas. Contact with organic materials will generate heat.	
REACTIVITY: not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, Industrial Chemicals Safety Manual	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Food Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.	