MATERIAL SAFETY DATA SHEET

TENDEC VC87

Page 1 of 4 Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 57411

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: TENDEC VC87

Product Descriptor: WETTING AND FOAM CONTROL ADDITIVE

MANUFACTURER: JOHNSONDIVERSEY, INC. EMERGENCY PHONE NUMBER: (800)851-7145

3630 E. KEMPER ROAD CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name CAS Number % Exposure Limits Units

NONE

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION - Contains cleaning agents that may cause eye irritation. May be harmful if swallowed. Do not get in eyes. Do not take internally. POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Irritation with pain, swelling and redness may develop.

SKIN: Irritation or dryness develops with long contact. INGESTION: If swallowed, gastric distress, diarrhea, nausea and vomiting may

occur. INHALATION: May cause irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive

skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes

IV. FIRST AID MEASURES

EYES: SKIN: Immediately flush with plenty of water. Get medical attention.

Rinse off product and wash with mild soap and water.

INGESTION: Do not take internally. If swallowed, drink several glasses of

water. Do not induce vomiting. Contact a physician or Poison

Control Center. NOTE: Never give fluids by mouth to an

unconscious person.

INHALATION: Remove to fresh air and seek medical attention.

V. FIRE FIGHTING MEASURES

FLAME EXTENSION: N/A FLASH POINT (degrees F): >400 FLASH POINT (degrees F): >400 FLAME EXTENSION: N/A FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure

breathing apparatus SCBA) in fire area.

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

MATERIAL SAFETY DATA SHEET

TENDEC VC87

Page 2 of 4 Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 57411

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool dry area. Keep from freezing. If frozen, thaw and mix to make usable. Do not pressurize container to empty. Keep container closed when not in use.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.

PROTECTIVE GLOVES: Liquid proof rubber or neoprene gloves. Avoid cotton, wool and leather.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear, colorless liquid, musty odor.

BOILING POINT (DEG F): 214 F FREEZING POINT: <40 F

SPECIFIC GRAVITY/BULK DENSITY: 1.044

pH: 6.3 pH 1% SOLUTION: 6.5%

VOLATILE BY VOLUME: 45%

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 17.5 at 20 C VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents; Chlorine and

chlorinated compounds

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of

carbon

HAZARDOUS POLYMERIZATION: None known.

MATERIAL SAFETY DATA SHEET

TENDEC VC87

Page 3 of 4 Revised 2/02/04 Replaces 8/12/03 Printed 2/03/04

MSDS ID: 57411

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: No data available.

TOXICITY TEST DATA: No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 5% Lb/Gal VOC: 0.43

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

ACUTE:YES CHRONIC:NO FIRE:NO REACTIVITY:NO

SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 1 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 0 FIRE: 1 REACTIVITY: 0 SPECIAL: None

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

PROPYLENE GLYCOL - CAS #57-55-6

ALCOHOL ETHOXYLATE - CAS #9003-11-6

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

MSDS ID: 57411

TENDEC VC87

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.