
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE PLE VL3**MSDS ID: 57415**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: DICOLUBE PLE VL3
Product Descriptor: STRESS-CRACK FREE CONVEYOR LUBRICANT
MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
ALKYLATED NAPHTHALENE SULFONATE, SODIUM SALT	PROPRIETARY	15 - 30%	None established	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION - Contains cleaning agents that may cause eye irritation. May be harmful if swallowed. Do not get in eyes. Do not take internally.
POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Causes eye irritation. SKIN: Irritation or dryness develops with long contact. INGESTION: May cause nausea and diarrhea.
INHALATION: May cause irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. Get medical attention.
SKIN: Rinse off product and wash with mild soap and water.
INGESTION: Do not take internally. If swallowed, drink several glasses of water. Do not induce vomiting. Contact a physician or Poison Control Center. NOTE: Never give fluids by mouth to an unconscious person.
INHALATION: Remove to fresh air. If breathing difficulties arise, get medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): >400F FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Product may burn if liquid is evaporated by heat or fire. Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE PLE VL3

MSDS ID: 57415

V. FIRE FIGHTING MEASURES (Cont.)

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.

PROTECTIVE GLOVES: Alkali resistant.

RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear light yellow liquid, mild amine odor.

BOILING POINT (DEG F): 216 F

FREEZING POINT: N/D

SPECIFIC GRAVITY/BULK DENSITY: 1.03

pH: 8.0

pH 1% SOLUTION: 8.0%

VOLATILE BY VOLUME: 56%

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 17.5 at 20C

VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Oxidizing agents; Chlorine and chlorinated compounds

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of carbon; oxides of sulfur; oxides of nitrogen

HAZARDOUS POLYMERIZATION: None known.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE PLE VL3

MSDS ID: 57415

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: No data available.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: none

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 1 FIRE: 0 REACTIVITY: 0 SPECIAL: None

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

ALKYLATED NAPHTHALENE SULFONATE, SODIUM SALT - PROPRIETARY

COCOAMINE ETHOXYLATE - 61791-14-8

SODIUM TALLATE - CAS #61790-45-2

COCONUT FATTY ACID - CAS #61788-47-4

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE PLE VL3

MSDS ID: 57415

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.