
MATERIAL SAFETY DATA SHEET

Page 1 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE SUPER PET VL2**MSDS ID: 57480**

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: DICOLUBE SUPER PET VL2

Product Descriptor: SOAP BASED PET SAFE CONVEYOR LUBRICANT

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
ETHYLENEDIAMINE TETRAACETIC ACID, TETRAPOTASSIUM SALT	5964-35-2	1 - 5%	None est.	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION - Contains cleaning agents that may cause eye irritation. Prolonged contact with undiluted product may cause skin irritation. May be harmful if swallowed. Avoid contact with eyes, skin, or clothing.

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Causes eye irritation. SKIN: Irritation or dryness develops with long contact. INGESTION: None known. INHALATION: None known.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis or sensitive skin.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes and skin.

IV. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. Get medical attention.

SKIN: Rinse off product and wash with mild soap and water.

INGESTION: Do not take internally. If swallowed, drink several glasses of water. Do not induce vomiting. Contact a physician or Poison Control Center. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air. If breathing difficulties arise, get medical attention.

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): None

FLAME EXTENSION: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LEL: N/E

UEL: N/E

UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.

EXTINGUISHING MEDIA: Water, water spray, CO2, foam or dry powder.

FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus (SCBA) in fire area.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE SUPER PET VL2

MSDS ID: 57480

V. FIRE FIGHTING MEASURES (Cont.)

SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:

Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.

This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool dry area. Keep from freezing. If frozen, thaw and mix to make usable. Do not pressurize container to empty. Keep container closed when not in use.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.

PROTECTIVE GLOVES: Liquid proof rubber or neoprene gloves. Avoid cotton, wool and leather.

RESPIRATORY PROTECTION: Not normally required.

OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.

ENGINEERING CONTROLS:

VENTILATION: None required.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear, amber, foaming liquid.

BOILING POINT (DEG F): 212F

FREEZING POINT: <32F

SPECIFIC GRAVITY/BULK DENSITY: 1.06

pH: 10.4 - 11

pH 1% SOLUTION: 9 - 10

VOLATILE BY VOLUME: 70%

SOLUBILITY IN WATER: Soluble

VAPOR PRESSURE(mmHg): 17.5 at 20C

VAPOR DENSITY: 17.3

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None known. oxides of carbon; oxides of sulfur

HAZARDOUS POLYMERIZATION: None known.

MATERIAL SAFETY DATA SHEET

Page 3 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE SUPER PET VL2

MSDS ID: 57480

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: No data available.

TOXICITY TEST DATA:

No data available.

XII. ECOLOGICAL INFORMATION

ECOTOXICITY TEST DATA:

No data available.

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Adjust pH of diluted product and discharge to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container according to product labeling or Federal, State or local regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: NO REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 1 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

NFPA RATING: HEALTH: 0 FIRE: 0 REACTIVITY: 0 SPECIAL: None

STATE RIGHT-TO-KNOW INFORMATION:

TETRAPOTASSIUM ETHYLENEDIAMINE TETRAACETATE - CAS #5964-35-2

NONIONIC ACID, POTASSIUM SALT - CAS #23282-34-0

ALKYL CARBOXYLIC ACID, POTASSIUM SALT - CAS #67701-09-1

SODIUM ALPHA OLEFIN SULFONATE - CAS #68439-57-6

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

DICOLUBE SUPER PET VL2

MSDS ID: 57480

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.