

FILLERCLEAN VK12

MSDS ID: 57500

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: FILLERCLEAN VK12

Product Descriptor: ALKALINE DETERGENT FOR EXTERIOR FILLER CLEANING

MANUFACTURER: JOHNSON DIVERSEY, INC. EMERGENCY PHONE NUMBER: (800) 851-7145
3630 E. KEMPER ROAD
CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
TETRASODIUM ETHYLENE DIAMINE	64-02-8	1 - 5%	None established	
TETRAACETATE				
TRIETHANOLAMINE	102-71-6	1 - 5%	TWA 5	MG/M3

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Product contains irritating or harmful chemicals which cause eye or skin irritation or burns. May be harmful if swallowed. Do not get product in eyes, on skin or clothing. Wear eye protection and rubber gloves to prevent skin contact when handling product. Wash after handling. Avoid breathing dust, vapors or product spray.

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Severe irritation with redness, pain and swelling. SKIN: Irritation with dryness or itching may develop with pain and redness. INGESTION: If swallowed, pain, nausea and vomiting may result. INHALATION: Causes irritation of respiratory tract.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin, respiratory tract, and gastrointestinal tract.

IV. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention.

SKIN: Flush thoroughly with plenty of water. Wash with mild soap and water. Remove contaminated clothes and shoes and clean before reuse. Get medical attention for any painful, red or injured skin.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air and seek medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FILLERCLEAN VK12**MSDS ID: 57500**

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): None FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
Liquid produces hydrogen on contact with soft, active metals.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Contain spill. Wear protective clothing. Soak up or absorb liquid on suitable absorbent material. Collect and place in chemical waste container. Dispose of in accordance with local, State and Federal regulations. Flush spill area with water.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store in a cool, dry area, keep away from acids. Keep container closed when not in use. Wear protective gear when handling or using. Do not pressurize container to empty.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.
PROTECTIVE GLOVES: Alkali resistant.
RESPIRATORY PROTECTION: Product does not have any established exposure limits. NIOSH/MSHA approved respirator recommended in enclosed or confined spaces where high air concentration or long exposure may occur.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.
ENGINEERING CONTROLS:
VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear pale yellow liquid.

BOILING POINT (DEG F): >200F	FREEZING POINT: 32F
SPECIFIC GRAVITY/BULK DENSITY: 1.085	
pH: 12	pH 1% SOLUTION: 11%
VOLATILE BY VOLUME: 84.1%	
SOLUBILITY IN WATER: Soluble	
VAPOR PRESSURE(mmHg): 17.5 at 20C	VAPOR DENSITY: 17.3

FILLERCLEAN VK12

MSDS ID: 57500

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.

INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Aluminum; Soft metals

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of sulfur; oxides of carbon; oxides of nitrogen; oxides of phosphorus

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

TOXICITY TEST DATA:

SODIUM CARBONATE:

Acute Oral LD50 (rat) - 4090 mg/kg (RTECS)

Acute Inhalation LC50 (rat, 2 hr.) - 2.3 mg/l (Env. Res. 31:138 (1983))

Triethanolamine:

Acute Oral LD50 (rat) >4000 mg/kg

Acute Dermal LD50 (rabbit) >2000 mg/kg

XII. ECOLOGICAL INFORMATION

Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

ECOTOXICITY TEST DATA:

Sodium Carbonate:

Acute LC50 (48 Hr.) (Daphnia magna) 265-565 mg/l

Acute LC50 (96 Hr.) (Lepomis macrochirus) 300-325 mg/l

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Adjust pH of diluted product and discharge to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Triple rinse container with water and add to process. Recycle or dispose of container according to product labeling or Federal, State or local regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: None

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

FILLERCLEAN VK12**MSDS ID: 57500**

XV. REGULATORY INFORMATION (Cont.)

Section 313 Toxic Chemicals:

None

SARA Section 311/312:

ACUTE:YES CHRONIC:NO FIRE:NO REACTIVITY:NO
SUDDEN RELEASE OF PRESSURE:NO

LISTED CARCINOGEN: None

NTP: No IARC: No OSHA: No

HMIS RATINGS: HEALTH: 2 FIRE: 0 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: C

NFPA RATING: HEALTH: 2 FIRE: 0 REACTIVITY:0 SPECIAL:Alkali

STATE RIGHT-TO-KNOW INFORMATION:

WATER - CAS #7732-18-5

TETRASODIUM ETHYLENEDIAMINE TETRAACETATE - CAS #64-02-8

SODIUM CARBONATE - CAS #497-19-8

TRIETHANOLAMINE - CAS #102-71-6

SODIUM CUMENE SULFONATE - CAS #28348-53-0

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

DISCLAIMER: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.