

MATERIAL SAFETY DATA SHEET



I - PRODUCT IDENTIFICATION AND USE MSDS ID: 6195

PROPYLENE GLYCOL PRODUCT NAME:

USE: Anti-freeze

SUPPLIER: **EMERGENCY PHONE:**

JohnsonDiversey Canada, Inc.

2401 Bristol Circle

Oakville Ontario, L6H 6P1, Canada

1-800-668-7171

WHMIS CLASSIFICATION: TRADE NAME / SYNONYMS: D2B not applicable

CHEMICAL FAMILY: Glycol **CHEMICAL NAME:** Propylene Glycol

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS#	LD50 / LC50	Route / Species
Propylene glycol	60-100	000057-55-6	LD50 20000 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: natural rubber or neoprene Eve: safety glasses Footwear: not required

If mists are generated, use NIOSH approved Respiratory: Other: not required

mask

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye contact.

VENTILATION REQUIREMENTS: general ventilation

INCOMPATIBILITY (Material to Avoid): acidic and oxidizing materials

SPILL PROCEDURES: Contain the spill. Mop up or soak up with absorbent clay for disposal. Wash spill area with large volumes of water.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, colourless liquid

S.G. / BULK DENSITY(g/cc): pH: not applicable VAPOUR PRESSURE (mmHq): not available VAPOUR DENSITY (air=1): 2.6

ODOUR THRESHOLD: not applicable **BOILING POINT:** 188°C

FREEZING POINT: -60°C PERCENT VOLATILE:

SOLUBILITY IN WATER: soluble **EVAPORATION RATE (water=1):** >1

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation. No serious or irreversible effects expected if treated promptly.

SKIN: Repeated or prolonged contact may result in irritation.

1.04

INGESTION: May cause irritation

INHALATION: No serious or irreversible effects expected.

LD50 (calculated): 20,000 mg/kg LC50 (calculated): not available

OTHER TOXIC EFFECTS: Propylene Glycol TLV 50 ppm AIHA WEEL

EFFECTS OF CHRONIC none known **EXPOSURE TO MATERIAL: VI - FIRST AID MEASURES** EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician. SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician. INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician. INHALATION: Remove patient to fresh air. VII - FIRE AND EXPLOSION DATA FLAMMABLE: No FLASH POINT, °C: **AUTO IGNITION TEMPERATURE,°C:** not applicable N/Ap. **EXTINGUISHING MEDIA:** Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other [] SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus. HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon. **EXPLOSIVE SENSITIVITY TO:** not applicable **VIII - REACTIVITY DATA** STABILITY: Unstable [] Stable [x] **CONDITIONS TO AVOID:** not applicable INCOMPATIBILITY (Material to Avoid): acidic and oxidizing materials HAZARDOUS DECOMPOSITION PRODUCTS: carbon monoxide REACTIVITY: not dangerously reactive IX - MSDS PREPARATION

SOURCES USED: RTECS PREPARED BY: Johnson Diversey Canada, Inc.

Regulatory Department Industrial Division Phone (905) 829-1200

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.

PREPARATION DATE:

April 15, 2003