



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 6841

PRODUCT NAME: MINERAL SPIRITS

USE: Solvent

SUPPLIER:

JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada

EMERGENCY PHONE:

1-800-668-7171

WHMIS CLASSIFICATION: B3 D2B

CHEMICAL FAMILY: Hydrocarbon solvent

TRADE NAME / SYNONYMS: Petroleum Hydrocarbon

CHEMICAL NAME: Petroleum Hydrocarbon

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Petroleum hydrocarbon	60-100	008052-41-3	LD50 6320 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:

Gloves: natural rubber or neoprene

Eye: safety glasses

Footwear: rubber boots

Respiratory: If mists are generated, use NIOSH approved mask

Other: rubber apron

SPECIAL HANDLING PROCEDURES AND EQUIPMENT: Avoid eye and skin contact. Do not breathe mist or spray. Do not expose to heat, spark or open flame.

VENTILATION REQUIREMENTS: mechanical exhaust

INCOMPATIBILITY (Material to Avoid): strong oxidizers

SPILL PROCEDURES: Ensure adequate ventilation. Remove all sources of heat and ignition. Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal. LARGE SPILLS: Dike and pump into suitable containers.

WASTE DISPOSAL: Dispose according to municipal, provincial, and federal regulations.

STORAGE / SHIPPING REQUIREMENT: Store in a cool dry area in a closed container. Avoid excessive heat.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Clear, colourless liquid

S.G. / BULK DENSITY(g/cc): 0.88

pH: not applicable

VAPOUR PRESSURE (mmHg): not available

VAPOUR DENSITY (air=1): 4.8

ODOUR THRESHOLD: not available

BOILING POINT: 150-205°C

FREEZING POINT: not available

PERCENT VOLATILE: 100%

SOLUBILITY IN WATER: insoluble

EVAPORATION RATE (water=1): not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES: May cause irritation.

SKIN: Repeated or prolonged contact may result in drying and cracking of skin.

INGESTION: May cause irritation of the digestive tract. Nausea and vomiting likely.

INHALATION: Excessive exposure may cause headache and nausea.

LD50 (calculated): >8000 mg/kg	LC50 (calculated): >1400 ppm/4H
OTHER TOXIC EFFECTS: Petroleum hydrocarbon 525 mg/m3	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: same as above	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician.
SKIN:	Wash with soap. Flush affected area thoroughly with water. If irritation develops, contact a physician. Apply hand cream to reduce dryness.
INGESTION:	Do not induce vomiting. Contact a physician immediately.
INHALATION:	Remove patient to fresh air. Apply artificial resuscitation if necessary. Contact a physician.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: Yes, ignited by spark or open flame.	
FLASH POINT, °C: 42°C (TCC)	AUTO IGNITION TEMPERATURE, °C: 240°C
EXTINGUISHING MEDIA: Water [] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.	
EXPLOSIVE SENSITIVITY TO: Impact [] Static Discharge [x] Heat [] Other [x]	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: high temperature	
INCOMPATIBILITY (Material to Avoid) : strong oxidizers	
HAZARDOUS DECOMPOSITION PRODUCTS: not available	
REACTIVITY: Strong oxidizers increase risk of explosion.	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, MSDS	PREPARED BY: JohnsonDiversey Canada, Inc. Regulatory Department Industrial Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
<p>Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.</p>	