



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 92014

PRODUCT NAME: TASKI SOLSAN**USE:** Mopping Agent**SUPPLIER:**JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada**EMERGENCY PHONE:****1-800-668-7171****WHMIS CLASSIFICATION:** B3 D2B**CHEMICAL FAMILY:** Solvent**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Petroleum distillates	30-60	064742-47-8	LD50 >5,000 mg/kg	oral/rat
Petroleum naphtha	30-60	064741-65-7	not available	N/A

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:**Gloves:** Neoprene or Nitrile**Eye:** safety goggles**Footwear:** not required**Respiratory:** If mists are generated, use NIOSH approved mask**Other:** not applicable**SPECIAL HANDLING PROCEDURES AND EQUIPMENT:** Avoid eye and skin contact. Do not breathe mist, spray or vapours.**VENTILATION REQUIREMENTS:** local ventilation**INCOMPATIBILITY (Material to Avoid):** None**SPILL PROCEDURES:** Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.**WASTE DISPOSAL:** Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Colourless liquid; perfumed**S.G. / BULK DENSITY(g/cc):** 0.775**pH:** not available**VAPOUR PRESSURE (mmHg):** 12**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** not available**BOILING POINT:** 230°C**FREEZING POINT:** not available**PERCENT VOLATILE:** approx 50 %**SOLUBILITY IN WATER:** insoluble**EVAPORATION RATE (water=1):** 200

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** May cause irritation.**SKIN:** Repeated or prolonged contact may result in irritation.**INGESTION:** May cause severe irritation of the digestive tract.**INHALATION:** Breathing dust may cause respiratory irritation.**LD50 (calculated):** >5,000 mg/kg**LC50 (calculated):** not available

OTHER TOXIC EFFECTS: TLV - (Petroleum distillates): 300 ppm.

EFFECTS OF CHRONIC not available

EXPOSURE TO MATERIAL:

VI - FIRST AID MEASURES

EYES: Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician.

SKIN: Flush affected area thoroughly with water. If irritation develops, contact a physician.

INGESTION: Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.

INHALATION: Remove patient to fresh air. Get medical attention for any breathing difficulty.

VII - FIRE AND EXPLOSION DATA

FLAMMABLE: Yes, combustible if heated.

FLASH POINT, °C: 59

AUTO IGNITION TEMPERATURE, °C: N/A

EXTINGUISHING MEDIA: Water [x] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and full protective equipment. Fire may flash back. Treat as an oil fire.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

EXPLOSIVE SENSITIVITY TO: not applicable

VIII - REACTIVITY DATA

STABILITY: Stable [x] Unstable []

CONDITIONS TO AVOID: Keep away from spark or open flame. Keep away from heat.

INCOMPATIBILITY (Material to Avoid) : None

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

REACTIVITY: not dangerously reactive

IX - MSDS PREPARATION

SOURCES USED: RTECS, MSDS

PREPARED BY: JohnsonDiversey Canada, Inc.
Regulatory Department
Institutional Division
Phone (905) 829-1200

PREPARATION DATE: May 26, 2003

Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.