JohnsonDiversey



MATERIAL SAFETY DATA SHEET Printed: 02/06/2004

I Chemical Product and Company Indentification Indentification/ Information/ Information on Ingredients	Product Name Product Code Manufacturer Chemical Family Chemical Name of ETHYL ALCOHO SODIUM LAURY (9004-82-4) SODIUM DODEC (25155-30-0	95402 JOHNSOND 3630 E. KEM CINCINNA? LIQUID DI Hazardous Ing OL (64-17-5) (L ETHER SU	FI, OH 45241-20 ETERGENT F redient JLFATE	046	SCC	HING I % 1 1-5 20	DISHES Exposur 1000 NAV NAV		ect) (30 (80	0)831-9889 3)592-1024 0)424-9300 26/1999 Units PPM
III Haz ards Identific ation	Signs C Signs C and C Symptoms C of C PROLONGED OR REPEATED SKIN EXPOSURE MAY CAUSE RRITATION PROLONGED OR REPEATED SKIN EXPOSURE MAY CAUSE RRITATION PROLONGED OR REPEATED SKIN EXPOSURE MAY CAUSE Carcinogen Info V PROLONGED OR REPEATED SKIN EXPOSURE MAY CAUSE V NONE KNOWN Carcinogen Info NTP V NTP V OSHA PROLONGED OR REPEATED SKIN EXPOSURE MAY CAUSE PROLONGED OR REPEATED SKIN EXPOSURE MAY CAUSE PROLONGED OR REPEATED SKIN EXPOSURE MAY CAUSE PROLONGED OR REPEATED SKIN EXPOSURE NOT CAUSE PROLONGED OR REPEATED SKIN EXPOSURE NOT CAUSE PROLONGED									
IV First Aid Measures	Inhalation MOVE PERSON TO FRESH AIR. IF SEVERE, CONTACT A PHYSICIAN Eyes RINSE IMMEDIATELY WITH WATER. REMOVE CONTACT LENSES IF ANY, CONTINUE RINSING WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. CONTACT A PHYSICIAN IMMEDIATELY. Skin WASH WITH WATER. IFF IRRITATION PERSISTS, CONTACT A PHYSICIAN Ingestion DO NOT INDUCE VOMITTING. IF CONSCIOUS GIVE LARGE AMOUNTS OF WATER. NEVER GIVE ANYTHING BY MOUTH IF PERSON IS UNCONSCIOUS. CONTACT A PHYSICIAN IMMEDIATELY									
V Fire Fighting Measures	Fire Control WEAR A SELF CONTAINED BREATHING APPARATUS WITH FULL PROTECTIVE GE Measures/ AR Equipment									

L

VI Accidental Measures	Spill and Leak PREVENT RUNOFF. COLLECT WITH ABSORBENT MATERIAL AND DISPOSE. OBSERVE GOVERMENT REGULATIONS Clean UP Procedures										
	Environmental Precautions										
	Ventilation Required? NONE Instructions GENERAL VENTILATION										
VII Handling and Storage	Safe Storage, STORE IN ORIGINAL CONATINER IN A COOL, DRY PLACE AWAY FROM Handling INCOMPATIBLE MATERIALS and Use Instructions										
	Imcompatible Materials STRONG OXIDIZING AGENTS, CHLORINE BLEACH										
	Protective Gloves										
VIII	Eye Protection										
Exposure Controls/ Personal Protection	Respiratory Protection										
	Other Protective Clothing Equipment										
	Characteristics o of Hazardous Chemcial										
IX	Vapor Pressure NAV MmHg@ °C Vapor Density(Air=1) NAV pH 6 Water Solubility 100 % Appearance & Odor CLEAR, YELLOW LIQUID; PERFUMED FRFUMED FRF										
Physical and Chemical	Appearance & Odor CLEAR, YELLOW LIQUID; PERFUMED Boiling Point 0°F Melting Point °F Flammability Limits in Air By Volume: Upper NAV Lower NAV										
Properties	Flash Point NONE °F Auto Ignition °F Oxidizing Properties										
	Specific Gravity 1.035 Volatile by Volume %										
	Evaporation Rate(n-Butyl Acetate=1)										
	Peroxide, Pyrophoric, Unstable or Water Reactive										
37	Reactivity and Hazardous Polymerization NONE										
Х	Possible Hazardous Reactions										
Stability and	Conditions to Avoid Materials STRONG OXIDIZING AGENTS, CHLORINE BLEACH										
Reactivity	Materials STRONG OXIDIZING AGENTS, CHLORINE BLEACH To Avoid Hazardous NONE										
	Decomposition Products										
XI Toxicological Information											
XII	Possible Effects and Environmental Fate										
Ecological Information	Degradability										
mornavon	Aquatic Toxicity Method of DISPOSE IN ACCORDANCE WITH LOCAL/STATE/FEDERAL REGULATIONS										
XIII Disposal Consideration	Disposal, Residues and Safe Handling										
	Disposal of NONE Contaminated Material										
XIV Transport Information	COMPOUNDS, CLEANING, N.O.I., LIQUID										
XV-Regulatory Information											
XVI-Other Information											
S.A.R.A. Title III Section 313											
State Right to Know Information	ETHYL ALCOHOL - CAS #64-17-5 SODIUM LAURYL ETHER SULFATE - CAS #9004-82-4 SODIUM DODECYL SULFONATE - CAS #25155-30-0										