(425)889-4100 6/28/2004 1:02 PAGE 002/009 Fax Server

016 03/26/04 LIQUICHLOR / SODIUM HYPOCHLORITE 10-16%

PRODUCT NAME: LIQUICHLOR / SODIUM HYPOCHLORITE 10-16%

MSDS NUMBER: OX622680

EFFECTIVE DATE: 1/15/2003

SUPERSEDES: 1/10/1999

ISSUED BY: 007427

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Sodium Hypochlorite Solution (10 - 16% w/w)

CAS#: 7681-52-9

Synonyms: Sodium Hypochlorite Solution - Trade % (11 - 19), Bleach, Javel Water, Clorox, Sunny Sol 150, Liquid Chlorine Solution, Liquid Bleach,

Hypochlorite Bleach, Hypo

Product Use: Bleach, disinfectant

Emergency Contacts (24 hr.)

A FOR INFORMATION REGARDING ON SITE CHEMICAL EMERGENCIES INVOLVING A SPILL

OR LEAK, CALL

U.S.: 1-800-424-9300 - CHEMTREC Canada: 1-613-996-6666 - CANUTEC

Distributed by: Univar USA Inc. 6100 Carillon Point Kirkland, WA 98033 425-889-3400

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredient(s) % (w/w) ACGIH OSHA CAS NO. A Sodium Hypochlorite 10 - 16 Not established Not 7681-52-9

0.5 ppm established

(as chlorine)

Sodium Hydroxide 0.3 - 4 2 mg/m3 (ceiling) 2 mg/m3 1310-73-2

SECTION 3 HAZARD IDENTIFICATION

Emergency Overview: CORROSIVE! Contact with acid liberates toxic chlorine gas. Causes burns to skin, eyes, respiratory tract and mucous membranes. Harmful or fatal if swallowed. May cause sensitization by skin contact. Toxic to aquatic organisms. Read the entire MSDS for a more thorough evaluation of the hazards.

Potential Health Effects:

Inhalation: Mist can irritate the nose and throat. If mixed with acids, hypochlorite solutions release large amounts of chlorine gas. This gas can cause severe irritation of the nose and throat. Exposure to high levels of chlorine gas may result in severe lung damage.

Skin Contact: Sodium hypochlorite mist and solutions can cause skin irritation. In severe cases, chemical burns may result.

Eye Contact: Can cause severe eye irritation and permanent eye injury. Ingestion: May cause irritation, pain and inflammation of the mouth and stomach, vomiting, shock, confusion, delirium, coma and, in severe cases, death. Perforation of the esophagus or stomach may occur.

Subchronic Effects: SKIN: Prolonged or repeated skin contact with solutions containing as little as 4-6% sodium hypochlorite can cause allergic contact dermatitis. Symptoms include chronic, itchy eczema. Sensitized people can react to very dilute (0.04-0.06% NaOCl) solutions that touch their skin Existing Medical Conditions Possibly Aggravated by Exposure: Skin irritation may be aggravated in individuals with existing skin lesions. Breathing of vapors or mists may aggravate acute or chronic asthma and chronic pulmonary disease such as emphysema and bronchitis.

Carcinogenicity: Sodium hypochlorite is not classified as a carcinogen by ACGIH (American Conference of Governmental Industrial Hygienists) or IARC (International Agency for Research on Cancer), not regulated as a carcinogen by OSHA (Occupational Safety and Health Administration), and not listed as a carcinogen by NTP (National Toxicology Program).

SECTION 4 FIRST AID MEASURES

General: If you feel unwell seek medical advice (show the label where

possible).

Inhalation: Move victim to fresh air. Give artificial respiration ONLY if breathing has stopped. Do not use mouth-to-mouth method if victim ingested or inhaled the substance: induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Give Cardiopulmonary Resuscitation (CPR) only if there is no pulse AND no breathing. Obtain medical attention IMMEDIATELY. Skin Contact: Immediately flush skin with running water for at least 15 - 20 minutes. Under running water remove contaminated clothing, jewelry, and shoes. If irritation persists, repeat flushing. For burns, obtain medical attention. Discard heavily contaminated clothing and shoes in a manner, which limits further exposure. Otherwise, wash clothing separately before

Eye Contact: Immediately flush eyes with running water for a minimum of 20 minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention IMMEDIATELY. Do not transport victim until the recommended flushing period is completed unless flushing can be continued during transport.

Ingestion: DO NOT INDUCE VOMITING. If victim is alert and not convulsing, rinse mouth and give as much water as possible to dilute material. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomitus, rinse mouth and administer more water. IMMEDIATELY transport victim to an emergency facility.

Note to Physicians: Symptomatic. Treatment and supportive therapy as indicated. Do NOT give acidic antidotes such as juice, soft drink, vinegar, etc. This product contains materials that may cause severe pneumonitis if aspirated. If ingestion has occurred less than 2 hours earlier, carry out careful gastric lavage; use endotracheal cuff if available, to prevent aspiration. Observe patient for respiratory difficulty from aspiration pneumonitis. Give artificial resuscitation and appropriate chemotherapy if respiration is depressed. Following exposure the patient should be kept under medical review for at least 48 hours as delayed pneumonitis may occur. Pulmonary edema is likely and may be delayed. Steroid therapy, if given early, may be effective in preventing or alleviating edema.

SECTION 5 FIRE FIGHTING MEASURES
Flash Point Not applicable. Not combustible
Flammable Limits (Lower) Not applicable
Flammable Limits (Upper) Not applicable
Auto Ignition Temperature Not applicable
Combustion and Thermal Decomposition Products Chlorine, sodium oxide,
oxygen
Rate of Burning Not applicable
Explosive Power Not applicable
Sensitivity to Mechanical Impact Not applicable

Fire and Explosion Hazards: Sodium hypochlorite is a strong chemical oxidant, but solutions do not support combustion. Reaction with nitrogen compounds, chloroorganic compounds, or easily oxidizable compounds (reducing agents) may be explosive. This material is non-flammable but is decomposed by heat and light, causing a pressure build-up, which could result in an explosion. When heated, it may release chlorine gas. Vigorous reaction with oxidizable or organic materials may result in fire. See Section 10. Extinguishing Media: For large fires use an all purpose type AFFF alcohol foam resistant medium expansion according to foam manufacturer's recommended techniques. The foam supplier should be consulted for recommendations regarding foam types and delivery rates for specific applications. Use carbon dioxide or dry chemical media for small fires. If only water is

available, use it in the form of a fog. Special Information: Water may be used to cool containers of Hypochlorite solution exposed to heat from a fire. This should be done from a safe distance since containers may rupture.

Move containers from fire area if you can do it without risk. Dike fire control water for later disposal; do not scatter the material. Fire involving tanks or trailer loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Do not get water inside containers. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from the ends of tanks.

Evacuation: If tank or tank truck involved in a fire, ISOLATE and consider evacuation of one-half (1/2) mile radius.

Fire Fighting Protective Equipment: Firefighters should wear protective equipment and self-contained breathing apparatus with full facepiece operated in positive pressure mode in a fire involving this material. Toxic gas and vapors are produced upon decomposition.

NOTE: Also see "Section 10 - Stability and Reactivity"

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spills, Leaks, or Releases:

Restrict access to area until completion of clean up. Ensure trained personnel conduct clean up.

Remove all ignition sources (no smoking, flares, sparks or flames). All equipment should be grounded and non-sparking. Ventilate area. Wear adequate personal protective equipment. Do not touch spilled material. Stop leak if possible without personal risk.

Small spills: Cover with DRY earth, sand or other non-combustible material. Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal. Rinse area with water.

Large spills: Prevent entry into sewers and confined areas. Dike with inert material (sand, earth, etc.). Contact fire and emergency services and supplier for advice. Collect product for recovery or disposal by pumping it into polyethylene containers. Consider in-situ neutralization and disposal. Ensure adequate decontamination of tools and equipment following clean up. Collect contaminated soil and water, and absorbent for proper disposal. Comply with Federal, Provincial/State and local regulations on reporting releases.

Deactivation for Small Spills: Hypochlorite can be broken down by covering it with a reducing agent such as sodium sulfite or sodium thiosulfate. Deactivating Chemicals: Use sodium sulfite or diluted hydrogen peroxide to reduce the material. Ensure there is no chlorine residue before neutralizing with a weak solution of hydrochloric or sulfuric acid. Waste Disposal Methods: Dispose of waste material at an approved waste treatment/disposal facility in accordance with applicable regulations. Do

treatment/disposal facility, in accordance with applicable regulations. Do not dispose of waste with normal garbage or to sewer systems.

Note: - Clean-up material may be a RCRA Hazardous Waste on disposal.
- Spills are subject to CERCLA reporting requirements: RQ = 100 lbs.

SECTION 7 - HANDLING AND STORAGE

Precautions: Have emergency equipment (for fires, spills, leaks, etc.) readily available. Ensure all containers are labeled. Wear appropriate Personal Protection Equipment. People working with this chemical should be properly trained regarding its hazards and its safe use. Handling Procedures and Equipment: Avoid generating mist. Use smallest possible amounts in designated areas with adequate ventilation. Keep containers closed when not in use. Empty containers may contain hazardous residues. Use corrosion-resistant transfer equipment when dispensing. Storage Requirements: Store in a cool, dry, well-ventilated area, out of direct sunlight. Store containers at 15 - 29 deg C (59 - 84 deg F). Do not store above 30 deg C (86 deg F) or below freezing point. Keep containers tightly closed when not in use and when empty. Protect from damage. Vent caps should be checked with full personal protection. Store away from incompatible materials such as reducing materials, strong acids, nitrogen

compounds, copper, nickel and cobalt. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area. This product has a shelf life of up to six months at 60 deg F or lower. Outdoor storage tanks should be suitably diked or otherwise provided with an adequate means of secondary containment. Appropriate secondary containment measures should be taken to prevent spills or leaks from indoor storage tanks and tank-truck unloading stations from entering sewers or other channels that discharge directly to a water body or a municipal sewage system.

SECTION 8 - EXPOSURE CONTROLS t PERSONAL PROTECTION PREVENTIVE MEASURES Recommendations listed in this section indicate the type of equipment, which will provide protection against over exposure to this product. Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.

Engineering Controls: Local exhaust ventilation should be applied wherever there is an incidence of point source emissions or dispersion of regulated contaminants in the work area. Ventilation control of the contaminant as close to its point of generation is both the most economical and safest method to minimize personnel exposure to airborne contaminants. The most effective measures are the total enclosure of processes and the mechanization of handling procedures to prevent all personal contact. Smoking should be prohibited in areas in which sodium hypochlorite solution is stored or handled.

PERSONAL PROTECTIVE EQUIPMENT

Eye Protection: Wear splash resistant chemical goggles and full-face shield. Maintain eye wash fountain and quick-drench facilities in work area. Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron, rain jacket, pants or coveralls, as appropriate, to prevent skin contact.

RECOMMENDED (resistance to breakthrough longer than 8 hours): butyl rubber, natural rubber, neoprene, nitrile rubber, polyethylene, Viton, SaranexTM,

ResponderTM

Recommendations are valid for permeation rates reaching 0.1 ug/cm2/min or 1 mg/m2/min and over. Resistance of specific materials can vary from product to product. Breakthrough times are obtained under conditions of continuous contact, generally at room temperature. Evaluate resistance under conditions of use and maintain clothing carefully.

Respiratory Protection: A NIOSH/MSHA approved air-purifying respirator equipped with acid mist cartridges for concentrations up to 10 times the TLV. Use a supplied air respirator if concentrations are higher or unknown.

EXPOSURE GUIDELINES PRODUCT:

Sodium Hypochlorite

Workplace environmental exposure level guides (WEELS) / American Industrial Hygiene Association (AIHA) / 2001 short-term time weighted average ; 2 mg/m3: 15 minute

	Sodium Hypochlorite	Chlorine*	Sodium Hydroxide
ACGIH TWA	Not established	0.5 ppm	Not established
OSHA PEL	Not established	0.5 ppm	2 mg/m3
NIOSH IDLH	Not established	10 ppm	Not established
ACGIH STEL	Not established	1 ppm	Not established
OSHA STEL	Not established	1 ppm as C	12 Not established
NIOSH (15 min	. ceiling)		
	Not established	0.5 ppm	Not established
ACGIH Ceiling	Not established	Not establ:	ished 2 mg/m3

^{*} Chlorine may be present as a decomposition product.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES Chemical Name Sodium hypochlorite Chemical Family Hypochlorous acid salt Molecular Formula Na-O-Cl Molecular Weight 74.4

Appearance Green to yellow, watery liquid
Odor Pungent chlorine-like odor
PH 11-13
Vapor Pressure (mm Hg at 21 deg C(69.8 deg F) 12 mmHg
Vapor Density (Air = 1) No data
Boiling Point Decomposes above 40 deg C (104 deg F)

Freezing Point 7.5 deg F (-13.6 deg C)

Solubility (Water) Completely

Specific Gravity About 1.198 (12.5% w/w solution) @ 20 deg C (68 deg F)

Evaporation Rate Not available % Volatile by Volume Not available

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable at room temperature.

Hazardous Decomposition Products: Thermal decomposition: Chlorine, sodium oxide, oxygen, oxides of chlorine, sodium chlorate, and hydrogen.

Conditions to Avoid: Keep away from high heat, and sunlight or ultra-violet light. Do not store above 30 deg C (86 deg F). Do not allow solutions to evaporate dry. Keep away from incompatibles.

Incompatibility with other Substances: May react violently with strong acids producing chlorine gas, which is toxic. Other incompatibles include organic material, cellulose, oxidizable materials, ammonia, urea, ammonium salts, ethyleneimine, cyanides, nitrogen compounds, alcohols, metals, and metal oxides. Reacts with metals to produce flammable hydrogen gas. Metal and metal oxide catalysts decompose hypochlorites, evolving oxygen and often causing explosions. May react explosively with nitrogen containing compounds or form chloroamines, which are explosive. Alkaline hypochlorite solutions may react explosively with some chloroorganic compounds.

Corrosivity to Metals: Solutions can be corrosive to many metals.

Hazardous Polymerization: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

TOXICOLOGICAL DATA Sodium Hypochlorite:

Toxicity Data: TDLo (Lowest published toxic dose) oral-woman- 1 gm/kg

45 mg/kg intravenous-man TDLo LD50 oral rat- 8910 mg/kg LD50 oral mouse- 5800 mg/kg LC50 rat- >10500 mg/m3 (1 hr)

Irritation Data: Eyes: One drop of 15% solution (pH 11.2) caused immediate severe pain. If not quickly washed off with water, it caused bleeding and swelling of the tender tissue surrounding the eye (conjunctiva) and damage with swelling to the front part of the eye (cornea). The eyes sometimes healed in two to three weeks with slight or no scar damage to the cornea. Skin: A solution of 3.5% NaOCl applied to rabbit skin for 15 or 30 minutes caused severe skin damage.

Sodium Hydroxide:

Irritation data: 500 mg/24 hour(s) skin-rabbit severe; 400 pg eyes-rabbit

mild; 1 percent eyes-rabbit severe;

Toxicity data: 1350 mg/kg skin-rabbit LD50; 104-340 mg/kg oral-rat LD50 Mutagenicity: Sodium hypochlorite caused mutations in several short-term studies using bacteria and cultured mammalian cells. The significance of these tests is unclear. It was not mutagenic in tests (chromosome aberration and micronucleus) on live animals.

Reproductive Effects: High doses of NaOCl in drinking water caused a small but significant increase in abnormal sperm in mice.

Teratogenicity and Fetotoxicity: No data available

Carcinogenicity: See Section 3, page 2.

Synergistic Materials: None known

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicological Information: Harmful to aquatic life in low concentrations. Fish Toxicity: LC50 (48 hr) rainbow trout 0.07 mg/l.

LC50 (96 hr) fathead minnow 5.9 mg/l.

Invertebrate and Microbial Toxicity: LOEC Oncorhynchus kisutch 0.02 mg/l. Persistence and Degradation: No data available.

SECTION 13- DISPOSAL CONSIDERATIONS

Review federal, state and local government requirements prior to disposal. Do not dispose of waste with normal garbage, or to sewer systems. Whatever cannot be saved for recovery or recycling, including containers should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste

management options. RCRA: Test waste material for corrosivity, D002, prior to disposal.

SECTION 14 TRANSPORT INFORMATION

TDG CLR *

Hypochlorite Solution - with Hypochlorite Solution Shipping Name

more than 7 percent available

chlorine

Hazard Class / Division 8: Corrosive 8: Corrosive

Identification No. UN1791 UN1791 II III ERAP/RO N/AP N/AP

Note: * TDG CLR (Clear Language Regulations) became effective August 15,

IATA/ICAO Shipping Description: Hypochlorite solution, Class 8, UN1791, PG II or III is accepted for air transport.

SECTION 15 - REGULATORY INFORMATION

USA CLASSIFICATION

OSHA Classification: Hazardous by definition of Hazard Communication

Standard (29 CFR 1910.1200)

SARA Regulations sections 313 and 40 CFR 372: N

SARA Hazard Categories, SARA SECTIONS 311/312 (40CFR370.21):

ACUTE: Y CHRONIC: N FIRE: N REACTIVE: N SUDDEN RELEASE: N

OSHA PROCESS SAFETY (29CFR1910.119): N

CERCLA SECTION 103 (40CFR302.4): Y

Reportable Quantity (RQ) under CERCLA: 100 lbs. (45.4 kg)

TSCA Inventory Status: Y

Other Regulations/Legislation which apply to this product: Right-to-Know/Disclosure Lists: Illinois, Massachusetts, New Jersey,

Pennsylvania,

This product does not contain nor is it manufactured with ozone depleting substances.

CANADIAN CLASSIFICATION

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and this MSDS (Material Safety Data Sheet) contains all the information required by the CPR. Controlled Products Regulations (WHMIS) Classification: D2B: Material causing other toxic effects -Toxic E: Corrosive

CEPA / Canadian Domestic Substances List (DSL): Y WHMIS Ingredient Disclosure List: Meets criteria for disclosure at 1% or greater.

EINECS Number: 231-668-3

SECTION 16 - OTHER INFORMATION

National Fire Protection Association (NFPA) Rating Hazardous Materials Identification System (HMIS) Rating

NFPA HMIS

4 = Extreme/Severe

HEALTH 3 3 3 = High/Serious 2 = Moderate 0 0 1 = Slight

0 = Minimum

W = Water Reactive

LEGEND

ACGIH - American Conference of Governmental Industrial Hygienists

CAS # - Chemical Abstracts Service Registry Number

CERCLA - Comprehensive Environmental Response, Compensation, and Liability

CFR - Code of Federal Regulations

DOT - Department of Transportation EPA - Environmental Protection Agency

IDLH - Immediately Dangerous to Life and Health

LC50 - The concentration of material in air expected to kill 50% of a group

of test animals

REACTIVITY 1

LD50 - Lethal Dose expected to kill 50% of a group of test animals

MSHA - Mine Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

PVC - Polyvinyl chloride

RCRA - Resource Conservation and Recovery Act

SARA - Superfund Amendments and Reauthorization Act of the U.S. EPA

STEL - Short Term Exposure Limit

TDG - Transportation of Dangerous Goods Act/Regulations

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

----- FOR ADDITIONAL INFORMATION -----CONTACT: MSDS COORDINATOR UNIVAR USA INC.

DURING BUSINESS HOURS, PACIFIC TIME (425)889-3400 ----- NOTICE -----

******* UNIVAR USA INC ("UNIVAR") EXPRESSLY DISCLAIMS _____

ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED HEREIN, ______

AND SHALL UNDER NO CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES . **

DO NOT USE INGREDIENT INFORMATION AND/OR INGREDIENT PERCENTAGES IN THIS MSDS AS A PRODUCT SPECIFICATION. FOR PRODUCT SPECIFICATION INFORMATION REFER TO A PRODUCT SPECIFICATION SHEET AND/OR A CERTIFICATE OF ANALYSIS. THESE CAN BE OBTAINED FROM YOUR LOCAL UNIVAR SALES OFFICE.

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS BELIEVED TO BE ACCURATE, UNIVAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR SUFFICIENCY. CONDITIONS OF USE ARE BEYOND UNIVARS CONTROL AND THEREFORE USERS

(425)889-4100 6/28/2004 1:02 PAGE 009/009 Fax Server

ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM THE PUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER PROCESS.

* * * END OF MSDS * * *

and mucous membranes.

.g., udno, feces, etc.) will refease chiodine herricais (e.g., arrimonte, acide, nly with water according to label

DOBESTIC ANUALS
 deep skin and eye inflation or chemical burns to the eye skin and eye inflation or chemical burns to the eye skin and eye inflation or chemical burns to the eye skin and eye inflation or chemical burns to the eye of t

on as possible. Do not return until strong

r other waters unless in accordance with Containing this product linto lakes,

pasticada is toxic to fish and aquatic

withoutly has been notified in writing prior to ani Discharge Elimination System

containing this product to sewer systems

sewage treatment plant authority. For

loand or Regional Office of the EPA

zere skiln and eye imitation or chemical burns to

FCHILDREN

NOTE: This product degrades with ago, use within one month of receipt. Use a chlorine test let and increase delege as reconstany, to ethain required level of waithable Chlorine

It is a violation of tedesal faw to use this product in a manner inconsistent with its labe STORAGE AND DISPOSAL: Store this product in a cool dry area, away from direct a

DIRECTIONS FOR USE

J2:00

FOR INSTITUTIONAL AND INDUSTRIAL USES DO NOT STORE IN OR ABOUT DWELLING

92/59/5994

and head to avoid deterioration. In case of spill, flood areas with large quantities of wa poroduct or finates that cannot be used should be diluted with water batters disposel for sanitary sewer. Do not container but place in traish adjection. Do not container of food or feed by storage, disposel or begriang of equipment.

food or lead by storage, disposal or dearring of equipment

See Product Bulletin for additional precautions and specific directions for uso

MERT NGREDENTS.

ACTIVE INSPERIENT: Section Pypochicable

LIQUICHLOR® 12.5% SOLUTION

A THEN IS

Insalinated against a

treatment advice.

so by the poison corted porter "MODEWAS O nediately for breakward achice.

ansalous pansan.

ou when calling a potoca control

SICIAN:

Spario tito use of gostilio litrago.

MATERIAL SAFETY DATA SHEET

PROD NO:

LOT NO:

NET CONTENTS:

D



349211

further freatment action writaulance, then give artifical the first 5 minutes, then continue , if possible.

ly with water for 15-20 minutes.

CAS NUMBERS: SODIUM HYPOCHLORITE 7891-62-9 RQ, HYPOCHLORITE SOLUTIONS, 8, UN1791, PG III (DONTAINS SODIUM INPOCHLORITE)

Revision Data Label Number

Trademark of Univar USA Inc.

PWS037

Packaged in Tampa, FL

to absorb spills. Comply with all governmental regulations on reporting release disce sodum bisulfae, flush neutralized material to vasele treatment system wif rubber aproin, chemical goggles, and respiratory protection. Flush small spills In case of Spill. Wear protective equipment including rubber boots, rubber glovi stream. Use water spray to cool nearby containers exposed to fire. Firefighten In case of Fire: Use water spray, dry chemical or CO2. Do not use a direct water For emergency assistance involving chemicals call CHEMTREC day or night at

water. Avoid contact with acids. Do not use combustible materials, such as as waste treatment system with lots of water. For large spills, contain, neutralize of should wear self-contained breathing apparatus.

FOLLOW ALL LABEL WARNINGS EVEN AFTER THE CONTAINER IS container retains product vapor and residue. Never add any chemicals to withdrawat. Do not use pressure to empty since the container is not a pri Loosen closure cautiously when opening and replace closure after each Vent container frequently, and more often in hot weather, to relieve press

EMERGENCY RESPONSE

empty container because violent and dangerous reactions may occur. vessel. Wash thoroughly after handling. Empty Containers: The empty apron. Wear resiratory protection if local exhaust ventilation is inadequate Handling: Always wear protective dothing including gogglies, rubber glow

KEEP CONTAINER CLOSED CONTAINER ADVICE

EMPTY.

EPA EST, NO. 00660-FL-002 EPA REG. NO. 650-198

03/03/18 - 004

Univar USA The

Health: Fire:

3949

NFPA Ratings:

29/29

6190 CARILLON POINT, KIRKLAND, WA 98033, (425) 889-940

- MURIATIC ACID 20 BE' WATER WHITE TACOMA
 MURIATIC ACID 22 BE' WATER WHITE TACOMA
- MURIATIC ACID 18%-NIAGARA
- MURIATIC ACID 10%-DEER PARK
- MUR ACD 20 WW-TAC (CAN)
- MUR ACD 22 WW-TAC (CAN)
- MUR ACID 20 COM NF (CAN)
- MUR ACD 20 WW-NIAG (CAN)

CONTACT: MSDS COORDINATOR UNIVAR USA INC.
DURING BUSINESS HOURS, PACIFIC TIME (425)889-3400
******** UNIVAR USA INC ("UNIVAR") EXPRESSLY DISCLAIMS
ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED HEREIN,
AND SHALL UNDER NO CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**
DO NOT USE INGREDIENT INFORMATION AND/OR INGREDIENT PERCENTAGES IN THIS MSDS AS A PRODUCT SPECIFICATION. FOR PRODUCT SPECIFICATION INFORMATION REFER TO A PRODUCT SPECIFICATION SHEET AND/OR A CERTIFICATE OF ANALYSIS. THESE CAN BE OBTAINED FROM YOUR LOCAL UNIVAR SALES OFFICE.

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS BELIEVED TO BE ACCURATE, UNIVAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR SUFFICIENCY. CONDITIONS OF USE ARE BEYOND UNIVARS CONTROL AND THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM THE PUBLICATION OR USE OF, OR RELIANCE UPON , INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER PROCESS.

* * * END OF MSDS * * *