

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): **AQUASPORT WOOD FLOOR MAINTAINER** Product Number: 5838

Product Division: Janitorial

Spartan Chemical Company, Inc.	Product/Technical Information:	1-(800)-537-8990
1110 Spartan Drive	Medical Emergency:	1-(888)-314-6171 (24 hours)
Maumee OH 43537	0,	CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Cleaning compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: 1- Slight
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z-1-A			
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m ^³	STEL mg/m ^³	CEILING mg/m ^³	NTP, IARC or OSHA Carcinogen
Petroleum distillates	1-5	64742-46-7	5 [oil mist]	Not Established	Not Established	No
*Ethylene glycol	1-5	107-21-1	Not Established	Not Established	127 (ACGIH)	No
Triethanolamine oleate	1-5	2717-15-9	Not Established	Not Established	Not Established	No
Alcohol ethoxylate	1-5	68131-39-5	Not Established	Not Established	Not Established	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: 210-212 °F	Vapor Pressure:	Undetermined
Vapor Density (AIR = 1): Unknown	Solubility in Water:	Forms an emulsion.
pH: 11.5-12.5	Specific Gravity ($H_2O=1$):	1.0
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight:	10-12
Physical State: Liquid		
Appearance & Odor: Opague white liquid, fresh fragrance.		

.

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56	
Flammable Limits: Not Established	Flame Extension: N/A	
Extinguishing Media: Product does not support combustion	. Use extinguishing media appropriate for surrounding fire.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained containers with water spray.	breathing apparatus and protective clothing. Cool fire-exposed	
Unusual Fire & Explosive Hazards: Combustion products are toxic.		

SECTION V: HEALTH HAZARD DAT Threshold Limit Value:		Primary Routes of Entry:	Inhalation, Skin Contact, Eyes & Oral	
Effects of Overexposure-	 Avoid contact with eyes, skin or clothing. Do not swallow. Avoid breathing product mist. 			
Conditions Aggravated by User	Avoid contamination of food. Wa Use of this product may aggravate pr	• • •	· · · · · ·	
conditions Aggiavated by Use.	dermatitis.	eexisting skin, eye and respirator	y disorders including astima and	
Emergency & First Aid Procedures	:			
Eyes:	Flush eyes with water for at least 15 persists.	minutes. Remove contact lenses.	Get medical attention if irritation	
Skin:	Remove contaminated clothing. Flus irritation persists. Wash contaminate		ninutes. Get medical attention if	
Ingestion:	Do not induce vomiting. Drink one o not give anything by mouth to an uno	5 I	roduct. Get medical attention. Do	
Inhalation:	Move person to fresh air. Get medic	al attention if irritation persists.		

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong oxidizers
Hazardous Decomposition Products: CO , CO_2	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Small spills of one gallon or less may be flushed with plenty of water to sanitary sewer system (If permitted by local sewer regulations). Dike and contain large spills with inert material and transfer liquid to containers for recovery or disposal.
Waste Disposal Method:	Dispose of in compliance with all federal, state and local laws and regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not normally required when good general ventilation is provided. However, if exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use-conditions and chemicals in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber or other impervious gloves.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Do not contaminate water, food or feed by storage or disposal. Keep out of reach of children. Keep from

	freezing.				
Other Precaution	California Prop	California Proposition 65: WARNING: This product contains chemicals known to the State of California to			
		cause cancer and birth defects or other reproductive harm.			
© SCC 11/15/2004	Name:	Ronald T. Cook	Title:	Manager, Regulatory Affairs	
AQUASPORT WOOD FLOOR MAINTAINER	Effective Date:	11/15/2004			
Ref: 29 CFR 1910.1200 (OSHA)	Changes:	New Product			

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.