

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

AQUASPORT WOOD FLOOR SANDING SEAL

Product Number: 5839

Product Division: **Janitorial**

Spartan Chemical Company, Inc. Product/Technical Information: 1-(800)-537-8990

1110 Spartan Drive Medical Emergency: 1-(888)-314-6171 (24 hours)

Maumee, OH 43537 Chemical Leak/Spil Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: *1 - Slight; Chronic Hazard
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from

listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z-1-A			
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
Acrylic polymer	20-25	Proprietary	Not Established	Not Established	Not Established	No
*2-Butoxyethanol	5-10	111-76-2	120 [skin]	Not Established	Not Established	No
Dipropylene glycol methyl ether	1-5	34590-94-8	600 [skin]	909 (skin)	Not Established	No
				(ACGIH)		

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: 210 °F	Vapor Pressure: Unknown			
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete			
pH: 7.0 - 8.0	Specific Gravity (H ₂ O=1): 1.036			
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 20-30 %			
Physical State: Liquid				
Appearance & Odor: Translucent emulsion, slight ammonia	Appearance & Odor: Translucent emulsion, slight ammoniacal odor			

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: >210°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not support combustion	n. Use extinguishing media appropriate for surrounding fire.
0 1151 51111 5	d breathing apparatus and protective clothing. Cool fire-exposed
Unusual Fire & Explosive Hazards: Material can splatter above 210 °F.	Dried product can burn. Combustion products are toxic.

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes and		
65.76.4 2 74.46.	Not Established	Oral.		
		ymptoms may include redness, pain and swelling.		
Conditions to Avoid:	,	may include nausea, vomiting, pain and diarrhea.		
	Harmful if absorbed through skir			
		respiratory irritation, headache and nausea. cause central nervous system depression with symptoms such as		
	headache; dizziness; nausea and dro	owsiness. Exposure to 2-butoxyethanol may cause blood cell; liver		
	and kidney damage based on animal			
		clothing. Avoid breathing vapors or mist. Use with allow. Wash thoroughly after handling. Observe		
	recommended exposure limits.			
Conditions Aggravated by Use:	Use of this product may aggravate pr	eexisting skin; eye and respiratory disorders including asthma and		
	dermatitis.			
mergency & First Aid Procedures		n at least 15 minutes. Demons contact langua. Cat madical		
Eyes:	• •	r at least 15 minutes. Remove contact lenses. Get medical		
Skin	attention.	h skin theroughly with planty of water. Cet medical attention if		
SKIII.	kin: Remove contaminated clothing. Flush skin thoroughly with plenty of water. Get medical atte			
Indestion:	irritation persists. Wash contaminated clothing before reuse.			
ingestion.		r two glasses of water to dilute product. Get immediate medical		
Inhalation	attention. Do not give anything by m	·		
Inhalation:	Move person to fresh air. Get medica	l attention if irritation persists.		
CCTION VI: REACTIVITY DATA Stability:		Incompatible Materials: Oxidizing agents		
Hazardous Decomposition Products:	Carbon oxides, nitrogen oxides	Hazardous Polymerization: Will Not Occur		
CCTION VII: SPILL OR LEAK PRO	CEDURES			
Steps to be Taken in Case	Discount and a set of the set of	otal (and a south assume south should not a Navad to south		
Material is Released or Spilled:	containers for disposal. Keep spill ou	rial (sand, earth, commercial absorbent, etc.) and transfer to		
Waste Disposal Method:		vered material and ensure conformity with federal, state and local		
waste Bispesai Metrica.	regulations.	voice material and orisare comorning with reactar, state and local		
ECTION VIII: SPECIAL PROTECT	ION INFORMATION			
Pasniratory Protection	Not normally needed when good year	tilation is provided. However, if exposure limits are exceeded (see		
Respiratory Protection.	Not normally needed when good ventilation is provided. However, if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, use of a NIOSH approved respirator suitable for the condition of use and substances in Section II should be considered.			
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.			
Protective Gloves(Specify Type):	Use of rubber or other impervious gloves is recommended to prevent skin contact.			
Eye Protection(Specify Type):				
Other Protective Equipment:	For further guidance see 29 CFR 191	0.132-138.		
ECTION IX: SPECIAL PRECAUTIO	NS			
Drocoutions, Lieudine 9 Charles		container tightly sealed. Store in a cool, well ventilated area away		
ELECALIDORS: HADDIIDO & SIOTIDO.	Keen out of reach of children Keen	container tightly sealed. Store in a cool, well ventilated area away.		
rrecadions, rianding a storing.	from heat, direct sunlight and oxidizing			

Precautions; Handling & Storing:	Keep out of read	ch of children.	Keep container tightly se	aled. Store	in a cool, well ventilated area away
	from heat, direct sunlight and oxidizing agents. Keep from freezing.				
Other Precautions:	California Proposition 65: WARNING: This product contains chemicals known to the State of California to				
	cause cancer and birth defects or other reproductive harm.				
© SCC 11/15/2004	Name:	Ronald T. Coc	ok Title:	Ma	anager, Regulatory Affairs

Manager, Regulatory Affairs

AQUASPORT WOOD FLOOR SANDING Effective Date: 11/15/2004

Ref: 29 CFR 1910.1200 (OSHA)

Changes:

New Product

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.