

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): BONNET AND TRAFFIC LANE CARPET CLEANER Product Number: 3085 Product Division: Janitorial

Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee OH 43537 Product/Technical Information: 1-(800)-537-8990 Medical Emergency: 1-(888)-314-6171 (24 hours) Chemical Leak/Spil Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Cleaning compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 2 - Moderate	Health: 2 - Moderate
Fire: 1- Slight	Fire: 1- Slight
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

		Table Z-1-A				
Chemical Name (s)	%Wt	CAS Registry No.	TWA mg/m ^³	STEL mg/m³	CEILING mg/m ^³	NTP, IARC or OSHA Carcinogen
Sodium lauroyl sarcosinate Petroleum distillate N-lauroyl sarcosinate	5-10 1-5 1-5	137-16-6 64742-47-8 97-78-9	Not Established 2300 (EXXON) Not Established	Not Established Not Established Not Established	Not Established Not Established Not Established	No No No

SECTION III: PHYSICAL DATA

Boiling Point: 210 °F	Vapor Pressure:	Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water:	Forms an emulsion
pH: 8.5-9.0	Specific Gravity (H ₂ O=1):	0.995
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight:	10-12
Physical State: Liquid		
Appearance & Odor: Milky emulsion, floral fragrance		

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 200 °F	Method Used: ASTM-D56	
Flammable Limits: N/A	Flame Extension: N/A	
Extinguishing Media: Product does not support combustion	n. Use extinguishing media appropriate for surrounding fire.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.		
Unusual Fire & Explosive Hazards: Combustion products are toxic.		

Threshold Limit Value:	Not established	Primary Routes of Entry:	Inhalation, Skin Contact, Eyes and Ingestion
I	 e- CAUSES EYE IRRITATION: May cause severe eye irritation with corneal injury which may result in d: permanent impairment of vision. Symptoms may include tearing, stinging and redness. MAY CAUSE SKIN IRRITATION: Prolonged or repeated exposure may cause moderate skin irritation. Symptoms may include stinging, redness and swelling. MAY CAUSE RESPIRATORY IRRITATION: Inhalation of vapor or mist may cause respiratory tract irritation. Symptoms may include coughing, soreness in respiratory tract, chest tightness and difficulty breathing. MAY BE HARMFUL IF SWALLOWED: Swallowing small amounts related to normal product handling are not likely to cause injury. Swallowing larger amounts may cause injury. Contains Petroleum distillates: Vapor concentrations greater that 700 ppm are irritating to the eyes and the respiratory tract and may cause headache, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. Small amounts of petroleum distillates aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death. Do not get in eyes. Avoid contact with skin and clothing. Avoid breathing product vapors or mist. Do not taste or swallow. Wash thoroughly after handling. 		
Conditions Aggravated by Use:	Persons with impaired lung function of high concentrations of petroleum dis		xperience breathing difficulties if
Emergency & First Aid Procedure	es:		
	Flush eyes with water for at least 15 attention.	5 minutes. Remove contact lens	ses. Get immediate medical
Skin:	Wash thoroughly with soap and wat contaminated clothing before reuse.	er. If irritation persists; get me	dical attention. Wash
Ingestion:	Do not induce vomiting. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person.		
Inhalation:	n: Move person to fresh air. Get medical attention if irritation persists.		

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong oxidizers
Hazardous Decomposition Products: None known	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Dike and contain large spill with inert material and transfer liquid to containers for recovery or disposal. Waste Disposal Method: Incineration or approved landfill.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not usually needed when good general ventilation is provided. However, if exposure limits are exceeded (See Section II) or if respiratory irritation occurs, the use of a NIOSH approved respirator suitable for the conditions of use and chemicals in Section II should be considered.
Ventilation:	Good general ventilation should be sufficient for most conditions. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber gloves
Eye Protection(Specify Type):	Splash goggles
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep from freezing, Keep out of reach of children.

Other Precautions: California Proposition 65 : Warning: This product contains chemicals known to the State of California to cause cancer.

Name:

Ref: 29 CFR 1910.1200 (OSHA)

Changes: Update Sections IV & IX

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.