



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):
CONCRETE SEAL
 Product Number: 2977

Product Division:
Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
 Medical Emergency: **1-(888)-314-6171 (24 hours)**
 Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 2 - Moderate Fire: 2 - Moderate Reactivity: 0 - Minimal	Health: 2 - Moderate Fire: 2 - Moderate Reactivity: 0 - Minimal Pers. Prot. Equip.: B - Safety Glasses; gloves

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
*1,2,4-Trimethylbenzene	20-25	95-63-6	125	Not Established	Not Established	No
*Xylene	2-6	1330-20-7	435	655	Not Established	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: 311 °F	Vapor Pressure: 2.7 mm Hg @ 20°F
Vapor Density (AIR = 1): >1	Solubility in Water: Nil
pH: N/A	Specific Gravity (H ₂ O=1): 0.90
Evaporation Rate (but.ac.=1): 0.19	Percent Solid by Weight: 15-20
Physical State: Liquid	
Appearance & Odor: Water clear, slightly viscous, aromatic	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: 107°F	Method Used: ASTM-D56
Flammable Limits: LEL - 1.0 UEL - 6.5	Flame Extension: N/A
Extinguishing Media: Small Fires: extinguish with dry chemical, CO ₂ , or foam. Large Fires: The use of dry chemical or foam is recommended. Water may be an ineffective extinguishing agent.	
Special Fire Fighting Procedures: The use of a SCBA is recommended for fire fighters. Water may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.	
Unusual Fire & Explosive Hazards: This material is combustible and may be ignited by heat or flame. This material will burn, but not ignite readily.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes
Effects of Overexposure- Eye Contact: This product is an eye irritant. Direct contact with the liquid or exposure to its vapors or mists may cause burning, tearing, redness and swelling. Skin Contact: The product may cause skin irritation. Prolonged or repeated exposure to this material may cause redness and burning, drying and cracking of the skin. Persons with pre-existing skin disorders may be more susceptible to the effects of this material. Inhalation: Breathing high concentrations of vapors or mists may cause irritation of the nose and throat, signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Prolonged or repeated exposure to vapors or mists may cause liver and kidney damage. Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties due to the irritant properties of this material. Ingestion: Ingestion of excessive quantities may cause irritation of the digestive tract and signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination, and fatigue). Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.	
Conditions Aggravated by Use: Unknown	

Emergency & First Aid Procedures:

Eyes: Move victim away from exposure to vapors and into fresh air. Remove contact lenses. If irritation or redness develops; seek medical attention. For direct contact; flush the affected eye(s) with clean water for at least 15 minutes. Seek medical attention.
Skin: Removed contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists; seek medical attention.
Ingestion: ***SEEK EMERGENCY MEDICAL ATTENTION*** This material is lightly toxic by ingestion and an aspiration hazard. If victim is drowsy or unconscious; place on the left side with the head down. Do not give anything by mouth. If victim is conscious and alert; vomiting should be induced for ingestion of large amounts (more than 5 ounces in an adult) preferably with syrup of ipecac under direction from a physician or poison center. If syrup of ipecac is not available; vomiting can be induced by gently placing 2 fingers in the back of the throat. If possible; do not leave the victim unattended.
Inhalation: If symptoms of exposure develop; move victim away from source of exposure and into fresh air. If symptoms persist; seek immediate medical attention. If victim is not breathing; artificial respiration should be administered. If breathing difficulties develop; oxygen should be administered by qualified personnel.

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: This product is incompatible with strong acids or bases; oxidizing agents and selected amines.
Hazardous Decomposition Products: CO, CO ₂	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Pick up with absorbent material and dispose of in accordance with state and local regulations.
Waste Disposal Method: Use qualified disposal service.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: The use of respiratory protection is advised when concentrations exceed the established exposure limits (see Section II), additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, systems safe for such locations should be used.
Ventilation: Good general ventilation should be sufficient for most conditions. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type): Solvent resistant gloves
Eye Protection(Specify Type): Goggles
Other Protective Equipment: Impermeable aprons

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep containers tightly closed. Keep containers cool; dry and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use good personal hygiene practice. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize; cut; weld; braze; solder; drill; grind or expose such containers to

heat; flame; sparks or other sources of ignition; they may explode and cause injury or death. "Empty" drums should be completely drained; properly bunged and promptly shipped to the supplier or a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this product; refer to Occupational Safety and Health Administration regulations; ANSI Z49.1; and other governmental and industrial references pertaining to cleaning; repairing; welding or other contemplated operations.

Other Precautions: During use; eliminate any source of ignition. Remove all foodstuffs and packaging materials from area to be coated.

© SCC 01/05/2000

Name: Ronald T. Cook

Title: Manager, Regulatory Affairs

CONCRETE SEAL

Effective Date: 01/05/2000

Supercedes: 09/21/99

Ref: 29 CFR 1910.1200 (OSHA)

Changes: Section I correction

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.