



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):
GREEN SOLUTIONS FLOOR FINISH REMOVER
Product Number: 3505

Product Division:
Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
Medical Emergency: **1-(888)-314-6171 (24 hours)**
Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Corrosive liquids, n.o.s., 8, UN 1760, III, (contains potassium hydroxide)

NFPA Ratings:	HMIS Ratings:
Health: 3 - Serious Fire: 1 - Slight Reactivity: 0 - Minimal	Health: *3 - Serious; Chronic Hazard Fire: 1 - Slight Reactivity: 0 - Minimal Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
*Diethylene glycol monobutyl ether	30	112-34-5	Not Established	Not Established	Not Established	No
Monoethanolamine	5-10	141-43-5	6	15 (ACGIH)	Not Established	No
Potassium hydroxide	1-5	1310-58-3	Not Established	Not Established	2 (NIOSH)	No
Alkyl imino acid sodium salt	1-5	Proprietary	Not Established	Not Established	Not Established	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: 200 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 13.0-13.7	Specific Gravity (H ₂ O=1): 1.02
Evaporation Rate (but. ace. =1): <1	Percent Solid by Weight: 3 - 5
Physical State: Liquid	
Appearance & Odor: Clear liquid, mild odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 200°F	Method Used: ASTM-D56
Flammable Limits: N/A	Flame Extension: N/A
Extinguishing Media: Carbon dioxide, dry chemical, synthetic foam or water.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.	
Unusual Fire & Explosive Hazards: Combustion products are toxic.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes & Oral
Effects of Overexposure- Conditions to Avoid:	CORROSIVE CAUSES SEVERE EYE DAMAGE OR IRRITATION: Symptoms include pain, redness, swelling of the conjunctiva, tissue destruction and possible permanent corneal damage. CAUSES SEVERE SKIN DAMAGE OR IRRITATION: Symptoms include pain, redness, tissue destruction and chemical burns. Harmful contact may not cause immediate pain. Repeated contact may cause a dermatitis. HARMFUL OR FATAL IF SWALLOWED: Causes damage or chemical burns to esophagus and mucous membranes with symptoms of pain, nausea, vomiting and diarrhea. Aspiration of product into the lungs may occur during ingestion or vomiting, resulting in lung injury. HARMFUL IF INHALED: Breathing product vapor or mist may cause irritation or damage of the respiratory tract, with symptoms of nasal discomfort and discharge with chest pain and coughing. HARMFUL IF ABSORBED THROUGH SKIN: Contains monoethanolamine which may cause liver and kidney damage with repeated exposure. DO NOT GET IN EYES, ON SKIN OR CLOTHING. AVOID BREATHING PRODUCT VAPOR OR MIST. DO NOT TASTE OR SWALLOW. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.
Conditions Aggravated by Use:	Preexisting skin; eye and respiratory disorders including asthma and fibrotic pulmonary disease.
Emergency & First Aid Procedures:	
Eyes:	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Call a poison control center or doctor for treatment advice.
Skin:	Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a poison control center or doctor for treatment advice. Wash contaminated clothing before reuse. Destroy contaminated shoes.
Ingestion:	Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting. Drink one or two glasses of water to dilute product. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation or dizziness; move person to fresh air. If not breathing; give artificial respiration. If breathing is difficult; give oxygen. Call a poison control center or doctor for treatment advice.

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong acids and oxidizing agents
Hazardous Decomposition Products: None known	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Contain large spills and transfer the material to appropriate containers for reclamation or disposal. Absorb remaining material or small spills with an inert material and dispose in accordance with federal, state and local regulations.
Waste Disposal Method:	Assure conformance with federal, state and local regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not normally required when good general ventilation is provided. However if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, the use of a NIOSH approved air purifying respirator suitable for the use-conditions and chemicals listed in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Solvent/alkali impervious gloves are recommended to prevent skin contact.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	Solvent /alkali impervious boots are recommended. Use of impervious apron, face shield and other protective equipment should be considered in order to prevent or minimize contact with this product. Eye wash stations and washing facilities should be readily accessible. See 29 CFR 1910.132-138.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep container tightly closed. Store in a cool, dry area. Do not freeze. Do not store above 120°F. Do

not mix with other chemicals. Keep out of reach of children.

Other Precautions: California Proposition 65 :

WARNING: This product contains trace amounts of a chemical known to the State of California to cause cancer or birth defects or other reproductive harm.

© SCC 11/20/2003

Name: Ronald T. Cook

Title: Manager, Regulatory Affairs

**GREEN SOLUTIONS FLOOR FINISH
REMOVER**

Effective Date: 11/20/2003

Supercedes: 04/04/2003

Ref: 29 CFR 1910.1200 (OSHA)

Changes: Update Sections II, IV & IX

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.