



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):
LAMINATE LIGHTS ENDURAMAX PART B
Product Number: 4034 - Part B; 4134 - Part B

Product Division:
Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
Medical Emergency: **1-(888)-314-6171 (24 hours)**
Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 2 - Moderate Fire: 1- Slight Reactivity: 1- Slight	Health: *2 - Moderate; Chronic Hazard Fire: 1- Slight Reactivity: 1- Slight Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Aliphatic polyisocyanate	70-75	Proprietary	0.5 (Bayer)	1 (Bayer)	Not Established	No
Tributoxyethyl phosphate	25-30	78-51-3	Not Established	Not Established	Not Established	No
*1-6-Hexamethylene diisocyanate	< 0.2	822-06-0	0.035 (ACGIH)	Not Established	0.14 (NIOSH)	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: Not Established °F	Vapor Pressure: Not established
Vapor Density (AIR = 1): Not established	Solubility in Water: Dispersible
pH: Not applicable	Specific Gravity (H ₂ O=1): 1.12
Evaporation Rate (but. ace.=1): Not established	Percent Solid by Weight: 0
Physical State: Liquid	
Appearance & Odor: Clear pale yellow liquid, fruity odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: Not determined. Expected to be greater than 200°F	Method Used: Estimate
Flammable Limits: N/A	Flame Extension: N/A
Extinguishing Media: Carbon dioxide, dry chemical, water spray.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray. Do not approach container because of danger of rupturing. Do not permit water to enter containers.	
Unusual Fire & Explosive Hazards: Closed containers may rupture violently when heated or if contents are contaminated with water due to rapid production of carbon dioxide. Combustion generates toxic fumes of Hydrogen cyanide and nitrogen oxides.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes and Oral.
Effects of Overexposure- Conditions to Avoid:	CAUSES EYE IRRITATION: Symptoms may include pain, tearing, swelling and redness. CAUSES SKIN IRRITATION: Symptoms may include redness, swelling, pain, rash, scaling, blistering and possible dermatitis. Can cause dermal sensitization. HARMFUL IF SWALLOWED: Symptoms may include severe irritation of mouth, throat and digestive tract. HARMFUL VAPOR: Inhalation of vapor or mist can cause severe irritation of the nose; throat and lungs. Symptoms may include coughing; chest pain; shortness of breath; impairment of lung function; bronchitis; bronchial spasm; pulmonary edema and pneumonitis. Can cause pulmonary sensitization. Contains aliphatic polyisocyanate and hexamethylene diisocyanate which can cause dermal and pulmonary sensitization, even at low concentrations. Sensitized individuals should not be exposed to any concentration of this material. Evidence exists that cross-sensitization between Hexamethylene diisocyanate and other isocyanates, particularly hydrogenated MDI and TDI can occur. Prolonged or repeated exposure to diisocyanate compounds may cause lung damage. Contains tributoxyethyl phosphate which may cause nervous system effects such as ataxia, breathing abnormalities and tremors with prolonged or repeated contact. AVOID CONTACT WITH EYES, SKIN OR CLOTHING. AVOID BREATHING PRODUCT VAPORS OR MIST. DO NOT SWALLOW OR TASTE. WASH THOROUGHLY AFTER HANDLING AND SHOWER AFTER WORK PERIOD.
Conditions Aggravated by Use:	Individuals with prior allergenic reaction to isocyanates must not be exposed to this product. Use or exposure to this product may aggravate preexisting eye; skin and respiratory disorders. (such as dermatitis; asthma; bronchitis or emphysema)

Emergency & First Aid Procedures:

Eyes:	Immediately flush eyes with water for at least 15 minutes. Remove contact lenses. Get prompt medical attention.
Skin:	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention. Wash contaminated clothing before reuse. Do not take clothing home to be laundered.
Ingestion:	DO NOT induce vomiting. Give milk or water to drink. If vomiting occurs spontaneously keep airway clear. Get immediate medical attention. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation; move person to fresh air. If breathing is difficult give oxygen. Give artificial respiration if breathing has stopped. Get prompt medical attention.

Note to Physician: This product can be a pulmonary sensitizer in some individuals. No specific antidote - treat symptomatically.

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Water - amines -strong bases - alcohols - metal compounds- surface active materials - acids -strong oxidizing agents.
Hazardous Decomposition Products: Under conditions of high heat or fire, decomposition may yield carbon dioxide - carbon monoxide - oxides of nitrogen - hydrogen cyanide and phosphine	Hazardous Polymerization: Product will undergo polymerization at temperatures above 400 F. Polymerization will also occur if contaminated with water or moisture.

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	PPE should be worn by those cleaning up spills and leaks. Ventilate area and contain spill with absorbent material such as vermiculite, sand or fuller's earth. Treat contained spill with decontamination solution consisting of 2% detergent in water and allow to react for at least 10 minutes. Transfer decontaminated liquid and solid material to suitable open containers. Wash down spill area with additional decontamination solution.
Waste Disposal Method:	Dispose of liquid and contaminated solids in accordance with local, state and federal regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not expected to be needed with non-spray application and good ventilation. However, if exposure limits are exceeded (see Section II) use of a NIOSH approved respirator suitable for the conditions of use and substances in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Impervious gloves (butyl rubber or nitrile) are recommended to prevent skin contact.

Eye Protection(Specify Type): Splash goggles are recommended to prevent eye contact.

Other Protective Equipment: Use of other protective clothing such as long sleeved shirt and trousers are recommended. Chemical resistant apron or other impervious clothing may be considered to avoid skin contact. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. For further guidance see 29 CFR 1910.132-138.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Store at a temperature between 34 and 120 F. Do not freeze. Store away from sources of heat. Keep away from sources of ignition and reactive materials. Store in a well ventilated area. Keep material dry to avoid exothermic reaction with water. Keep container tightly closed when not in use.

Other Precautions: Container is hazardous when empty. Do not reuse empty container. Follow all MSDS and label warnings even after container is emptied. Keep out of reach of children.

© SCC 04/05/2004

Name: Ronald T. Cook

Title: Manager, Regulatory Affairs

**LAMINATE LIGHTS ENDURAMAX
PART B**

Effective Date: 04/05/2004

Supersedes: 11/20/2004

Ref: 29 CFR 1910.1200 (OSHA)

Changes: Update Product Numbers

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.