



# Spartan Chemical Company, Inc.

## Material Safety Data Sheet

### SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

**METAL SPRAY LF**

Product Number: 2824

Product Division:

**IPG**

**Spartan Chemical Company, Inc.**  
**1110 Spartan Drive**  
**Maumee OH 43537**

Product/Technical Information: **1-(800)-537-8990**

Medical Emergency: **1-(888)-314-6171 (24 hours)**

Chemical Leak/Spil Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Cleaning compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
<b>Health:</b> 1- Slight <b>Fire:</b> 0 - Minimal <b>Reactivity:</b> 0 - Minimal	<b>Health:</b> 1- Slight <b>Fire:</b> 0 - Minimal <b>Reactivity:</b> 0 - Minimal <b>Pers. Prot. Equip.:</b> B - Safety Glasses; gloves

### SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			Carcinogen
			TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	CEILING mg/m <sup>3</sup>	
NO HAZARDOUS INGREDIENTS AS DEFINED BY 29 CFR 1910.1200 AT 1% OR GREATER CONCENTRATION	NA -	NA -	NA -	NA -	NA -	No -

### SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure: 18 mm Hg @ 75°F
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 8.8-9.1 (concentrate)	Specific Gravity (H <sub>2</sub> O=1): 1.03
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 18-20
Physical State: Liquid	
Appearance & Odor: Amber, water thin liquid	

### SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: None	Method Used: ASTM-D56
Flammable Limits: N/A	Flame Extension: N/A
Extinguishing Media: N/A	
Special Fire Fighting Procedures: N/A	
Unusual Fire & Explosive Hazards: N/A	

**SECTION V: HEALTH HAZARD DATA**

Threshold Limit Value: Not established	Primary Routes of Entry: Skin Contact
Effects of Overexposure- May cause skin and eye irritation. Do not get into eyes. Conditions to Avoid:	
Conditions Aggravated by Use: Unknown	
<b>Emergency &amp; First Aid Procedures:</b>	
Eyes: In case of contact; immediately flush eyes with water for at least 15 minutes; remove contact lenses. Call a physician.	
Skin: Flush skin with water. Remove and wash clothing before reuse.	
Ingestion: If swallowed induce vomiting; call a physician immediately. Never give anything by mouth to an unconscious person.	

**SECTION VI: REACTIVITY DATA**

Stability: Stable	Incompatible Materials: Strong acids and strong oxidizing agents
Hazardous Decomposition Products: None known	Hazardous Polymerization: Will Not Occur

**SECTION VII: SPILL OR LEAK PROCEDURES**

Steps to be Taken in Case Material is Released or Spilled: Flush with water to sanitary sewer system.
Waste Disposal Method: Same as above

**SECTION VIII: SPECIAL PROTECTION INFORMATION**

Respiratory Protection: None required
Ventilation: Good general ventilation should be sufficient for most conditions. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type): Rubber gloves
Eye Protection(Specify Type): OSHA approved chemical resistant goggles
Other Protective Equipment: None

**SECTION IX: SPECIAL PRECAUTIONS**

Precautions; Handling & Storing: None necessary
Other Precautions: None

© SCC 09/27/99

**METAL SPRAY LF**

Ref: 29 CFR 1910.1200 (OSHA)

Name: Ronald T. Cook

Effective Date: 09/27/99

Changes: Address and Format

Title: Manager, Regulatory Affairs

Supercedes: 02/12/98

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.