

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): **NEW GENERATION 100 - OFF WHITE (Part A)**

Product Division: **Janitorial**

Product Number: 5875

Spartan Chemical Company, Inc.

Product/Technical Information: 1-(800)-537-8990

1110 Spartan Drive Maumee OH 43537 Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spil Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: 1- Slight
Fire: 1- Slight	Fire: 1- Slight
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: B - Safety Glasses; gloves

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

				Table Z-1-A		
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	Carcinoge n
Bisphenol-A epoxy Oxirane C12-C14	80-85 15-20	25068-38-6 68609-97-2	Not Established Not Established	Not Established Not Established	Not Established Not Established	No No

SECTION III: PHYSICAL DATA

Boiling Point: >400 °F	Vapor Pressure:	<0.1 mm Hg @ 75°F
Vapor Density (AIR = 1): Heavier than air	Solubility in Water:	Insoluble
pH: N/A	Specific Gravity (H ₂ O=1):	1.14 (9.55 lbs./gal.)
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight:	100
Physical State: Liquid		
Appearance & Odor: Off white, odorless liquid		

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

monoxide gas.

Flash Point:	(Setaflash) >200°F	Method Used: ASTM-D3278
Flammable Limits:	N/A	Flame Extension: N/A
Extinguishing Media: Use water fog, "alcohol" foam, dry chemical or Carbon dioxide.		
Special Fire Fighting Procedures: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.		

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established	Primary Routes of Entry: Skin Contact, Eyes			
Effects of Overexposure- Avoid eye and skin contact. Do not allow to cure on skin. Avoid use of solvents for skin clean-up. Conditions to Avoid:				
Conditions Aggravated by Use: May cause skin sensitization;	rated by Use: May cause skin sensitization; irritation in some individuals.			
Emergency & First Aid Procedures:				
Eyes: Hold eyelids apart and immed Call a physician.	Hold eyelids apart and immediately flush with water for at least 15 minutes. Remove contact lenses. Call a physician.			
1 9	Flush with water for 15 minutes followed by wash with soap and water. s and shoes. Wash before reuse.			
Ingestion: Do NOT induce vomiting; seel	k medical attention.			

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Oxidizers. Strong acids; bases; amines and mercaptans can cause polymerization.
Hazardous Decomposition Products: Carbon monoxide. Aldehydes and acids may be formed during combustion. Not readily ignitable.	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case

Material is Released or Spilled: Absorb and collect with inert material. Collect for disposal.

Waste Disposal Method: Comply with all Federal, State and Local Regulations. This material is not defined as a hazardous

waste under current RCRA regulations. Cure with Part B to create innocuous solid water.

Supercedes:

02/10/98

SECTION VIII: SPECIAL PROTECTION INFORMATION

_	Respiratory Protection:	: Not required under normal conditions		
_	Ventilation:	Good general ventilation should be sufficient for most conditions.		
_	Protective Gloves(Specify Type):	Impervious neoprene, latex, or vinyl gloves		
	Eye Protection(Specify Type):	Standard safety goggles		
	Other Protective Equipment:	An eye wash facility and/or source of fresh water should be available. Wash before eating, smoking, or using toilet. Wash promptly if skin becomes contaminated.		

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Keep away from heat and flam	e.	
Other Precautions:	Do not apply to hot surfaces. Isolate work area.	Fresh; wet; uncured coatings can be very slippery.	Use warning signs.

© SCC 09/27/99 Name: Ronald T. Cook Title: Manager, Regulatory Affairs

NEW GENERATION 100 - OFF

Ref: 29 CFR 1910.1200 (OSHA)

WHITE (Part A)

Effective Date: 09/27/99

Changes: Address and Format

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.