

# Spartan Chemical Company, Inc. **Material Safety Data Sheet**

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): Product Division: **NEW GENERATION 50 BRIGHT GREY Janitorial** 

(PART A)

Product Number: 5850

Product/Technical Information: 1-(800)-537-8990 Spartan Chemical Company, Inc.

1110 Spartan Drive Medical Emergency: 1-(888)-314-6171 (24 hours)

Maumee OH 43537 Chemical Leak/Spil Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 2 - Moderate	Health: 2 - Moderate
Fire: 1- Slight	Fire: 1- Slight
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: B - Safety Glasses; gloves

#### SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

					3 3	
				Table Z-1-A		
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	Carcinoge n
Bisphenol-A based epoxy *2-Propoxyethanol Aromatic solvent	35-40 9 01-05	68334-76-9 2807-30-9 64742-94-5	Not Established Not Established Not Established	Not Established Not Established Not Established	Not Established Not Established Not Established	No No No

Comment: \*This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARÁ) and of 40 CFR 372. This product does not contain any California Proposition 65 designated chemicals.

## SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure:	1.3 mm Hg @ 75°F
Vapor Density (AIR = 1): Unknown	Solubility in Water:	Complete
pH: 8.5-9.5	Specific Gravity (H <sub>2</sub> O=1):	1.04
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight:	40-45
Physical State: Liquid	Volatile Organic Compounds:	261 g/L (ACM), When combined with $\ensuremath{\epsilon}$ B: 275 g/L (ACM)

Appearance & Odor: White, creamy emulsion; slight solvent odor

# SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: >200°F	Method Used: ASTM-D56
Flammable Limits: N/A	Flame Extension: N/A
Extinguishing Media: Use carbon dioxide or dry chemical for	or small fires; aqueous foam or water for large fires.

Special Fire Fighting Procedures: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective

equipment when entering confined areas where potential for exposure to vapors or products of

combustion exists.

Unusual Fire & Explosive Hazards: Closed containers may rupture due to build up of pressure when exposed to extreme heat.

## **SECTION V: HEALTH HAZARD DATA**

Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes		
Effects of Overexposure- Causes eye and skin irritation. Harmful if swallowed. May cause respiratory irritation. Avoid eye Conditions to Avoid: skin contact. Do not swallow. Avoid breathing vapors or mist. Contains solvents which may cinjury to liver; kidneys; bone marrow; blood cells and central nervous system after repe overexposure and prolonged use.			
Unknown			
Emergency & First Aid Procedures:			
In case of contact; immediately flush Call a physician	n eyes with water for at least 15 minutes. Remove contact lenses.		
Do not allow to cure on skin. Rinse in and/or skin sensitization in some indiv	mmediately with water and detergent. May cause allergic reaction viduals.		
Get immediate medical attention.			
In case of respiratory irritation; Move	e person to fresh air.		
	Causes eye and skin irritation. Harm skin contact. Do not swallow. Avoi injury to liver; kidneys; bone ma overexposure and prolonged use.  Unknown  es:  In case of contact; immediately flust Call a physician  Do not allow to cure on skin. Rinse i and/or skin sensitization in some indicated immediate medical attention.		

## SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong acids; bases; amines and mercaptans can cause polymerization.	
Hazardous Decomposition Products: Fumes produced when heated to decomposition may include: carbon monoxide and carbon dioxide.	Hazardous Polymerization: Will Not Occur	

#### SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case		
Material is Released or Spilled:	Absorb with inert material and collect for disposal.	Flush area with water

Waste Disposal Method: Incinerate or use biological treatment in accordance with Federal, state and local regulations. This material is not defined as hazardous waste under current RCRA regulations.

#### SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Wear a properly fitted NIOSH/MSHA approved respirator whenever exposure to vapor/mist is likely unless levels are below applicable limits.
Ventilation:	Good general ventilation should be sufficient for most conditions. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	For operations where contact can occur, wear impervious (neoprene) gloves.
Eye Protection(Specify Type):	Safety goggles
Other Protective Equipment:	An eye wash facility and/or source of fresh water should be available.

#### SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep from freezing.

Other Precautions: Avoid contact with skin. Do not apply to hot surfaces. Avoid excessive heat.

© SCC 09/27/99 Name: Ronald T. Cook Title: Manager, Regulatory Affairs

**NEW GENERATION 50 BRIGHT** 

**GREY** (PART A)

Ref: 29 CFR 1910.1200 (OSHA) Changes: Update Section V, Address and Format

Effective Date: 09/27/99

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.

Supercedes:

02/10/98