



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):
NEW GENERATION PRIMERCOAT (Part A)
Product Number: 5890

Product Division:
Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
Medical Emergency: **1-(888)-314-6171 (24 hours)**
Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 2 - Moderate Fire: 1- Slight Reactivity: 0 - Minimal	Health: 2 - Moderate Fire: 1- Slight Reactivity: 0 - Minimal Pers. Prot. Equip.: B - Safety Glasses; gloves

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Bisphenol-A based epoxy *2-Propoxyethanol	30 10-15	68334-76-9 2807-30-9	Not Established Not Established	Not Established Not Established	Not Established Not Established	No No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: >300 °F	Vapor Pressure: <1.3 mm Hg @ 75°F
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 8.5-10.0	Specific Gravity (H ₂ O=1): 1.04
Evaporation Rate (but.ace.=1): < 1	Percent Solid by Weight: 30
Physical State: Liquid	Volatile Organic Compounds: When combined with Part B: 350 g/L (l)
Appearance & Odor: White emulsion; slight solvent odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: >200°F	Method Used: ASTM-D56
Flammable Limits: N/A	Flame Extension: N/A
Extinguishing Media: Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.	
Special Fire Fighting Procedures: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.	
Unusual Fire & Explosive Hazards: Closed containers may rupture due to build up of pressure when exposed to extreme heat.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes
Effects of Overexposure- Causes eye and skin irritation. Harmful if swallowed. May cause respiratory irritation. Avoid eye and skin contact. Do not swallow. Avoid breathing vapors or mist. Contains solvents which may cause injury to liver; kidneys; bone marrow; blood cells and central nervous system after repeated overexposure and prolonged use.	
Conditions Aggravated by Use: Unknown	
Emergency & First Aid Procedures:	
Eyes: Hold eyelids apart and immediately flush with water for at least 15 minutes. Remove contact lenses. Call a physician.	
Skin: Do not allow to cure on skin. Rinse immediately with water and detergent. May cause allergic reaction and/or skin sensitization in some individuals.	
Ingestion: Call a physician immediately.	
Inhalation: In case of respiratory irritation; move person to fresh air.	

SECTION VI: REACTIVITY DATA

Stability: Stable. Curing reaction is exothermic	Incompatible Materials: Strong acids; bases; amines and mercaptans can cause polymerization.
Hazardous Decomposition Products: Fumes produced when heated to decomposition may include: Carbon monoxide and carbon dioxide.	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Absorb and collect with inert material and collect for disposal. Flush area with water.
Waste Disposal Method: Incinerate or use biological treatment in accordance with Federal, state and local Regulations. This material is not defined as a hazardous waste under current RCRA regulations. Cure with Part B to create innocuous solid water.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: Wear a properly fitted NIOSH/MSHA approved respirator whenever exposure to vapor/mist is likely unless levels are below applicable limits.
Ventilation: Good general ventilation should be sufficient for most conditions.
Protective Gloves(Specify Type): For operations where contact can occur, wear impervious (neoprene) gloves
Eye Protection(Specify Type): Safety goggles
Other Protective Equipment: An eye wash facility and/or source of fresh water should be available.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep from freezing.
Other Precautions: Avoid contact with skin. Do not apply to hot surfaces. Avoid excessive heat.

© SCC 09/27/99

**NEW GENERATION PRIMERCOAT
(Part A)**

Ref: 29 CFR 1910.1200 (OSHA)

Name: Ronald T. Cook

Effective Date: 09/27/99

Changes: Update Section V, Address and Format

Title: Manager, Regulatory Affairs

Supersedes: 02/10/98

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.