



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

STAINLESS STEEL CLEANER AND POLISH(AEROSOL)

Product Number: 6310

Product Division:

Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**

Medical Emergency: **1-(888)-314-6171 (24 hours)**

Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: ORM-D, Consumer commodity, cleaning compounds, aerosol, n.o.s.

| NFPA Ratings: | HMIS Ratings: |
|--|---|
| Health: 1- Slight Fire: 0 - Minimal Reactivity: 1- Slight | Health: 1- Slight Fire: 0 - Minimal Reactivity: 1- Slight Pers. Prot. Equip.: A - Safety Glasses |

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

| Chemical Name(s) | %Wt | CAS Registry No. | Table Z-1-A | | | Carcinogen |
|--------------------------|-------|------------------|-----------------------|------------------------|---------------------------|------------|
| | | | TWA mg/m ³ | STEL mg/m ³ | CEILING mg/m ³ | |
| Odorless mineral spirits | 05-10 | 8052-41-3 | 350 (NIOSH) | Not Established | 1800 (NIOSH) | No |
| Propane | 05-10 | 74-98-6 | 1800 | Not Established | Not Established | No |
| Isobutane | 01-05 | 75-28-5 | 1900 (NIOSH) | Not Established | Not Established | No |

SECTION III: PHYSICAL DATA

| | |
|---|---|
| Boiling Point: N/A | Vapor Pressure: Unknown |
| Vapor Density (AIR = 1): Unknown | Solubility in Water: Forms an emulsion |
| pH: 8.8 | Specific Gravity (H ₂ O=1): 0.97 |
| Evaporation Rate (but.ace.=1): >1 | Percent Solid by Weight: 7.9 |
| Physical State: Liquid | |
| Appearance & Odor: Creamy sprayed film, lemon fragrance | |

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

| | |
|---|-----------------------|
| Flash Point: None | Method Used: ASTM-D56 |
| Flammable Limits: N/A | Flame Extension: NA |
| Extinguishing Media: Water fog, dry chemical, CO ₂ | |
| Special Fire Fighting Procedures: Use equipment or shielding required to protect personnel against bursting, rupturing or venting containers. | |
| Unusual Fire & Explosive Hazards: At elevated temperatures (over 54°C/130°F) container may vent, rupture or burst. | |

SECTION V: HEALTH HAZARD DATA

| | |
|--|---|
| Threshold Limit Value: Not Established | Primary Routes of Entry: Inhalation, Skin Contact |
| Effects of Overexposure- Avoid skin and eye contact, may cause skin or eye irritation. Conditions to Avoid: | |
| Conditions Aggravated by Use: Unknown | |
| Emergency & First Aid Procedures: | |
| Eyes: In case of contact; flush eyes with water for at least 15 minutes. Remove contact lenses. | |
| Skin: Wash off in flowing water or shower. Wash clothing before reuse. | |
| Ingestion: Induce vomiting if large amounts are ingested. Seek medical attention. | |

SECTION VI: REACTIVITY DATA

| | |
|--|---|
| Stability: Stable | Incompatible Materials: Oxidizing material; acids |
| Hazardous Decomposition Products: None known | Hazardous Polymerization: Will Not Occur |

SECTION VII: SPILL OR LEAK PROCEDURES

| |
|---|
| Steps to be Taken in Case Material is Released or Spilled: Dilute with water and flush into sanitary sewer system. |
| Waste Disposal Method: Do not incinerate or puncture aerosol container. Dispose of in accordance with state or local regulations. |

SECTION VIII: SPECIAL PROTECTION INFORMATION

| |
|---|
| Respiratory Protection: None required |
| Ventilation: Good general ventilation should be sufficient for most conditions. Local exhaust ventilation may be necessary for some operations. |
| Protective Gloves(Specify Type): None required |
| Eye Protection(Specify Type): Safety glasses while spraying |
| Other Protective Equipment: None required |

SECTION IX: SPECIAL PRECAUTIONS

| |
|---|
| Precautions; Handling & Storing: Contents under pressure. Do not use near fire, sparks, or flame. Do not store where temperatures could exceed 120°F. |
| Other Precautions: None |

© SCC 11/05/99

Name: Ronald T. Cook

Title: Manager, Regulatory Affairs

**STAINLESS STEEL CLEANER AND
POLISH (AEROSOL)**

Effective Date: 11/05/99

Supersedes: 09/24/99

Ref: 29 CFR 1910.1200 (OSHA)

Changes: Section II correction

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.