



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

TOUGH ON GREASE

Product Number: 2034

Product Division:

Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
 Medical Emergency: **1-(888)-314-6171 (24 hours)**
 Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Cleaning compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 2 - Moderate Fire: 0 - Minimal Reactivity: 0 - Minimal	Health: 2 - Moderate Fire: 0 - Minimal Reactivity: 0 - Minimal Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Nonyl phenol ethoxylate	1-5	9016-45-9	Not Established	Not Established	Not Established	No
Dipropylene glycol n-propyl ether	1-5	29911-27-1	Not Established	Not Established	Not Established	No
Sodium tripolyphosphate	-	-	-	-	-	-
Sodium xylene sulfonate	1-5	1300-72-7	Not Established	Not Established	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 11.7 - 12.3	Specific Gravity (H ₂ O=1): 1.04
Evaporation Rate (but.ace. = 1): <1	Percent Solid by Weight: 5-10
Physical State: Liquid	
Appearance & Odor: Clear liquid, mild solvent odor.	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not support combustion. Use extinguishing media appropriate for surrounding fire.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.	
Unusual Fire & Explosive Hazards: Combustion products are toxic.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes & Oral
Effects of Overexposure- Conditions to Avoid:	CAUSES EYE AND SKIN IRRITATION: Symptoms include pain, redness, swelling of the conjunctiva and tissue damage. MAY BE HARMFUL IF SWALLOWED: Symptoms include pain, nausea, vomiting and diarrhea. BREATHING PRODUCT VAPORS OR MIST MAY CAUSE RESPIRATORY IRRITATION: Symptoms may include nasal discomfort and coughing. Avoid contact with eyes, skin and clothing. Avoid breathing product vapors or mists. Do not swallow. Use with adequate ventilation. Wash thoroughly after handling.
Conditions Aggravated by Use:	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and fibrotic pulmonary disease.

Emergency & First Aid Procedures:

Eyes:	Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Remove contaminated clothing. Flush skin with water for at least 15 minutes. Get medical attention if irritation persists. Wash contaminated clothing before reuse.
Ingestion:	Do not induce vomiting. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation or dizziness; move person to fresh air. If not breathing; give artificial respiration. If breathing is difficult; give oxygen. Get medical attention if irritation persists.

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong acids and oxidizing agents
Hazardous Decomposition Products: Not established	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Dike and contain spill with inert material (sand, earth, commercial absorbent, etc.) and transfer to containers for disposal. Rinse area with water and flush to sanitary sewer. Keep spill out of storm sewers and waterways.
Waste Disposal Method:	Dispose of in compliance with all federal, state and local laws and regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not normally required when good general ventilation is provided. However if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, the use of a NIOSH approved respirator suitable for the use-conditions and chemicals listed in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber or other impervious gloves.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Keep container tightly closed. Store in a cool, dry area. Do not freeze. Do not store above 120°F. Do not mix with other chemicals. Keep out of reach of children
Other Precautions:	California Proposition 65 Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

© SCC 06/01/2004 Name: Ronald T. Cook Title: Manager, Regulatory Affairs
TOUGH ON GREASE Effective Date: 06/01/2004 Supersedes: 09/24/99
Ref: 29 CFR 1910.1200 (OSHA) Changes: Update Sections I, II, III, IV, V, VII, VIII & IX

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.