

POLYESTERLINK

MSDS ID: N0498340

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: polyesterLINK

Product Descriptor: METAL TREATING COMPOUND

MANUFACTURER: JOHNSON DIVERSEY, INC.

EMERGENCY PHONE NUMBER: (800) 851-7145

3630 E. KEMPER ROAD

CINCINNATI, OH. 45241

II. HAZARDOUS COMPONENTS

Component Name	CAS Number	%	Exposure Limits	Units
HEXYLENE GLYCOL	107-41-5	>30%	TLV C 125 PEL C 1MG/M3 25	

III. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING - Product contains irritating or harmful chemical and solvents. Causes eye and skin irritation or burns, and possible respiratory irritation. May be harmful if swallowed. Do not get in eyes, on skin or clothing. Wear eye protection, rubber gloves, protective clothing and footwear. Wash after handling. Avoid breathing dust, mist, or vapors. Heat and evaporation may release vapors that cause respiratory irritation, dizziness or headache. Wear respiratory protection in enclosed areas.

POSSIBLE ROUTES OF ENTRY: Inhalation and ingestion.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE: EYES: Irritation with pain, swelling and redness may develop.

SKIN: Causes skin irritation. INGESTION: May cause nausea and diarrhea. INHALATION: Dust, spray or mists may cause burns or irritation.

CHRONIC: Same as acute effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Dermatitis, sensitive skin, pulmonary function and asthma.

TARGET ORGAN(S) OF CHEMICAL HAZARD(S): Eyes, skin and respiratory tract.

IV. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. Get medical attention.

SKIN: Flush skin with plenty of water and wash with mild soap. If irritation develops, get medical attention.

INGESTION: If swallowed, rinse mouth with water. Dilute by drinking several glasses of water. DO NOT induce vomiting. If patient vomits, rerinse mouth. Get immediate medical attention. NOTE: Never give fluids by mouth to an unconscious person.

INHALATION: Remove to fresh air and seek medical attention.

MATERIAL SAFETY DATA SHEET

Page 2 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

POLYESTERLINK

MSDS ID: N0498340

V. FIRE FIGHTING MEASURES

FLASH POINT (degrees F): >212 FLAME EXTENSION: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME: LEL: N/E UEL: N/E
UNUSUAL FIRE OR EXPLOSIVE HAZARDS: Toxic fumes or vapor may form during fire.
EXTINGUISHING MEDIA: Water spray, CO2, foam or dry powder.
FIRE FIGHTING INSTRUCTIONS: Wear full protective gear and positive pressure breathing apparatus SCBA) in fire area.
SPECIAL INSTRUCTIONS: Spilled product may cause slippery surface and fall hazard.

VI. ACCIDENTAL RELEASE MEASURES

IF MATERIAL IS RELEASED OR SPILLED:
Flush small amounts to drain. Collect and return large amounts to container.
This product does not contain a reportable quantity (RQ) under CERCLA.

VII. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Store drums in cool areas out of direct sunlight and away from combustibles.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses with side shields. Chemical goggles if contact or splash hazard exists.
PROTECTIVE GLOVES: Solvent resistant.
RESPIRATORY PROTECTION: Use NIOSH/MSHA approved respirator where TLV/PEL may be exceeded.
OTHER PROTECTIVE CLOTHING/EQUIPMENT: Eyewash and safety shower in area if contact or splash hazard exists.
ENGINEERING CONTROLS:
VENTILATION: Good general ventilation should be sufficient to control airborne levels.

IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: CLEAR LIQUID, SLIGHT ODOR.

BOILING POINT (DEG F): >200 FREEZING POINT: -58 F
SPECIFIC GRAVITY/BULK DENSITY: 0.941
pH: 5.7 pH 1% SOLUTION: 6.6
VOLATILE BY VOLUME: 0
SOLUBILITY IN WATER: Soluble
VAPOR PRESSURE(mmHg): 0.05 at 20 C VAPOR DENSITY: N/E

X. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Product stable.
INCOMPATIBILITY WITH OTHER MATERIALS: Acids; Oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion forms; oxides of carbon

POLYESTERLINK

MSDS ID: N0498340

X. STABILITY AND REACTIVITY (Cont.)

HAZARDOUS POLYMERIZATION: None known.

XI. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL TESTING: Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

TOXICITY TEST DATA:

Hexylene Glycol:

Acute Oral LD50	rat	4790 mg/kg
Acute Oral LD50	mouse	3500 mg/kg

XII. ECOLOGICAL INFORMATION

Toxicological testing has not been performed on the product. Listed below is the available toxicology test data for components of the product.

ECOTOXICITY TEST DATA:

Hexylene Glycol:

LC50 (96 hrs.) Pimephales promelas 10,700 mg/l

ENVIRONMENTAL FATE: No data available.

XIII. DISPOSAL CONSIDERATIONS

RCRA REGULATED: Not Regulated.

Discharge diluted product to industrial sewer in accordance with discharge permit or local POTW regulations. Use product in container until empty. Rinse container with water. Recycle or dispose of container according to product labeling or governmental regulations.

XIV. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up to date shipping information.

XV. REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA: All ingredients in this product are on TSCA inventory.

HAPS: NONE

VOC CONTENT (EPA Method 24A): % VOC: 0 Lb/Gal VOC: 0

CERCLA/EPCRA:

Section 313 Toxic Chemicals:

NONE

SARA Section 311/312:

ACUTE: YES CHRONIC: NO FIRE: YES REACTIVITY: NO

SUDDEN RELEASE OF PRESSURE: NO

LISTED CARCINOGEN: None

NTP: NO IARC: NO OSHA: NO

HMIS RATINGS: HEALTH: 2 FIRE: 1 REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: B

MATERIAL SAFETY DATA SHEET

Page 4 of 4
Revised 2/02/04
Replaces 8/12/03
Printed 2/03/04

POLYESTERLINK

MSDS ID: N0498340

XV. REGULATORY INFORMATION (Cont.)

NFPA RATING: HEALTH: 0 FIRE: 1 REACTIVITY:0 SPECIAL:NONE

STATE RIGHT-TO-KNOW INFORMATION:

HEXYLENE GLYCOL - CAS# 107-41-5

TRADE SECRET - NJ-TSRN-DL-00034

TRADE SECRET - NJ-TSRN-DL-00035

CALIFORNIA PROPOSITION 65:

None of the ingredients are on the California proposition 65 list.

XVI. OTHER INFORMATION

Disclaimer: The information contained in this material safety data sheet is based on the knowledge of this specific product and current national legislation. It applies to the product as sold, use dilutions may be less hazardous. It may not be valid for this material if used in combination with any other materials or in a process. It is the user's responsibility to evaluate the handling, and use.