

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 05-Aug-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Product Name: Product Number: Recommended Use: Uses Advised Against:	NAD-75 0075 Stripping solution For Industrial and Institutional Use Only			
Manufacturer/Supplier:	Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com			
24 Hour Emergency Phone Number Medical Emergency/Information Transportation/Spill/Leak:				
	2. HAZARDS IDENTIFICATION			
GHS Classification Skin Corrosion/Irritation: Serious Eye Damage/Eye Irritation:	Category 1 Category 1			
GHS Label Elements Signal Word:	Danger			
Symbols:	Danger			
Hazard Statements:	Causes severe skin burns and serious eye damage.			
<u>Precautionary Statements:</u> Prevention:	Do not breathe mist, vapors or spray. Wash hands and any exposed skin thoroughly after handling. Wear protective gloves. Wear eye / face protection. Wear protective clothing.			
Response:	IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.			
-Eyes	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
-Skin	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse.			
-Inhalation:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for			
-Ingestion: -Specific Treatment:	breathing. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.			
Storage: Disposal:	Store locked up. Dispose of contents and container in accordance with local, state and federal regulations.			
Hazards Not Otherwise Classified:	Not Applicable			

Other Information:

- Corrosive.
- · Harmful if swallowed
- Harmful contact may not cause immediate pain.
- Inhalation of vapors or mist may cause respiratory irritation or damage.
- Keep out of reach of children.

• NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	60-100
sodium silicate	1344-09-8	1-5
monoethanolamine	141-43-5	1-5
sodium hydroxide	1310-73-2	1-5
sodium xylene sulfonate	1300-72-7	1-5
tetrasodium ethylenediaminetetraacetate	64-02-8	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
-Skin Contact:	Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse.
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
-Ingestion:	Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.
Note to Physicians:	NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Product does not support combustion, Use extinguishing agent suitable for type of surrounding fire
Specific Hazards Arising from the Chemical:	Dried product is capable of burning. Combustion products are toxic.
Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.		
Environmental Precautions:	Do not rinse spill onto the ground, into storm sewers or bodies of water.		
Methods for Clean-Up:	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with		
	non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite)		
	and place in container for disposal according to local / national regulations (see Section 13).		

7. HANDLING AND STORAGE

Advice on Safe Handling:

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

Storage Conditions:

atter handling. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
monoethanolamine	STEL: 6 ppm	TWA: 3 ppm	IDLH: 30 ppm
141-43-5	TWA: 3 ppm	TWA: 6 mg/m ³	TWA: 3 ppm
		(vacated) TWA: 3 ppm	TWA: 8 mg/m ³
		(vacated) TWA: 8 mg/m ³	STEL: 6 ppm
		(vacated) STEL: 6 ppm	STEL: 15 mg/m ³
		(vacated) STEL: 15 mg/m ³	
sodium hydroxide	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³	IDLH: 10 mg/m ³
1310-73-2		(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Personal Protective Equipment	Eye wash stations and showe product is handled.	er facilities should be readily acce	essible in areas where the
Eye/Face Protection:	Wear splash goggles. For sev	vere use-conditions, wear a face	shield over the goggles
Skin and Body Protection:	Wear rubber or other chemica of other protective equipment with this product.	al-resistant gloves and solvent / a should be considered in order to	Ikali resistant boots. The use
Respiratory Protection:	NIOSH/MSHA approved resp 3 should be considered.	s are exceeded or respiratory irrit irator suitable for the use-condition	
General Hygiene Considerations:	See 29 CFR 1910.132-138 fo	d skin thoroughly after handling. r further guidance.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid		
Color:	Red		
Odor:	Sweet		
pH:	13.0-13.6		
Melting Point / Freezing Point:	No information available.		
Boiling Point / Boiling Range:	100 °C / 212 °F		
Flash Point:	> 100 °C / > 212 °F ASTM D56		
Evaporation Rate:	< 1 (Butyl acetate = 1)		
Flammability (solid, gas)	No information available.		
Upper Flammability Limit:	No information available.		
Lower Flammability Limit:	No information available.		
Vapor Pressure:	No information available.		
Vapor Density:	No information available.		
Specific Gravity:	1.06		
Solubility(ies):	Soluble in water		
Partition Coefficient:	No information available.		
Autoignition Temperature:	No information available.		
Decomposition Temperature:	No information available.		
Viscosity:	No information available.		

10. STABILITY AND REACTIVITY

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical Stability:	Stable under normal conditions.
Possibility of Hazardous Reactions:	Contact with aluminum or other reactive metals may release hydrogen gas.
Conditions to Avoid:	Extremes of temperature and direct sunlight.
Incompatible Materials:	Strong oxidizing agents. Strong acids.
Hazardous Decomposition	May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.
Products:	

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Symptoms of Exposure:	Eyes, Skin, Ingestion, Inhalation.
-Eye Contact:	Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.
-Skin Contact:	Pain, redness, blistering and possible chemical burn.
-Inhalation:	Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and coughing.
-Ingestion:	Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and diarrhea.
Immediate, Delayed, Chronic Effect	ts
Product Information:	Data not available or insufficient for classification.
Target Organ Effects: Numerical Measures of Toxicity	Central nervous systemEyes. Respiratory SystemSkin.
I he following acute toxicity estimates	s (ATE) are calculated based on the GHS document.
•	

ATEmix (oral):	15384 mg/kg
ATEmix (dermal):	24602 mg/kg
ATEmix (inhalation-dust/mist):	59.4 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available
sodium silicate 1344-09-8	= 1153 mg/kg (Rat)	> 4640 mg/kg (Rabbit)	Not Available
monoethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg (Rabbit) = 1025 mg/kg (Rabbit)	Not Available
sodium hydroxide 1310-73-2	Not Available	= 1350 mg/kg (Rabbit)	Not Available
sodium xylene sulfonate 1300-72-7	= 7200 mg/kg(Rat)	Not Available	Not Available
tetrasodium ethylenediaminetetraacetate 64-02-8	= 10 g/kg (Rat)	Not Available	Not Available

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity	otoxicity					
Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea		
sodium silicate 1344-09-8	Not Available	301 - 478: 96 h Lepomis macrochirus mg/L LC50 3185: 96 h Brachydanio rerio mg/L LC50 semi-static	Not Available	216: 96 h Daphnia magna mg/L EC50		

monoethanolamine	15: 72 h Desmodesmus	227: 96 h Pimephales	Not Available	65: 48 h Daphnia magna
141-43-5	subspicatus mg/L EC50	promelas mg/L LC50		mg/L EC50
	3	flow-through 3684: 96 h		3
		Brachydanio rerio mg/L		
		LC50 static 300 - 1000: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static 114 - 196: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 200: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 flow-through		
sodium hydroxide	Not Available	45.4: 96 h Oncorhynchus	Not Available	Not Available
1310-73-2		mykiss mg/L LC50 static		
tetrasodium	1.01: 72 h Desmodesmus	41: 96 h Lepomis	Not Available	610: 24 h Daphnia magna
ethylenediaminetetraacetate	subspicatus mg/L EC50	macrochirus mg/L LC50		mg/L EC50
64-02-8		static 59.8: 96 h Pimephales		-
		promelas mg/L LC50 static		

Persistence and Degradability:	No information available.
Bioaccumulation:	No information available.
Other Adverse Effects:	No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Contaminated Packaging: US EPA Waste Number: Dispose of in accordance with federal, state and local regulations. Dispose of in accordance with federal, state and local regulations. D002

14. TRANSPORT INFORMATION

<u>DOT:</u> UN/ID No: Proper Shipping Name: Hazard Class: Packing Group: Special Provisions:	UN1760 Corrosive liquids, n.o.s., (contains ethanolamine) 8 II For totes add: I.B.C. Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.
IMDG: UN/ID No: Proper Shipping Name: Hazard Class: Packing Group: Additional information:	UN1760 Corrosive liquids, n.o.s., (contains ethanolamine) 8 II For totes add: I.B.C.

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

<u>SARA 313</u>

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories	
Acute Health Hazard:	Yes
Chronic Health Hazard:	No
Fire Hazard:	No
Sudden release of pressure hazard:	No

Revision Date: 05-Aug-2015

Reactive Hazard:

No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION						
NFPA HMIS	Health Hazards: 3 Health Hazards: 3	Flammability: 0 Flammability: 0	Instability: 0 Physical Hazards: 0	Special: N/A		
Revision Date: Reasons for Revision:	05-Aug-2015 Section 14 and 15					

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet