

Version 2.0	Revision Date 04/23/2018	Print Date 07/23/2018
SECTION 1. PRODUCT AND COMP	ANY IDENTIFICATION	

Material name	:	A00211LP MST TRAD LEMON PL MTRD 12NET7
Material number	:	0000000001001744
Manufacturer or supplier's	deta	ails
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Air Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	characteristic

GHS Classification

Flammable aerosols	:	Category 1
Gases under pressure	:	Liquefied gas
Eye irritation	:	Category 2A
Skin sensitisation	:	Category 1
Specific target organ toxicity -	:	Category 3 (Central nervous system)
single exposure		

GHS label elements

Hazard pictograms

Signal word





Version 2.0	Revision Date 04/23/2018	Print Date 07/23/2018
Hazard statements	 H222 Extremely flammable aero H280 Contains gas under presso H317 May cause an allergic skin H319 Causes serious eye irritatio H336 May cause drowsiness or 	ure; may explode if heated. reaction. on.
Precautionary statements	 Prevention: P210 Keep away from heat, hot and other ignition sources. No sr P211 Do not spray on an open fl P251 Pressurized container: Do use. P261 Avoid breathing dust/ fume P264 Wash skin thoroughly after P271 Use only outdoors or in a v P272 Contaminated work clothin the workplace. P280 Wear protective gloves/ ey Response: P302 + P352 IF ON SKIN: Wash P304 + P340 + P312 IF INHALE and keep comfortable for breathin CENTER/doctor if you feel unwe P305 + P351 + P338 IF IN EYES for several minutes. Remove cor easy to do. Continue rinsing. P333 + P313 If skin irritation or r advice/ attention. P337 + P313 If eye irritation pers attention. P363 Wash contaminated clothin Storage: P403 + P233 Store in a well-ven tightly closed. P410 + P412 Protect from sunlig temperatures exceeding 50 °C/ * Disposal: P501 Dispose of contents/contail regulation. 	moking. lame or other ignition source. not pierce or burn, even after e/ gas/ mist/ vapours/ spray. r handling. well-ventilated area. ng should not be allowed out of re protection/ face protection. n with plenty of soap and water. D: Remove person to fresh air ing. Call a POISON ell. S: Rinse cautiously with water ntact lenses, if present and rash occurs: Get medical sists: Get medical advice/ ng before reuse. tilated place. Keep container pht. Do not expose to 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
citral	5392-40-5	>= 0.1 - < 1
Oils, sweet orange (terpenes and terpenoids)	68647-72-3	>= 0.1 - < 1



Version 2.0

Revision Date 04/23/2018

Print Date 07/23/2018

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASUR	RES
General advice	: Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Move out of dangerous area.
If inhaled	: Remove to fresh air. Call a physician or poison control centre immediately.
In case of skin contact	 Wash off with warm water and soap. If on clothes, remove clothes. If symptoms persist, call a physician. Wash off immediately with plenty of water for at least 15 minutes. Wash contaminated clothing before re-use.
In case of eye contact	 Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water for at least 15 minutes.
If swallowed	 DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital. Never give anything by mouth to an unconscious person. Keep respiratory tract clear.
Most important symptoms and effects, both acute and delayed	 Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Effects are dependent on exposure (dose, concentration, contact time). May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO2) Dry chemical Water
Unsuitable extinguishing media	: High volume water jet
Specific hazards during	: Do not allow run-off from fire fighting to enter drains or water



Version 2.0	Revision Date 04/23/2018	Print Date 07/23/2018
firefighting	courses.	
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	: Use extinguishing measures that a circumstances and the surroundin	
Further information	: For safety reasons in case of fire, separately in closed containments Use a water spray to cool fully clo	S.
Special protective equipment for firefighters	: Wear self-contained breathing app necessary.	paratus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Take precautionary measures against static discharges. Always replace cap after use. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions.



Version 2.0	Revision Date 04/23/2018	Print Date 07/23/2018
	Electrical installations / working m the technological safety standards Keep in a dry, cool and well-ventil	i.
Materials to avoid	: Store and keep away from bases	and alkalies.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
citral	5392-40-5	TWA (Inhalable fraction and vapor)	5 ppm	ACGIH

Components with workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As	-	



		Print Date 07/23/2018
	po a exp	on as ssible after posure ases)
Engineering measures	: effective ventilation in all processi	ng areas
Personal protective equip	oment	
Respiratory protection	: Use respiratory protection unless ventilation is provided or exposure that exposures are within recomm	assessment demonstrates
Hand protection Material Remarks	Protective glovesThe suitability for a specific workp with the producers of the protectiv	
Eye protection	: Safety glasses Ensure that eyewash stations and the workstation location.	safety showers are close to
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous su	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: colourless
Odour	: characteristic
Odour Threshold	: No data available
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: Not applicable
Flash point	: Not applicable
Evaporation rate	: not determined
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available



Version 2.0	Revision Date 04/23/2018	Print Date 07/23/2018
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: <1 g/cm3	
Solubility(ies)		
Water solubility	: soluble	
Solubility in other solvents	: not determined	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents Bases Amines
Hazardous decomposition products	: Carbon dioxide (CO2) Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Effects are dependent on exposure (dose, concentration, contact time).



Version 2.0	Revision Date 04/23/2018	Print Date 07/23/2018
Carcinogenicity:		
IARC	No component of this product present equal to 0.1% is identified as probable	
ACGIH	human carcinogen by IARC. No component of this product present equal to 0.1% is identified as a carcin carcinogen by ACGIH.	t at levels greater than or
OSHA	No component of this product present equal to 0.1% is on OSHA's list of reg	
NTP	No component of this product present equal to 0.1% is identified as a known by NTP.	t at levels greater than or
Acute toxicity		
Components:		
acetone:		
Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h	
	Exposure time. 5 h	
	LC50 Rat: 50.1 mg/l	
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg	
	LD50 Rabbit: > 7,426 mg/kg	
Skin corrosion/irritation		
Product:		
Remarks: slight irritation		
Serious eye damage/eye irritati	on	
Product:		
Remarks: Irritating to eyes.		
Respiratory or skin sensitisatio	n	
Product:		
Remarks: Causes sensitisation	on.	
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		



Version 2.0

Revision Date 04/23/2018

Print Date 07/23/2018

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:	
Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available
Partition coefficient: n- octanol/water citral :	: Pow: 2.89
Partition coefficient: n- octanol/water	: Pow: 2.76
Mobility in soil	
No data available	
Other adverse effects	
No data available <u>Product:</u>	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S.



Version 2.0	Revision Date 04/23/2018	Print Date 07/23/2018
	Clean Air Act Section 602 (40 CF + B).	R 82, Subpt. A, App.A
Additional ecological information	: No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Dispose of in accordance with local regulations. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.



Version	20
VEISION	2.0

Revision Date 04/23/2018

Print Date 07/23/2018

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	 Flammable (gases, aerosols, liquids, or solids) Gases under pressure Serious eye damage or eye irritation Respiratory or skin sensitisation Specific target organ toxicity (single or repeated exposure)
SARA 302	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	 This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	
	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION




Version 2.0

Revision Date 04/23/2018

Print Date 07/23/2018

Further information



HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

- 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	 Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	:
	 Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ eye protection/ face protection. Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	04/23/2018
Print Date:	07/23/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

SAFETY DATA SHEET



A00211LP MST TRAD LEMON PL MTRD 12NET7

Version 2.0

Revision Date 04/23/2018

Print Date 07/23/2018

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical[™], Selig[™], Misty®, Next Dimension[™], Petro®, i-Chem®, TimeMist®, TimeWick[™], MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®,Rexodan®, Mykal[™], and a number of private labeled brands.