

SAFETY DATA SHEET

Date Prepared : 05/13/2015

SDS No : Triple S_Enforcer

SSS Enforcer Heavy Duty No Rinse Stripper

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SSS Enforcer Heavy Duty No Rinse Stripper
GENERAL USE: Floor finish remover
PRODUCT DESCRIPTION: Heavy Duty Speed Stripper
PRODUCT CODE: 48109, 48168
CHEMICAL FAMILY: Solvent/Alkali Blend

MANUFACTURED FOR

Triple S
2 Executive Park Drive
Billerica, MA 01862
<http://www.triple-s.com>
Customer Service: 978-667-7900

24 HR. EMERGENCY TELEPHONE NUMBERS

888-779-1339

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion, Category 1
Eye Corrosion, Category 1
Acute Toxicity (Oral), Category 4

Physical:

Combustible Liquid, Category 4

GHS LABEL



Corrosion



Exclamation
mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

Causes severe skin burns and eye damage.
Harmful if swallowed.
May be harmful if inhaled.
May cause drowsiness or dizziness.
Combustible liquid.

PRECAUTIONARY STATEMENT(S)

Prevention:

Wear protective gloves/protective clothing/eye protection/face protection.
Avoid release to the environment.
Wash hands thoroughly after handling.
Keep only in original packaging.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing fume, gas, mist, vapors, or spray.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Rinse mouth.

Do NOT induce vomiting.

Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Disposal:

Dispose of contents/container according to all local, state and Federal regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear Liquid

IMMEDIATE CONCERNS: Causes irreversible eye damage and skin burns.

POTENTIAL HEALTH EFFECTS

EYES: Corrosive, contact causes severe eye burns.

SKIN: Contact causes severe skin irritation and possible burns.

SKIN ABSORPTION: Harmful if absorbed through skin.

INGESTION: Harmful if swallowed.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches)

REPRODUCTIVE TOXICITY

TERATOGENIC EFFECTS: No listed substance

CARCINOGENICITY: Not Established

MUTAGENICITY: No listed substance

ROUTES OF ENTRY: Eye, skin, ingestion, Inhalation.

TARGET ORGAN STATEMENT: Blood, kidney, liver, Central nervous system

CANCER STATEMENT: None

WARNING CAUTION LABELS: Corrosive

PHYSICAL HAZARDS: Combustible material.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Ethylene glycol butyl ether	20 - 30	111-76-2
Monoethanolamine	0 - 5	141-43-5
Potassium Hydroxide	0 - 5	1310-58-3
Fragrance	< 1	N/A
Water	50 - 60	7732-18-5

4. FIRST AID MEASURES

EYES: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Seek medical attention immediately.

SKIN: Remove contaminated clothing. Immediately flush with water followed by washing with mild soap. Seek medical attention.

INGESTION: Get immediate medical attention. Do not induce vomiting unless instructed to do so by poison center or physician.

INHALATION: Remove victim to fresh air and monitor. Seek medical advise if irritation persists.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Severe burning sensation, damage marked by burns.

SKIN: Burning sensation, redness.

INGESTION: Irritation of mouth, throat, along with stomach upset, vomiting.

INHALATION: Irritation of nose, throat and lungs with coughing, sneezing, possible difficulty breathing.

ACUTE TOXICITY: Corrosive to eyes. Causes moderate to severe skin irritation. Harmful if swallowed.

CHRONIC EFFECTS: Not Established

NOTES TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: IIIA (140-200F)

GENERAL HAZARD: Combustible Liquid

EXTINGUISHING MEDIA: Use Dry chemical, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Alkaline vapors.

EXPLOSION HAZARDS: Fire exposed containers may burst due to increased pressure from heat.

FIRE FIGHTING PROCEDURES: Use an extinguishing agent suitable for surrounding fire.

FIRE FIGHTING EQUIPMENT: No special requirements.

HAZARDOUS DECOMPOSITION PRODUCTS: Not Established

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LARGE SPILL: Avoid walking in material. Prevent product from entering into stream, soil, storm sewer or other bodies of water.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid discharges into open waterways.

LAND SPILL: Avoid discharge to soil.

AIR SPILL: NA = Not Applicable

GENERAL PROCEDURES: Isolate spill or leak area immediately. Keep unauthorized personnel away. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, or confined areas. Absorb with dry earth, sand or other non-combustible material and transfer to containers.

RELEASE NOTES: Eliminate all ignition sources. Ventilate area well.

SPECIAL PROTECTIVE EQUIPMENT: Eye protection, rubber gloves, rubber boots to protect feet.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Close container after use.

HANDLING: Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

STORAGE: Store in closed container away from heat, spark or open flame.

STORAGE TEMPERATURE: (40°F) Minimum to (110°F) Maximum

STORAGE PRESSURE: Store at ambient atmospheric pressure.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Ethylene glycol butyl ether	TWA	50	240	20	97	NL	NL
	STEL					NL	NL
Monoethanolamine	TWA	3	6	3	7.5	NL	NL
	STEL			6	15	NL	NL
Potassium Hydroxide	TWA		2 mg/m3				
	STEL				2 mg/m3		

ENGINEERING CONTROLS: Provide mechanical ventilation when used in confined areas, or areas with poor ventilation.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical splash goggles and full face-shield.

SKIN: Rubber or other chemical resistant gloves.

RESPIRATORY: A respirator is not needed under normal and intended conditions of product use.

WORK HYGIENIC PRACTICES: Wash with soap and water after handling. Do not eat, drink or smoke while using product.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Solvent, characteristic

ODOR THRESHOLD: Not Established

COLOR: Water Clear

pH: 13.0 to 14.0

PERCENT VOLATILE: >90

FLASH POINT AND METHOD: 67°C (153°F) Tag Closed Cup (TCC)

FLAMMABLE LIMITS: 1.3 to 10.6

AUTOIGNITION TEMPERATURE: NA = Not Applicable

VAPOR PRESSURE: ~ 0.9 mm Hg at 20°C (68°F)

VAPOR DENSITY: > 1 Air = 1

BOILING POINT: 212° F; 100° C

FREEZING POINT: 32° F; 0° C

MELTING POINT: Not Available

THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: Complete

EVAPORATION RATE: (Water =1) 1.0

DENSITY: 8.43 at 20°C (68°F)

SPECIFIC GRAVITY: ~ 1.01 grams/ml.

VISCOSITY: Water thin.

(VOC): 31.600 % by weight

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable under normal storage and use conditions.

CONDITIONS TO AVOID: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

INCOMPATIBLE MATERIALS: Strong acids, oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Ethylene glycol butyl ether	1300 mg/kg (rat)	> 2000 mg/kg (rabbit)	> 3.1 mg/l
Monoethanolamine	1089 mg/kg (rat)	2504 mg/kg (rabbit)	~ 1.48 mg/l
Potassium Hydroxide	273 mg/kg (rat)	N/A	

EYES: Corrosive

DERMAL LD₅₀: > 2000 mg/kg guinea pig

SKIN ABSORPTION: Not Established

ORAL LD₅₀: ~ 1300 mg/kg Male and Female rats.

INHALATION LC₅₀: > 3.1 mg/L (vapor) Guinea pig

EYE EFFECTS: Corrosive to eyes. Permanent damage may occur.

SKIN EFFECTS: Corrosive to skin.

CARCINOGENICITY

Chemical Name	NTP Status	IARC Status	OSHA Status
Ethylene glycol butyl ether	No listed substance	Group 3 - Not classifiable as to its carcinogenicity to Humans	No listed substance

IARC: 3-Group 3: Not classifiable as to its carcinogenicity to humans.

IRRITATION: Irritant

CORROSIVITY: Corrosive

SENSITIZATION: No products were found.

NEUROTOXICITY: Central nervous system effects marked by dizziness, headache, nausea, unconsciousness.

GENETIC EFFECTS: No known significant effects or critical hazards.

REPRODUCTIVE EFFECTS: No known significant effects or critical hazards.

TARGET ORGANS: May cause damage to blood, Kidney, liver with prolonged or repeated exposure to high concentrations of vapors.

MUTAGENICITY: No known significant effects or critical hazards.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Not Established

ECOTOXICOLOGICAL INFORMATION: No known significant effects or critical hazards noted.

AQUATIC TOXICITY (ACUTE): No known significant effects or critical hazards.

96-HOUR LC₅₀: Not Established

96-HOUR EC₅₀: Not Established

Notes: Practically nontoxic

CHEMICAL FATE INFORMATION: This product is biodegradable.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. If discarded, this material and its containers should be treated as hazardous waste based on the characteristics of ignitability and corrosivity as defined under federal RCRA regulations (40 CFR 261). Consult local authorities for disposal into public sewer.

FOR LARGE SPILLS: Consult with local and state authorities for large volume disposal.

PRODUCT DISPOSAL: Small quantities (less than 1 gallon) of used material may be flushed to sanitary sewer with copious amounts of water. Larger quantities must be disposed of by a licensed disposal company.

EMPTY CONTAINER: Rinse container with clear water. Offer container for recycling, or dispose of in trash.

RCRA/EPA WASTE INFORMATION: Ignitability, corrosive

RCRA HAZARD CLASS: Not yet Determined

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Compound, Cleaning Liquid

TECHNICAL NAME: Potassium Hydroxide Solution

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: 1760

PACKING GROUP: III

PLACARDS: Corrosive

LABEL: Certain package sizes determine the proper labeling of containers. Consult manufacturer for specific information regarding proper labeling.

OTHER SHIPPING INFORMATION: Certain shipping modes and packaging sizes may have exceptions from the transport regulations. The classifications/information provided above may not reflect applicable exceptions. Contact the manufacturer for more specific information on the proper shipping of this material.

SPECIAL SHIPPING NOTES: Quantities less than or equal to one (1) gallon = Limited Quantity not regulated.

AIR (ICAO/IATA)

SHIPPING NAME: Not Established

VESSEL (IMO/IMDG)

SHIPPING NAME: Corrosive liquid, basic, inorganic, n.o.s.

TECHNICAL NAME: Potassium Hydroxide Solution

UN/NA NUMBER: 3264

PRIMARY HAZARD CLASS/DIVISION: 8

PACKING GROUP: III

PLACARDS: Corrosive

LABEL: Corrosive

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Corrosive

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Health - Acute

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: 2-butoxyethanol 111-76-2 (Category: N230 Certain Glycol Ethers)

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Ethylene glycol butyl ether	20 - 30	111-76-2

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: No listed substance

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Potassium Hydroxide	0 - 5	1,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All ingredients are listed on the TSCA Chemical Inventory.

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Ethylene glycol butyl ether	Massachusetts Right to Know Substance Pennsylvania Right to Know Substance New Jersey Right To Know Substance
Monoethanolamine	Massachusetts Right to Know Substance New Jersey Right To Know Substance New York Right to Know Substance Pennsylvania Right to Know Substance
Potassium Hydroxide	Massachusetts Right to Know Substance Pennsylvania Right to Know Substance New Jersey Right To Know Substance Rhode Island Right to Know Substance

CALIFORNIA PROPOSITION 65: No listed substance

CARCINOGEN: Contains an ingredient listed under IARC Group 3.

16. OTHER INFORMATION


PREPARED BY: Regulatory Affairs Department

Date Prepared: 05/13/2015

HMIS RATING

HEALTH		3
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		D

NFPA CODES



MANUFACTURER DISCLAIMER: This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of the product either alone or in combination with other products. It is the responsibility of the employer and/or user to provide a safe workplace, using health and safety information contained herein as a guide. This company will accept no liability for damages or losses incurred from the improper handling and use of this product.