

Material Safety Data Sheet OSHA's Hazard Communication Standard U.S. Department of Labor

29 CFR 1910.1200 OMB No. 1218-0072

Identity # 210170 Names SOLID COVER FLOOR FINISH

Section 1

Manufactureed for - GORM, Inc.

Address - 1501 S. Hudson Ave. Emergency Phone (Chemtrec) 1-(800)-255-3924 City - Ontario State - CA Phone - (909) 292-1400 Contact Person - Morten Riegg

Date Prepared- 12/19/2006

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components CAS# OSHA PEL ACGIH TLV Weight% (Optional)

2(Butoxyethoxy) Ethanol 111-76-2 NONE NONE

Note:

VOC Content- 56.7 g/L

Section 3 - Physical/Chemical Characteristics

Boiling Point- >212 F" Specific Gravity- 1.030

Vapor Pressure - Not Tested Welting Point - Not Tested Evaporation Rate - Not Tested

Solubility In Water- 100%

Appearance and Odor- OPAQUE WHITE COLOR LIQUID WITH BLAND ODOR.

Section 4 - Fire and Explosion Hazard Data

Flash Point- None Flammable Limits - Not Tested

LEL- Not Tested UEL- Not Tested

pH- 7.5 - 9.0 DOT# NONE

NFPA Hazard Rating - H F R S HMIS Hazard Rating - H F R (0- Least, 4- Extreme) 1 0 0 0 1 0 0

Extinguishing Media- CO2, DRY FOAM
Special Fire Fighting Procedures NONE

Unusual Fire and Explosion Hazards- NONE

Section 5 - Reactivity Data

Stability - Stable

Conditions to Avoid - None

Incompatible Materials to Avoid- Cationic Materials, Strong Oxidizers, Strong Acids

Hazardous Decomposition or Byproducts- CO, CO2

Hazardous Polymerization- NONE

Conditions to Avoid- None

Section 6 - Health Hazard Data

Routes of Entry
Inhalation? - Possible
Skin? - Possible
Ingestion? - Possible
Health Hazards - Same as Signs and Symptoms of Exposures
Note - All Chemicals in this Product are Found on the TSCA Inventory List.
OSHA Carcinogenicity? - None: NTP? - None: IARC Monographs? - None.

09100

Signs and symptons of over exposure:

Eyes - Burning Sensation

Skin- Slight irritation

Ingestion-Nausea

Inhalation- Not Expected to be a Problem

Medical Conditions Generally Aggravated by Exposure - Same as Signs and Symptoms of Over Exposure

Emergency and First Aid Procedures

Eyes - Flush With Water For 15 Minutes. If Irritation Persists, Call Physician.

Skin- Wash Off With Soap & Water, If Irritation Persists, Call Physician

Ingestion- Drink Large Amounts of Water, Call Physician

Inhalation- Not Expected to be a Problem

Section 7 - Precautions For Safe Handling and Use.

Steps to be taken in case material is released or spilled - Soak up with inert, absorbent material. Scoop up and place in a proper waste disposal container.

Waste Disposal Method - Dispose of in accordance with state and local regulations.

Precautions To Be Taken In Handling and Storing - Store in a cool, dry place, out of direct sunlight. Do not freeze, less than or equal to 32 F, or heat above 110 F.

Other Precautions - Keep out of reach of children. Follow directions on the container for proper use of this product.

Section 8 - Control Measures

Respiratory Protection - Open all doors and windows. "If" there is an exposure, and it is above the TLV or PEL, a NIOSH approved respirator equipped for the exposure or suitable respiratory protection per 29 CRF 1910.134, is required.

Ventilation Local Exhaust - If Available Special - None Mechanical - If Available Other - None

Protective Gloves- Plastic or Rubber, Chemical Resistant

Eye Protection- Glasses, Goggles

Other Protective Clothing or Equipment- None

Work Hygenic Practices - Use common sense and care around chemicals. Never mix chemicals. Consult your supervisor for other practices. All practices depend on your specific business. Directions for use are normally found on label which will dictate engineering and control measures.

Other Special Requirements None

Note: GORM believes the data set forth are accurate, GORM makes no warranty with respects thereto and disclaims all liability for reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion