## **MATERIAL SAFETY DATA SHEET**

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION								
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection							rsonal Protection-B	
Manufactured For: Triple S			DOT Hazard Classification: ORM-D					
Address: 2 Executive Park Dr.			Identity (trade name as used on label):					
Address: Billerica, MA 01862			SSS Contact & Circuit Board Cleaner III #05236					
·			MSDS Number: A00368 Revision- 6					
			Date Prepared: 12/07/06 Prepared By: CH/TR/IB					
			Information Calls: (770)422-2071					
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION								
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES			CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **		
HEPTANE		142-82-5	No	500	400	d		
2-METHYLPENTANE		107-83-5	No	500	500	d		
ISOPROPANOL			67-63-0	No	400	400	d	
3-METHYLPENTANE			96-14-0	No	500	500	d	
2,3 DIMETHYLBUTANE			79-29-8	No	500	500	d	
2,2 DIMETHYLBUTANE			75-83-2	No	500	500	d	
CARBON DIOXIDE			124-38-9	No	5000	5000	d	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS								
Boiling Point: N/A   Specific Gravity (H2O=1): Concentrate Only = 0.70								
			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): N/E			Evaporation Rate ( = 1): N/E					
			Water Reactive: No					
Appearance and Odor: Clear forceful spray with aliphatic solvent odor.								
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA								
				Ignition Temperature Flammability Limits in Air by % in Volume:				
(aerosols) EXTREMELY FLAMMABLE			N/E % LEL: N/E % UEL: N/E					
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.								
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.  Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.								
SECTION 4 - REACTIVITY HAZARD DATA								
STABILITY [X] STABLE [] UNSTABLE   HAZARDOUS POLYMERIZATION [] WILL [X]WILL NOT OCCUR								
1 1			ons to Avoid: Open flame, welding arcs, heat, sparks.					
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.								
SECTION 5 - HEALTH HAZARD DATA								
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS								
ACUTE EFFECTS								
Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible								
unconsciousness or asphyxiation.								
Eye Contact: Slight irritation.  Skin Contact: Slight irritation due to defatting of skin.								
Ingestion: Irritation. Aspiration into lungs can result in chemical pneumonitis and inhalation symptoms.								
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation may result in central nervous								
system effects.								
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.								
EMERGENCY FIRST AID PROCEDURES								
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.								
Skin Contact: Wash with soap and water. If irritated, seek medical attention.								
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.								
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.								
SECTION 6 - CONTROL AND PROTECTIVE MEASURES								
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH approved for organic vapor.								
Protective Gloves: Neoprene Eye Protection: Safety glasses recommended.								
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.								
Other Protective Clothing & Equipment: None								
Hygienic Work Practices: Wash with soap and water before handling food.								
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE								
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.								
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.								
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.								
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination.								