

# Safety Data Sheet

## Quikleen II

### SECTION I - IDENTIFICATION

**PRODUCT NAME:** Quikleen II  
**PRODUCT CODE:** 5120  
**PRODUCT USE:** Solvent cleaner  
**COMPANY NAME:** QuestVapco Corporation  
**COMPANY ADDRESS:** PO Box 624 Brenham, TX 77834  
**COMPANY PHONE:** 1-800-231-0454  
**EMERGENCY PHONE:** 800-255-3924

### SECTION II – HAZARDS IDENTIFICATION

**CLASSIFICATION:** Dissolved Gas  
Skin Irritant: Category 2  
Eye Irritant: Category 2A  
Specific Target Organ Toxicity (Single Exposure): Category 3  
Carcinogenicity: Category 1B  
Germ Cell Mutagenicity: Category 2

**HAZARD STATEMENT(S): DANGER:** Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. May cause drowsiness and dizziness. May cause cancer. Suspected of causing genetic defects.

This product contains the following percentage of chemicals of unknown toxicity: 0%

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/120F. Store in a well-ventilated place. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, eye protection, and protective clothing. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.



**SYMBOL:**

**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

### SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENT | CAS NUMBER | PERCENT |
|----------------------|------------|---------|
| Carbon Dioxide       | 124-38-9   | 3-7%    |
| Trichloroethylene    | 79-01-6    | 30-60%  |
| Tetrachloroethylene  | 127-18-4   | 30-60%  |

### SECTION IV - FIRST AID MEASURES

**EYES:** Remove contact lenses. Flush with water for at least 15 minutes. See a physician if irritation persists.

**INGESTION:** Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention.

**INHALATION:** If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

**SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation persists.

**ACUTE HEALTH HAZARDS:** Inhalation: dizziness, drowsiness, weakness, and fatigue

Eye: stinging, tearing, redness

Oral: Vomiting, nausea, irritation

Skin: Prolonged or repeated contact may dry skin

## Safety Data Sheet

### Quikleen II

**CHRONIC HEALTH HAZARDS:** Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

**NOTE TO PHYSICIAN:** Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

#### SECTION V – FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Use appropriate media for surrounding fire.

**UNSUITABLE EXTINGUISHING MEDIA:** N/A

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Contents under pressure. Exposure to temperatures above 120°F may cause bursting.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon, chlorine, hydrogen chloride and phosgene.

#### SECTION VI – ACCIDENTAL RELEASE MEASURES

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Use absorbent on spill, sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

#### SECTION VII – HANDLING AND STORAGE

**HANDLING AND STORAGE:** Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

**OTHER PRECAUTIONS:** Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warning and precautions listed for the product. Keep out of the reach of children

**INCOMPATIBILITY:** Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

#### SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

| HAZARDOUS INGREDIENT | OSHA PEL | ACGIH TLV |
|----------------------|----------|-----------|
| Carbon Dioxide       | 5000 ppm | 5000 ppm  |
| Trichloroethylene    | 10 ppm   | 25 ppm    |
| Tetrachloroethylene  | 25 ppm   | 100 ppm   |

**ENGINEERING CONTROLS / VENTILATION:** Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

**RESPIRATORY PROTECTION:** Wear NIOSH/MSHA approved organic vapor respiratory protection if used in confined, poorly ventilated areas.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses, Gloves, and Synthetic apron.

**ADDITIONAL MEASURES:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

#### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Clear, Colorless Spray

**ODOR:** Chlorinated solvent odor

**ODOR THRESHOLD:** N/D

## Safety Data Sheet

### Quikleen II

**BOILING POINT:** >188°F (87°C)  
**FREEZING POINT:** N/D  
**FLAMMABILITY:** Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200)  
**FLASH POINT:** N/D  
**AUTOIGNITION TEMPERATURE:** N/D  
**LOWER FLAMMABILITY LIMIT:** N/D  
**UPPER FLAMMABILITY LIMIT:** N/D  
**VAPOR PRESSURE (mm Hg):** 59  
**VAPOR DENSITY (AIR=1):** > 2  
**EVAPORATION RATE:** > 3 (Fast)  
**SPECIFIC GRAVITY (H2O=1):** 1.52  
**pH:** N/A  
**SOLIDS (%):** 0%  
**SOLUBILITY IN WATER:** 0%  
**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D  
**VOLATILITY INCLUDING WATER (%):** 100%  
**VOLATILE ORGANIC COMPOUNDS (VOC):** 50%  
**DIELECTRIC STRENGTH (Volts):** 29,000  
**DECOMPOSITION TEMPERATURE:** >400°C  
**VISCOSITY:** N/D

#### SECTION X – STABILITY AND REACTIVITY DATA

**REACTIVITY:** Chemically active metals and acids  
**CHEMICAL STABILITY:** Stable  
**CONDITIONS TO AVOID:** Temperatures greater than 122°F may cause bursting.

**INCOMPATIBILITY:** Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCT:** Oxides of carbon, chlorine, hydrogen chloride and phosgene.

**POSSIBLE HAZARDOUS REACTIONS:** None Known

#### SECTION XI – TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** **Trichloroethylene** (79-01-6) LD<sub>50</sub> (Oral, Rat) 5,650 mg/kg; Tumorigen, mutagenic reproductive effects in humans. **Tetrachloroethylene** (127-18-4) LD<sub>50</sub> (Oral, Rat) 2629 mg/kg; LD<sub>50</sub> (Dermal, Rabbit) > 3228 mg/kg; LD<sub>50</sub> (IPR, Mouse) 4700 mg/kg; LC<sub>50</sub> (Inhalation, Mouse, 4hr) 5200 ppm; LC<sub>50</sub> (Inhalation, Rat, 8hr) 34200 mg/m<sup>3</sup>

**ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin

**EYES:** Causes irritation, burning, redness, tearing.

**INGESTION:** Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, abdominal cramps.

**INHALATION:** Irritation to respiratory tract, dizziness, headache, nausea, depression of central nervous system, prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects, and death.

**SKIN:** Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

**MEDICAL CONDITION AGGRAVATED:** Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.

**ACUTE HEALTH HAZARDS:** Inhalation: dizziness, drowsiness, weakness, and fatigue

Eye: stinging, tearing, redness

Oral: Vomiting, nausea, irritation

Skin: Prolonged or repeated contact may dry skin

**CHRONIC HEALTH HAZARDS:** Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

**CARCINOGENICITY:** OSHA: Yes ACGIH: A2 - Suspected NTP: 2 - Anticipated

IARC: 2A - Probable OTHER: CA Prop 65

#### SECTION XII – ECOLOGICAL INFORMATION

**ECOLOGICAL INFORMATION:** **Trichloroethylene** (79-01-6) LC<sub>50</sub> (96hr) Fish: 10 and 100 mg/L. Slightly toxic to aquatic life.

**BIODEGRADABILITY:** Component or components of this product are not biodegradable.

**Safety Data Sheet**  
**Quikleen II**

**BIOACCUMULATION:** This product is not expected to bioaccumulate.

**SOIL MOBILITY:** This product is mobile in soil.

**OTHER ECOLOGICAL HAZARDS:** None Known

**SECTION XIII – DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

**SECTION XIV - TRANSPORTATION INFORMATION**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.2 (6.1)

**UN/NA NUMBER:** UN 1950

**PACKAGING GROUP:** N/A

**AIR SHIPMENT**

**PROPER SHIPPING NAME:** Forbidden by USDOT Regulations

**HAZARD CLASS/DIVISION:** 2.2 (6.1)

**UN/NA NUMBER:** UN 1950

**SHIPPING BY WATER:**

**VESSEL (IMO/IMDG)**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.2 (6.1)

**UN/NA NUMBER:** UN 1950

**ENVIRONMENTAL HAZARDS WATER:** N/A

**SECTION XV - REGULATORY INFORMATION**

**TSCA STATUS:** All Chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** **Trichloroethylene** (79-01-6)

Reportable Quantity = 100 lbs **Tetrachloroethylene** (127-18-4) Reportable Quantity = 100 lbs

**SARA 311/312 HAZARD CATEGORIES:** Acute Health, Chronic Health.

**SARA 313 REPORTABLE INGREDIENTS:** **Trichloroethylene** (79-01-6) **Tetrachloroethylene** (127-18-4)

**STATE REGULATIONS:** **Trichloroethylene** (79-01-6) is known to the state of California to cause cancer.

**Trichloroethylene** (79-01-6) Right-to-Know acts for New York, Rhode Island, Pennsylvania, Florida, Minnesota, Massachusetts, Michigan, New Jersey, Tennessee; Spill Reporting for Massachusetts, New Jersey, Louisiana; Connecticut hazardous material survey; Illinois toxic substances disclosure to employee act

**INTERNATIONAL REGULATIONS:** **Trichloroethylene**, CAS 79-01-6, - EC - yes, Japan – yes, Australia – yes, Korea – yes, Canada DSL – yes, Canada NDSL –no, Philipenes – yes. **Tetrachloroethylene** (127-18-4) WHMIS (Canada) Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class D-2A: Material causing other toxic effects (VERY TOXIC).

**NFPA HEALTH:** 2

**NFPA FLAMMABILITY:** 1

**NFPA REACTIVITY:** 0

**NFPA OTHER:** None

**HMIS HEALTH:** 2

**HMIS FLAMMABILITY:** 1

**HMIS REACTIVITY:** 0

**HMIS PROTECTION:** C

**SECTION XVI - ADDITIONAL INFORMATION**

**PREPARATION BY:** Jonathon Jarvis

**DATE PREPARED:** 12/13/2013

**REVISION DATE:** 11/13/2014

N/A = Not Applicable; N/D = Not Determined

## Safety Data Sheet

### Quikleen II

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.