



Wood Care: Polyurethane 350 Finish

HMIS		NFPA	Personal protective equipment
Health	2	2	None / Aucune / Ninguno
Flammability	2	0	
Physical Hazard / Instability	0	0	

Version Number: 2

Preparation date: 2015-03-26

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Wood Care: Polyurethane 350 Finish

MSDS #: MS0300284

Product Code: 5142180

Recommended use:

- Industrial/Institutional
- Floor care

Manufacturer, importer, supplier:

US Headquarters
Diversey, Inc.
8310 16th St.
Sturtevant, Wisconsin 53177-1964
Phone: 1-888-352-2249
MSDS Internet Address: www.diversey.com

Canadian Headquarters
Diversey, Inc. - Canada
3755 Laird Road
Mississauga, Ontario L5L 0B3
Phone: 1-800-668-3131

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION. CAUSES EYE AND SKIN IRRITATION. COMBUSTIBLE LIQUID AND VAPOR.

Principal routes of exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Eye contact: Moderately irritating to the eyes.

Skin contact: Moderately irritating to the skin.

Inhalation: None known.

Ingestion: May cause irritation to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS #	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Mineral spirits	8052-41-3	30 - 40%	5000	3000 mg/kg	Not available
Linseed oil	8001-26-1	5 - 10%	15000	Not available	Not available
Trimethyl benzene	25551-13-7	1 - 5%	8970	Not available	Not available
1,3,5-trimethylbenzene	108-67-8	0.1 - 1.5%	5000	Not available	≈24 g/m ³ (4 h)

4. FIRST AID MEASURES

Eye contact: Flush immediately with plenty of water. If irritation persists, get medical attention.

Skin contact: Flush immediately with plenty of water. If irritation persists, get medical attention.

Inhalation: No specific first aid measures are required.

Ingestion: If swallowed, give a cupful of water or milk.

Aggravated Medical Conditions: Persons with pre-existing skin disorders may be more susceptible to irritating effects.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use dry chemical, CO₂, water spray or "alcohol" foam.
Extinguishing media which must not be used for safety reasons: No information available.
Specific hazards: Keep product and empty container away from heat and sources of ignition.
Unusual hazards: None known.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment. Remove all sources of ignition. Ventilate the area.
Environmental precautions and clean-up methods: Keep out of water supplies and sewers. Prevent product from entering drains. Soak up with oil absorbent material. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. COMBUSTIBLE LIQUID AND VAPOR. Keep away from open flames, hot surfaces and sources of ignition. Use only in well-ventilated areas. **HANDLING OF WASTE MATERIALS:** Used finish materials (e.g. clean-up rags, steel wool, tacking towels) and sanding dust can spontaneously ignite if improperly discarded. Do not store waste finish materials or sanding dust in a pile or discard into the regular trash. Instead, immediately place all waste materials into a water-filled metal container and discard according to local, state and federal regulations. **FOR COMMERCIAL AND INDUSTRIAL USE ONLY.**

Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. **KEEP OUT OF REACH OF CHILDREN.**

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:
No special ventilation requirements General room ventilation is adequate

Personal Protective Equipment

Eye protection: No special requirements under normal use conditions.
Hand protection: No special requirements under normal use conditions
Skin and body protection: No special requirements under normal use conditions.
Respiratory protection: No special requirements under normal use conditions.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Ingredient(s)	CAS #	ACGIH	OSHA	Mexico
Mineral spirits	8052-41-3	100 ppm (TWA)	500 ppm (TWA) 2900 mg/m ³ (TWA)	200 ppm (STEL) 1050 mg/m ³ (STEL) 100 ppm (TWA) 523 mg/m ³ (TWA)
Trimethyl benzene	25551-13-7	25 ppm (TWA)		35 ppm (STEL) 170 mg/m ³ (STEL) 25 ppm (TWA) 125 mg/m ³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Appearance: Liquid
Specific gravity: 0.91
Vapor density: No information available
Boiling point/range: Not determined
Decomposition temperature: Not determined
Solubility: Insoluble
Solubility in other solvents: No information available
Partition coefficient (n-octanol/water): No information available
Elemental Phosphorus: 0 % by wt.
pH: Not applicable
Explosion limits: - upper: Not determined - lower: Not determined

Bulk density: No information available
Evaporation Rate: No information available
Color: Milky, Amber
Odor: Solvent
Melting point/range: Not determined
Autoignition temperature: No information available
Density: 7.59 lbs/gal 0.91 Kg/L
Flash point: 110 °F 43.3 °C
Viscosity: 320 S.U.S.
VOC: 350 g/L (40 CFR §59.400)
Dilution pH: No information available.

10. STABILITY AND REACTIVITY

Stability: The product is stable
Polymerization: Hazardous polymerization does not occur.
Hazardous decomposition products: None reasonably foreseeable.
Materials to avoid: Strong oxidising agents. Do not mix with any other product or chemical.
Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Oral LD50 estimated to be greater than 5000 mg/kg; Dermal LD50 estimated to be > 2000 mg/kg
Component Information: See Section 3.
Chronic toxicity: None known
Specific effects
Carcinogenic effects: • None known
Mutagenic effects: None known
Reproductive toxicity: None known
Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:
 Dispose of brushes and rags used for processing of the product as hazardous waste.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Proper shipping descriptions can vary by pack size. Please refer to the Diversey HazMat Library, **only available through Internet Explorer**, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Polyurethane resin	TS*	-	-	-	-
Mineral spirits	8052-41-3	X	X	X	-
Linseed oil	8001-26-1	-	-	X	-
Trimethyl benzene	25551-13-7	X	X	X	-
Driers	TS*	-	-	-	-
1,3,5-trimethylbenzene	108-67-8	X	X	-	-

CERCLA/ SARA

SARA 311/312 Hazard Categories

Immediate: X
Delayed: -
Fire: X
Reactivity: -
Sudden Release of Pressure: -

Canadian Regulations

WHMIS hazard class: B3 Combustible liquid, D2B Toxic materials.

Wood Care: Polyurethane 350 Finish



Ingredient(s)	CAS #	NPRI
Mineral spirits	8052-41-3	X
Trimethyl benzene	25551-13-7	X
1,3,5-trimethylbenzene	108-67-8	X

16. OTHER INFORMATION

Reason for revision: Not applicable
Prepared by: NAPRAC

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.