



Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	09-2779-8	Version Number:	20.02
Issue Date:	02/25/15	Supersedes Date:	05/07/14

SECTION 1: Identification

1.1. Product identifier

Scotch-Brite™ Quick Clean Griddle Liquid (No. 700 and No. 701)

Product Identification Numbers

ID Number	UPC	ID Number	UPC
70-0070-0037-8	00-48011-29603-1	70-0711-2704-0	00-48011-29603-1
70-0711-2705-7	00-48011-26012-4	70-0715-9365-4	00-48011-28398-7
70-0716-5801-0	00-51125-85780-7	70-0716-5821-8	00-51125-85793-2

1.2. Recommended use and restrictions on use

Recommended use

A powerful griddle cleaning liquid that is safe for use on food contact surfaces. Loosens and lifts carbonized grease and food soil upon contact on a hot griddle for easy removal. No fragrance added

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Commercial Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

2.3. Hazards not otherwise classified

May cause thermal burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
GLYCERIN	56-81-5	40 - 70 Trade Secret *
WATER	7732-18-5	10 - 30 Trade Secret *
POTASSIUM CARBONATE	584-08-7	7 - 13 Trade Secret *
SODIUM CARBONATE	497-19-8	1 - 5 Trade Secret *
TARTRAZINE	1934-21-0	0.05 - 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention. If heated product contacts the skin, immediately flush with large amounts of cool water for at least 15 minutes to minimize potential for thermal burns. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention. If heated product contacts the eye, immediately flush eyes with large amounts of cool water for 15 minutes to minimize potential for thermal burns. After flushing eyes, get immediate medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Acrolein

Hydrocarbons

Condition

During Combustion

During Combustion

Formaldehyde
Carbon monoxide
Carbon dioxide

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No unusual fire or explosion hazards are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin contact with hot material. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Store away from acids. Store away from areas where product may come into contact with food or pharmaceuticals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
GLYCERIN	56-81-5	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene
Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Odor, Color, Grade:	Clear yellow-orange color with a mild odor
Odor threshold	<i>No Data Available</i>
pH	Approximately 12
Boiling Point	Approximately 248 °F
Flash Point	No flash point
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Density	1.3 g/ml [<i>Ref Std: WATER=1</i>]
Specific Gravity	Approximately 1.3 [<i>Ref Std: WATER=1</i>]
Solubility in Water	Complete
Solubility- non-water	<i>No Data Available</i>
Autoignition temperature	698 °F [<i>Details: CONDITIONS: For glycerin only (NFPA, 11th ed.)</i>]
Decomposition temperature	<i>No Data Available</i>
Viscosity	Approximately 200 centipoise
Hazardous Air Pollutants	0
Volatile Organic Compounds	0

Percent volatile	10 - 30 %
VOC Less H2O & Exempt Solvents	0

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong acids

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

Vapors from heated material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
GLYCERIN	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
GLYCERIN	Ingestion	Rat	LD50 > 5,000 mg/kg
POTASSIUM CARBONATE	Dermal	Rabbit	LD50 > 2,000 mg/kg
POTASSIUM CARBONATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.58 mg/l
POTASSIUM CARBONATE	Ingestion	Rat	LD50 1,870 mg/kg
SODIUM CARBONATE	Dermal	Rabbit	LD50 > 2,000 mg/kg
SODIUM CARBONATE	Ingestion	Rat	LD50 2,800 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
GLYCERIN	Rabbit	No significant irritation
POTASSIUM CARBONATE	Rabbit	Minimal irritation
SODIUM CARBONATE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product		No significant irritation
GLYCERIN	Rabbit	No significant irritation
POTASSIUM CARBONATE	Rabbit	Corrosive
SODIUM CARBONATE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
GLYCERIN	Guinea pig	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SODIUM CARBONATE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
GLYCERIN	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
GLYCERIN	Ingestion	Not toxic to female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation

GLYCERIN	Ingestion	Not toxic to male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
GLYCERIN	Ingestion	Not toxic to development	Rat	NOAEL 2,000 mg/kg/day	2 generation
SODIUM CARBONATE	Ingestion	Not toxic to development	Mouse	NOAEL 340 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
POTASSIUM CARBONATE	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
GLYCERIN	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.91 mg/l	14 days
GLYCERIN	Inhalation	heart liver kidney and/or bladder	All data are negative	Rat	NOAEL 3.91 mg/l	14 days
GLYCERIN	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	All data are negative	Rat	NOAEL 10,000 mg/kg/day	2 years
SODIUM CARBONATE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.07 mg/l	3 months

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and

requirements.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

15.4. International Regulations

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None
Acid/Base: Alkaline

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 1 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	09-2779-8	Version Number:	20.02
Issue Date:	02/25/15	Supersedes Date:	05/07/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com