Version 1.0	Revision Date 05/13/2015	Print Date 06/02/2015		
SECTION 1. PRODUCT AND COMPANY IDENTIFICATION				

Material name	:	Hillyard Quick & Clean Extreme Odor Neutralizer Handheld
Material number	:	A00266AM
Manufacturer or supplier's d	eta	ils
Company	:	Hillyard Industries
Address	:	302 North 4 th Street Joseph, MO 64502
Telephone	:	816-233-1321 ext 8285

Emergency telephone numbers			
For SDS Information	:	816-233-1321 ext 8285	
For a Medical Emergency	:		
For a Transportation	:	CHEMTREC 800-424-9300	
Emergency			

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification

Flammable aerosols Gases under pressure Eye irritation Specific target organ toxicity - single exposure	 Category 1 Liquefied gas Category 2A Category 3 (Central nervous system)
GHS Label element	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source.

/ersion 1.0	Revision Date 05/13/2015	Print Date 06/02/2015
	 P251 Pressurized container: Do not pierce or burn, even after use. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear eye protection/ face protection. Response: P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. Storage: P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: P501 Dispose of contents/container in accordance with local regulation. 	
Potential Health Effects		
Carcinogenicity:		
IARC	No component of this product prese equal to 0.1% is identified as probat human carcinogen by IARC.	
ACGIH	No component of this product prese equal to 0.1% is identified as a carci carcinogen by ACGIH.	
OSHA	No component of this product prese equal to 0.1% is identified as a carci carcinogen by OSHA.	
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinoger by NTP.	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 5 - < 10

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area. Show this safety data sheet to the doctor in attendance.

Version 1.0	Revision Date 05/13/2015	Print Date 06/02/2015		
	Do not leave the victim unattended	l.		
If inhaled	advice.	 If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician. 		
In case of skin contact	minutes.	If skin irritation persists, call a physician.		
In case of eye contact		Protect unharmed eye.		
If swallowed	 Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital. 			

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray jet Carbon dioxide (CO2) Alcohol-resistant foam Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Version 1.0	Revision Date 05/13/2015	Print Date 06/02/2015	
Personal precautions, protective equipment and emergency procedures Beware of vapours accumulating to form concentrations. Vapours can accumulating		o form explosive	
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. 		
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica g acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. 		

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Do not breathe vapours or spray mist. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents Store and keep away from bases and alkalies.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm	NIOSH REL

ersion 1.0	Revision	Date 05/13/20 ⁻	15 Print D	Print Date 06/02/2015		
			590 mg/m3			
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1		
		TWA	750 ppm 1,800 mg/m3	OSHA P0		
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0		
propane	74-98-6	TWA	1,000 ppm	ACGIH		
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL		
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1		
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0		
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL		
		TWA	800 ppm 1,900 mg/m3	OSHA P0		

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Safety glasses Ensure that eyewash stations and safety showers are close to the workstation location.
Skin and body protection	:	impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Version 1.0

Revision Date 05/13/2015

Print Date 06/02/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	clear
Odour	:	characteristic
Odour Threshold	:	no data available
рН	:	no data available
Melting point/freezing point	:	no data available
Boiling point	:	no data available
Flash point	:	not applicable
Evaporation rate	:	not determined
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	70 hPa
Relative vapour density	:	no data available
Density	:	< 1 g/cm3
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	not determined
Partition coefficient: n- octanol/water	:	no data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	no data available
Viscosity		
Viscosity, kinematic	:	no data available
Heat of combustion	:	34.80 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.

Version 1.0	Revision Date 05/13/2015	Print Date 06/02/2015
	Extremes of temperature and direct	ct sunlight.
Incompatible materials	: Bases Oxidizing agents Amines	
Hazardous decomposition products	: Carbon dioxide (CO2) Carbon monoxide	

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:		
Acute oral toxicity	:	Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Components:		
acetone: Acute oral toxicity	:	LD50 rat: 5,800 mg/kg
Acute inhalation toxicity	:	LC50 rat: 132 mg/l Exposure time: 3 h
		LC50 rat: 50.1 mg/l
Acute dermal toxicity	:	LD50 guinea pig: > 7,426 mg/kg
		LD50 rabbit: > 7,426 mg/kg
propane: Acute inhalation toxicity	:	LC50 mouse: 1,237 mg/l Exposure time: 2 h
		LC50 rat: 658 mg/l Exposure time: 4 h
		LC50 rat: 1,355 mg/l
butane: Acute inhalation toxicity	:	LC50 mouse: 1,237 mg/l Exposure time: 2 h
		LC50 rat: 1,355 mg/l
Skin corrosion/irritation		

Version 1.0

Revision Date 05/13/2015

Print Date 06/02/2015

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

acetone: propane: butane:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available Bioaccumulative potential

Product:

Partition coefficient: noctanol/water : Remarks: no data available

Version 1.0	Revision Date 05/13/2015	Print Date 06/02/2015
<u>Components:</u> butane : Partition coefficient: n- octanol/water	: Pow: 2.89	
Mobility in soil		
no data available		
Other adverse effects		
no data available <u>Product:</u>		
Regulation	40 CFR Protection of Environment Stratospheric Ozone - CAA Section Substances	-
Remarks	This product neither contains, nor with a Class I or Class II ODS as d Clean Air Act Section 602 (40 CFR + B).	efined by the U.S.
Additional ecological information	: no data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Dispose of in accordance with local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. The product should not be allowed to enter drains, water courses or the soil.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

|--|

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazard	Is : Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard	
SARA 302	: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.	
The components of this product are reported in the following inventories:		
TSCA DSL AICS NZIOC PICCS IECSC	On TSCA Inventory This product contains one or several components that are not on the Canadian DSL nor NDSL. Not in compliance with the inventory Not in compliance with the inventory Not in compliance with the inventory Not in compliance with the inventory	

Inventory Acronym and Validity Area Legend:


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

Version 1.0

Revision Date 05/13/2015

Print Date 06/02/2015

SECTION 16. OTHER INFORMATION



OSHA GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	
- 	 Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Response: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	10
Revision Date:	05/13/2015
Print Date:	06/02/2015

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor