Material Safety Data Sheet

Conforms to ANSI Z-400.1-1993

1177

13300 East Nelson Avenue City of Industry, CA 91746

(800) 446-1888

Chemtel 24 Hour Emergency Response (800) 255-3924

1	Chemical	Product a	nd Company	Identification
---	----------	-----------	------------	----------------

Product: Slip Control Classification: Concentrated Antislip Cleaner/Degreaser A40

Composition/Information on Hazardous Ingredients

'						
Material	CAS#	%	OSHA(PEL)	TLV(ppm)	Other	
Hydroxyacetic Acid	79-14-1	<20	N/E	N/E	N/A	
Propylene Glycol Methyl Ether	107-98-2	<6	150 ppm	150 ppm	N/A	

3 Hazards Identification

Emergency Overview: Causes skin and eye irritation. Avoid skin and eye contact.

Contact with Eyes: May cause moderate irritation, redness, tearing and possible burns, depending on length of contact.

Contact with Skin: Prolonged or repeated contact may cause irritation and drying of skin.

Skin Absorption: No data.

Ingestion Symptoms: Swallowing will irritate throat, esophagus and digestive tract. Product may cause burns to mucous

membranes of the mouth, throat, esophagus and stomach.

Inhalation Symptoms: Airborne concentrations of mist/vapor may cause damage to the upper respiratory tract and even

lung tissue. If the product is heated, vapors are acutely toxic.

Chronic Effects: Overexposure may result in allergic skin reactions.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult, give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute remaining residue. Seek medical attention.

10/12/2011 0001 1177 Slip Control Page 1 of 3

5 Fire Fighting Measures

Flash Point(F° TCC): >200°F Flammable Limits: LEL No Data UEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

If diluted according to directions respirator not required.

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

ı	10/12/2011	0001	1177	Slip Control Page 2 of 3

9 Physical and Chemical Properties								
Boiling Point(F°):	>212°F	Solubility in Water:	Complete	Odor:	Fresh			
Specific Gravity:	1.08	Volatiles(% by Wt.):	86	pH:	1 - 2			
Appearance:	Clear	Vapor Density:	>1	VOC:	< 50 g/L			
Evaporation Rate:	<1	Vapor Pressure:	<17 mm Hg	Freezing Point(F°):	>32°F			
	< means less than > means greater than These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specific items.							
10 Stability and Re	activity							
Stability: Stable	Con	ditions to Avoid: Heat						
Materials to Avoid	: Strong Oxidizers	S						
Hazardous Deco	omposition Prod	ucts:						
Carbon oxides								
Hazardous Polyme	erization:							
Will Not Occur								
11 Toxicological In	formation							
No Toxicology Inforr	nation is available).						
12 Ecological Infor	mation							
No data available.								
13 Disposal Consid	derations							
Waste Disposal M	ethod:							
Dispose of waste	in accordance wit	th federal, state and local i	regulations					
14 Transport Inform	 mation							
HAZMAT: Yes	Hazard Co	ode: 1177	ID Number: UN3265	Hazard Class	: 8			
Hazardous Divisio	n. Corrosive liqu	iid, acidic, organic, n.o.s.		Packaging Group	: III			
Hazardous Conten	'	, , ,		r dokaging Group				
		Acid						
15 Regulatory Info	rmation							
Proposition 65: No	ot Listed.							
EPA: No								
16 Other Information								
HMIS/NFPA Hazard	d Rating: H	ealth 2 Flammal	bility 0 React	tivity 0				
The information contained herein is based on the data available to us. It is believed to be correct. No warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof. For further information consult Maintex, Inc.								
MSDS Approval Da	ate: 1/1/2013							
10/12/2011 000	01 1177			Slin Control	Page 3 of 3			
10/12/2011 000	· [· · · · · · · · · · · · · · · · ·			Slip Collifor	1 490 0 01 0			