HILLYARD The Cleaning Resource*

SAFETY DATA SHEET

1. Identification

Product identifier GYM LINE EN 664 YELLOW

Other means of identification

Product code HIL00664

Recommended use GRAPHIC ART PAINT

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company name HILLYARD INDUSTRIES
Address 302 North Fourth St.
St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure,

or accident involving chemicals.)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes eye irritation. May cause drowsiness

or dizziness. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Category 1

Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to

extinguish.

Material name: GYM LINE EN 664 YELLOW HIL00664 Version #: 01 Issue date: 06-01-2015

Storage Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal Buyer assumes all risk and liability associated with disposal of this product (original concentration

or dilution) in violation of applicable law in compliance with applicable federal, state and local

requirements.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Do not spray fine fog mist into sparks or open flame - vapors may ignite. Close container after each use. Avoid prolonged contact with eyes, skin and clothing. Wash thoroughly after handling. Do not take internally. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aliphatic Hydrocarbons (Stoddard Type)		8052-41-3	40 - < 50
Other components below reportable	levels		60 - < 70

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contactTake off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Biological limit values

US. OSHA Table Z-1 Limits for Air Con Components	Туре	Value
Aliphatic Hydrocarbons (Stoddard Type) (CAS 8052-41-3)	PEL	2900 mg/m3
		500 ppm
US. ACGIH Threshold Limit Values		
Components	Туре	Value
Aliphatic Hydrocarbons (Stoddard Type) (CAS 8052-41-3)	TWA	100 ppm
US. NIOSH: Pocket Guide to Chemical	Hazards	
Components	Туре	Value
Aliphatic Hydrocarbons (Stoddard Type) (CAS 8052-41-3)	Ceiling	1800 mg/m3
,	TWA	350 mg/m3

No biological exposure limits noted for the ingredient(s).

Material name: GYM LINE EN 664 YELLOW HIL00664 Version #: 01 Issue date: 06-01-2015

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Avoid contact with eyes. Use safety eyewear with splash guards or side shields, chemical goggles,

or face shields.

Skin protection

Wear appropriate chemical resistant gloves. **Hand protection**

Avoid contact with the skin. Normal work clothing (long sleeved shirts and long pants) is Other

recommended.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor

cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Yellow Liquid **Appearance**

Physical state Liquid. **Form** Liquid. Yellow Color

Aliphatic odor Odor **Odor threshold** Not available. Not available Not available Melting point/freezing point

Initial boiling point and boiling

range

300 - 316 °F (148.89 - 157.78 °C)

103.0 °F (39.4 °C) Tag Closed Cup Flash point

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

1 %

Flammability limit - upper

(%)

6 %

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. 2 hPa estimated Vapor pressure Vapor density Heavier than air

Relative density 1.06

Solubility(ies)

Negligable Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available **Decomposition temperature** Not available Not available Viscosity

Other information

Density 8.83 lbs/gal VOC (Weight %) 442 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. Eve contact Causes eye irritation.

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation

of nose and throat. Skin irritation. May cause redness and pain.

Information on toxicological effects

Narcotic effects. **Acute toxicity** Skin corrosion/irritation Causes skin irritation. Causes eye irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Prolonged inhalation may be harmful.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

3.16 - 7.15Aliphatic Hydrocarbons (Stoddard Type)

Mobility in soil No data available.

Material name: GYM LINE EN 664 YELLOW HIL00664 Version #: 01 Issue date: 06-01-2015 Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Review federal, state/provincial, and local government requirements prior to disposal. Collect and

reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

General information This material is regulated under IATA and IMDG regulations. Contact manufacturer for shipping

instructions.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Aliphatic Hydrocarbons (Stoddard Type) (CAS 8052-41-3)

SDS US

US. New Jersey Worker and Community Right-to-Know Act

Aliphatic Hydrocarbons (Stoddard Type) (CAS 8052-41-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Aliphatic Hydrocarbons (Stoddard Type) (CAS 8052-41-3)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

. . ,

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-01-2015

Version # 01

HMIS® ratings Health: 2*

Flammability: 3 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Material name: GYM LINE EN 664 YELLOW HIL00664 Version #: 01 Issue date: 06-01-2015