SAFETY DATA SHEET

DATE: September 30, 2024 EMERGENCY PHONE

CONTINENTAL CHEMICAL CO. 4920 E. WASHINGTON BLVD. COMMERCE CA. 90040

TRANSPORTATION: CHEMTREC: 800-424-9300 NON-TRANSPORTATION: HJB INC: 323-268-1288

101V 11/11/101V. 11/11/101V. 11/11/101V. 11/11/101V. 11/11/101V. 11/11/101V. 11/11/101V. 11/11/101V. 11/11/101V

SECTION I GENERAL INFORMATION

PRODUCT NAME: SAN-E3-HANDS

MANUFACTURER: CONTINENTAL CHEMICAL

HMIS: 020 G

SECTION II- HAZARDS IDENTIFICATION

CLASSIFICATION

GHS CLASSIFICATION: SKIN CORROSION (CATEGORY 1A)

SERIOUS EYE DAMAGE (CATEGORY 1) ACUTE AQUATIC TOXICITY (CATEGORY 3)

GHS LABEL ELEMENTS



PICTOGRAM:

SIGNAL WORD: FLAMMABLE

HAZARD STATEMENT: H314: CAUSES SEVERE EYE DAMAGE

H402: NOT HARMFUL TO AQUATIC LIFE

PRECAUTIONARY STATEMENTS: P280:WEAR PROTECTIVE GLOVES/PROTECTIVE

CLOTHING/EYE PROTECTION/FACE PROTECTION. P305/P351/P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE

CONTACT LENSES. CONTINUE RINSING.

P313: GET MEDICAL ATTENTION.

HMIS CLASSIFICATION: HEALTH HAZARD: 0

FLAMMABILITY: 2 PHYSICAL HAZARDS: 0

NFPA RATING: HEALTH HAZARD: 0

FIRE: 2 REACTIVITY HAZARD:0 POTENTIAL HEALTH EFFECTS

INHALATION: MAY BE HARMFUL IF INHALED. MATERIAL IS

EXTREMELY DESTRUCTIVE TO THE TISSUE OF THE MUCOUS MEMBRANE AND UPPER RESPIRATORY

TRACT.

SKIN: NONE

EYES: CAUSE SEVERE EYE BURNS.

INGESTION: TOXIC IF SWALLOWED. DO NOT INGEST.

SECTION III CHEMICAL COMPOSITION

COMPONENT CAS# CONCENTRATION

ISOPROPYL ALCOHOL 67-63-0 min. 70% DI-(C8-C10)-ALKYL DIMETHYL AMMONIUM CHLORIDES 68424-95-1 < 1.0% ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE 68424-85-1 < 1.0%

SECTION IV FIRST AID MEASURES

IF INHALED: IF INHALED, MOVE PERSON INTO FRESH AIR. IF NOT

BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

SKIN CONTACT: NONE

EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

IF INGESTED: DO NOTINDUCE VOMITING UNLESS INSTRUCTED TO

DO SO BY A PHYSICIAN. NEVER GIVE ANYTHING BY

MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH EITH WATER. CONSULT A PHYSICIAN.

SECTION V FIREFIGHTING MEASURES

FLAMMABILITY OVERVIEW: CONSIDERED A FLAMMABLE SOLVENT SOLUTION.

FLASH POINT: 20°C ASTM D-56

EXTINGUISHING MEDIA: USE WATER-SPRAY, FOAM, DRY CHEMICAL, OR

CARBON DIOXIDE.

SPECIAL PROTECTIVE EQUIPMENT: WEAR A SELF-CONTAINED BREATHING APPARATUS

(SCBA) FOR FIREFIGHTING, IF NECESSARY.

HAZARDOUS COMBUSTION PRODUCTS: HAZARDOUS DECOMPOSITION PRODUCTS UNDER

FIRE CONDITION: OXIDES OF CARBON, SMOKE,

FUMES.

SECTION VI ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: USE PERSONAL PROTECTIVE EQUIPMENT. AVOID

BREATHING VAPORS, MIST OR GAS. ALWAYS ENSURE ADEQUATE VENTILATION. EVACUATE

PERSONNEL TO SAFE AREAS.

ENVIRONMENTAL PRECAUTIONS: PREVENT FURTHER LEAKAGE OR SPILLIAGE.

PREVENT FROM ENTERING DRAINS AND

WATERWAYS. DISCHARGE INTO THE ENVIRONMENT

MUST BE AVOIDED.

CONTAINMENT AND CLEAN UP: SOAK UP WITH INERT ABSORBENT MATERIAL AND

DISPOSE OF AS HAZARDOUS WASTE. KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

SECTION VII HANDLING AND STORAGE

SAFE HANDLING: USE PERSONAL PROTECTIVE EQUIPMENT. AVOID

BREATHING VAPORS, MIST OR GAS. ALWAYS

ENSURE ADEQUATE VENTILATION.

SAFE STORAGE: KEEP CONTAINERS TIGHTLY CLOSE IN A DRY WELL

VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. STORE AWAY

FROM INCOMPATIBLE MATERIALS.

SECTION VIII EXPOSURE CONTROLS/ PERSONAL PROTECTION

EXPOSURE LIMITS

COMPONENTCAS NUMBEREXPOSURE LIMITBASISISOPROPYL ALCOHOL67-63-0400 mg/m3ACGIH-TLV

980 mg/m3 OSHA TABLE Z-1 200 mg/m3 NIOSH EXPOSURE LIMITS

PERSONAL PROTECTIVE EQUIPMENT

EYE PROTECTION: WEAR TIGHTLY FITTING SAFETY GOGGLES AND

FACE SHIELD. USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER NIOSH. HAVE EYE-WASH STATIONS AVAILABLE

WHERE EYE CONTACT CAN OCCUR.

HAND PROTECTION: NONE SKIN PROTECTION: NONE

RESPIRATORY PROTECTION: WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING

RESPIRATORS ARE APPROPRIATE, USE A NIOSH-APPROVED FULL FACE RESPIRATOR WITH APPROPRIATE CARTRIDGES. RESPIRATORY

PROTECTION MUST BE PROVIDED IN ACCORDANCE

WITH OSHA 29 CFR 1910.134.

GENERAL CONTROLS: ALWAYS ENSURE ADEQUATE VENTILATION AND

THAT WORKING AREAS CONTAINS SAFETY SHOWERS AND EYE WASH STATIONS. HANDLE MATERIAL IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES.

SECTION IX PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: LIQUID COLOR: CLEAR ODOR: ALCOHOL

pH (as is): NOT DETERMINE

VAPOR PRESSURE: 4.1 KPa @ 20°C BOILING POINT: 83 – 85°C

VAPOR DENSITY (air = 1): > 1

SPECIFIC GRAVITY: 0.85 – 0.86 @ 25°C SOLUBILITY IN WATER: COMPLETE

SECTION X STABILITY AND REACTIVITY

CHEMICAL STABILITY: STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

MATERIALS TO AVOID: AVOID HEAT, SPARKS, OPEN FLAMES OXIDIZING

AGENTS, CAUSTICS, CHLORINATED COMPOUNDS.

HAZARDOUS DECOMPOSITION: NONE

SECTION XI TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

 COMPONENT
 CAS NUMBER
 TEST
 TOXICITY

 ISOPROPYL ALCOHOL
 67-63-0
 ORAL LD50 (Rat)
 5840 mg/Kg

SKIN-DRAIZE (Rabbit) 13900 mg (24 hr) INHALATION LC50 25000 mg/m3

POTENTIAL HEALTH EFFECTS

INHALATION: MAY BE HARMFUL IF INHALED. MATERIAL IS

EXTREMELY DESTRUCTIVE TO THE TISSUE OF THE MUCOUS MEMBRANE AND UPPER RESPIRATORY

TRACT.

SKIN: N/A.

EYES: CAUSES SEVERE EYE BURNS.

INGESTION: TOXIC IF SWALLOWED. DO NOT INGEST.

SYMPTOMS OF EXPOSURE: BURNING SENSATION, NAUSEA, COUGH, WHEEZING,

LARYNGITIS, SHORTNESS OF BREATH, SPASM, INFLAMMATION, AND EDEMA OF THE LARYNX. SPASM, INFLAMMATION, AND EDEMA OF THE BRONCHI, PNEUMONITIS, PULMONARY EDEMA,

HEADACHE.

CHRONIC EFFECTS OF EXPOSURE: NO DATA AVAILABLE

CARCINOGENICITY: NO COMPONENTS OF THIS PRODUCT AT LEVELS

GREATER THAN 0.1% IS IDENTIFIED AS CARCINOGENIC BY IARC, ACGIH, OR OSHA.

SECTION XII ECOLOGICAL INFORMATION

ACUTE ECOTOXICITY

COMPONENTCAS NUMBER
ISOPROPYL ALCOHOLORGANISM
67-63-0ECOTOXICITY
NONENONENONE

ECOLOGICAL EFFECTS

PERSISTENCE AND DEGRADABILITY: NO DATA AVAILABLE

BIOACCUMULATION POTENTIAL: NOT EXPECTED TO BIO-ACCUMULATE

MOBILITY IN SOIL: NO DATA AVAILABLE

OTHER ADVERSE EFFECTS: NONE

SECTION XIII DISPOSAL

DISPOSAL: SURPLUS AND NON-RECYCLABLE MATERIAL

SHOULD BE TREATED AS HAZARDOUS WASTE AND

BE DISPOSED OF BY A LICENSED DISPOSAL COMPANY. DO NOT RELEASE INTO SEWERS OR

WATERWAYS.

CONTAMINATED PACKAGING: DISPOSE OF AS UNUSED PRODUCT.

SECTION XIV TRANSPORTATION

PRODUCT NAME:SAN E3 HANDS **PROPER SHIPPING NAME:**ISOPROPANOL
UN 1219

HAZARD CLASS OR DIVISION: 3 PACKING GROUP: II

DOT HAZARDOUS SUBSTANCE: ISOPROPANOL

SECTION XV REGULATORY INFORMATION

US FEDERAL

SARA 302 COMPONENTS: NONE LISTED

SARA 311/312 HAZARDS: ACUTE HEALTH HAZARD

SARA 313 COMPONENTS: NONE LISTED

TSCA INVENTORY: ISOPROPYL ALCOHOL (CAS 67-63-0)

EUROPEAN UNION

EC INVENTORY: ISOPROPYL ALCOHOL

STATE REGULATIONS

CA PROP 65: NONE LISTED

SECTION XVI OTHER INFORMATION

SDS VERSION: 1.0

REVISION DATE: 04/04/2015 SUPERSEDES: NEW TO GHS THE MANUFACTURER BASED ON ITS OWN DATA AND THE WORK OF OTHERS HAS ASSEMBLED THE INFORMATION IN THIS DATA SHEET. THE MANUFACTURER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, OR ADEQUACY OF THE INFORMATION CONTAINED HEREIN. THE MANUFACTURER SHALL NOT BE LIABLE (REGARDLESS OF FAULT) TO VENDEE, THE VENDEE'S EMPLOYEES, OR ANYONE FOR ANY DIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE ACCURACY, COMPLETENESS, ADEQUACY, OR FURNISHING OF SUCH INFORMATION.