

## Gloss Restorer

restaurador del lustre

This product is an ideal companion for any environmentally friendly floor care program. Meets today's need for a product that contains no zinc or other heavy metals that can be harmful to wastewater treatment systems. Regular use of this product keeps floors looking great day after day. A special proprietary mix of acrylic polymers and surfactants will bond to the surface of the floor to create an anti-slip surface. while reducing the negative impact conventional floor care products have on our environment. Concentrated for economical use dilutions. The use of this product in an automatic scrubber is highly recommended, and is the most productive way to maintain your floors.



This product meets Green Seal's environmental standard for industrial and institutional floor care products based on its reduced human and aquatic toxicity and reduced smog production potential.

Traditional Products	elements
Zinc cross-linked acrylic and modified-acrylic emulsion polymer	None
Nonylphenol ethoxylates	None
Formaldehyde	None
	Zinc-free cross-linked polymers
	1,2-benzisothiazoline-3-one
Traditional Compound Descriptions:	elements Compound Descriptions:
tinc cross-linked acrylic and modified-acrylic emulsion polymer – is u	
is a binder in floor finish and sealers. Trace amount of zinc may cause problem	It reduces toxicity of sewage effluent.
oxicity of sewage effluent and meeting discharge permit requirement.	Linear Alcohol Ethoxylate* - listed as Positive Environmental Profile surfactant
Nonylphenol ethoxylates – a non-ionic surfactant that is used to provide wet	1
and detergency. However, it is derived from a petroleum-based product. It has a	
suspected harmful biodegradable intermediate.	

## PRODUCT SPECIFICATIONS

Non-volatile Solids:

gents. However, it is a suspect carcinogen.

10.0 + 0.5%

Spray buffing or high speed burnishing

Color: Odor: Milky emulsion

Detergent Resistance:

not a suspected carcinogen.

With instant type strippers

pH:

Low

Formaldehyde – is commonly used as a preservative in coatings as well as deter-

1,2-benzisothiazoline-3-one - is an efficient microbiostat preservative for aqueous compositions such as floor finish and sealers. Low corrosivity and low odor. It is

Dry/Recoat Time:

8.4 - 9.0

Excellent

**VOC Content:** Storage/Stability:

**Buffability:** 

Removability:

Excellent 0.18 lbs./gal.

45 minutes min.

1 year

Slip Resistance: **Durability:** 

0.5 min. by ASTM-D2047

Weight Per Gallon: Freeze/Thaw Stability: 8.40 lbs./gal. Keep from freezing