Maintenance GLEANING PRODUCTS SILATE



BRILLIANT FLOOR FINISH



DESCRIPTION

A new generation floor finish formulated with a patented polymer technology that is designed to work with a variety of maintenance methods, equipment, and floors due to its ultra-compatibility and flexibility. The finish provides superior gloss, excellent durability and superior leveling. New chemistry allows the finish to form good film even in poor drying conditions. Response is unsurpassed with any type of UHS equipment - propane, battery, or electric.

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow directions accordingly. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow drying completely.

FINISHING: Apply 2 or 3 liberal coats of finish using a clean mop. Allow a minimum of 45 minutes drying time between coats. Apply additional coat to obtain desired gloss.

BURNISHING: Dust mop or sweep thoroughly. Clean floor with a neutral floor cleaner diluted according to directions. Burnish using the appropriate pads.

RESTORATION: Dust mop or sweep thoroughly. Dilute restorer according to manufacturer direction and apply to floor with clean mop or auto-scrubber. Allow to dry to a haze and buff out with any type of UHS equipment-propane, battery, or cord electric.

RECOATING: Dust mop or sweep thoroughly. Deep scrub using a neutral floor cleaner diluted according to directions. Apply 1 or 2 liberal coats of finish using a clean mop.

PRODUCT SPECIFICATIONS

Non-volatile solids:

20.0±0.5%

Coverage:

Up to 2000-2500

Color:

Milky emulsion

sq. ft. per gal.

Odor:

Mild

Detergent Resistance:

q. ii. pei gai.

Hq:

8.0 - 9.0

Heel Mark Resistance:

Excellent Excellent

Dry/Recoat Time:

45 minutes min.

VOC Content: 0.40 Storage/Stability: 2 ye

0.40 lbs./gal. 2 years

Slip Resistance: Leveling:

0.5 min. by (ASTM-D2047) Excellent

Weight per Gallon: Freeze/Thaw Stability:

8.62 lbs./gal. Keep from freezing

Buffability: Removability:

Dry burnish/Spray buff With instant type

strippers

Maintenance Mart