Sorbo Products P.O. Box 1312 Palm Desert, CA. 92261 (760)202- 4003 FAX:(760)202- 3003 www.sorboproducts.com

MATERIAL SAFETY DATA SHEET

WEIGHT % TWA/TLV

ODOR Some

MELTING or FREEZING POINT

VAPOR PRESSURE(mm Hg) low

SOLUBILITY IN WATER Soluble

pΗ

APPEARANCE Clear-slightly hazy liquid

VISCOSITY - 54.5 cST @ 100'C

BOILING POINT High

VAPOR DENSITY(Air=1) NA

PERCENT VOLATILE (by weight) Nil

EVAPORATION RATE (Butyl Acetate=1) Nil

SPECIFIC GRAVITY (WATER = 1) 1.003

******** III - FIRE AND EXPLOSIVE HAZARD DATA ***********

FLASH POINT 450' F LOWER EXPLOSION LIMIT (%) EXTINGUISHING MEDIA X FOAM X DRY CHEMICAL AUTO IGNITION TEMPERATURE UPPER EXPLOSION LIMIT (%) ALCOHOL FOAM X CO2 X WATER FOG OTHER

SPECIAL FIRE FIGHTING PROCEDURES:

Use water to cool fire-exposed containers. If a leak or spill has ignited, use water spray to disperse vapors.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

MATERIAL SAFETY DATA SHEET *****

*** IV - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

Eyes: Slight to moderate

Skin: Slightly irritating, with possible redness, edema, or drying of skin.

EMERGENCY AND FIRST AID PROCEDURES:

Eyes: Flush thoroughly with water for at least 15 minutes.

Skin: Wash exposed area with soap and water.

*** V - REACTIVITY DATA ***

STABILITY: X STABLE

CONDITIONS TO AVOID

UNSTABLE

HAZARDOUS DECOMPOSITION PRODUCTS Heating in air may produce irritating aldahydes, acids, and katones.

HAZARDOUS

POLYMERIZATION

CONDITIONS TO AVOID

MAY

X WILL NOT

9

?

INCOMPATIBILITY (MATERIALS TO AVOID)

WATER

OTHER

None

*** VI - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Contain spill if possible. Avoid contact with eyes. Wipe up or absorb on suitable material and shovel up.

WASTE DISPOSAL METHODS

Dispose of to conform with all Federal, State and local regulations.