

The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont Page Material Safety Data Sheet 1

"StoneTech" Professional Polish
6567CR Revised 6-FEB-2006

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont Chemical Solutions Enterprise

1007 Market Street Wilmington, DE 19898

PHONE NUMBERS

Product Information: 1-800-441-7515 (outside the U.S.

302-774-1000)

Transport Emergency : CHEMTREC 1-800-424-9300(outside U.S.

703-527-3887)

Medical Emergency : 1-800-441-3637 (outside the U.S.

302-774-1000)

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material CAS Number %

Isopropyl Alcohol (Isopropanol) 67-63-0

Emulsified Waxes

Water 7732-18-5

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation: May cause respiratory irritation with headache,

dizziness, and drowsiness.

Skin Contact: May cause skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: May be harmful if swallowed.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH

as a carcinogen.

Material Safety Data Sheet

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Notes to Physicians

Activated charcoal mixture may be beneficial. Suspend 50 g activated charcoal in 400 mL water and mix well. Administer 5 mL/kg, or 350 mL for an average adult.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : 146 F (63 C)

Method : Pensky-Martens Closed Cup - PMCC.

Combustible.

Extinguishing Media

Water Spray, Dry Chemical, CO2, Foam.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

Print Date: 2 - 8 - 2006

Material Safety Data Sheet

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Initial Containment

Dike spill.

Spill Clean Up

Dispose of in an approved container.

HANDLING AND STORAGE

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Store in a cool, dry place.

Avoid freezing or extended storage in high temperatures.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING

Material Safety Data Sheet

(EXPOSURE CONTROLS/PERSONAL PROTECTION - Continued)

Where there is potential for skin contact, have available and wear as appropriate impervious gloves, apron or smock.

Exposure Guidelines

Applicable Exposure Limits

Isopropyl Alcohol (Isopropanol)

PEL (OSHA) : 400 ppm, 980 mg/m3, 8 Hr. TWA

TLV (ACGIH) : 200 ppm, 8 Hr. TWA, A4

STEL 400 ppm

AEL * (DuPont) : 400 ppm, 8 & 12 Hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Solubility in Water : Soluble Odor : citrus. Form : Liquid. Color : White.

STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and storage conditions.

Incompatibility with Other Materials

Incompatible or can react with oxidizing agents.

Decomposition

Thermal decomposition may produce carbon dioxide, carbon monoxide.

DISPOSAL CONSIDERATIONS

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

Print Date: 2 - 8 - 2006

Material Safety Data Sheet

TRANSPORTATION INFORMATION

Shipping Information

Not Regulated as a hazardous material by DOT, IMO, or IATA.

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : Listed.

TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312

Acute : Yes Chronic : No Fire : No Reactivity : No Pressure : No

OTHER INFORMATION

NFPA, NPCA-HMIS

NPCA-HMIS Rating

Health : 1
Flammability : 1
Reactivity : 0

Personal Protection rating to be supplied by user depending on use conditions.

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsible for MSDS: MSDS Coordinator

> : DuPont Chemical Solutions Enterprise

Address : Wilmington, DE 19898

Telephone : (800) 441-7515

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS