PREMIER product line

WASH & WAX

Neutral High Foam Liquid Car, Truck & Vehicle Cleaner with Wax

Emulsifies Grease • No Film • No Streaks


Appearance Clear Blue Liquid
Odor Mild
pH (conc.) 8.5
Solubility Complete



Biodegradable Manufactured to ISO 9002 Specifications

NFPA 704 Hazard Rating:

4=Extreme, 3=High, 2=Moderate 1=Slight, 0=Minimal



Rating for this product:

Health 0	.,, None
Fire 0	Will Not Burn
Reactivity 0	Stable

EMERGENCY: (800) 535-5053 24 Hour MSDS Information

Other Useful Products:

	PROD
PRODUCT NAME	CODE
Cleaning Gem	J3104
USDA approved cleaner/degr	
Liquid Car Clean	
car wash liquid	
See Ready-to-Use	B2302
glass & hard surface cleaner	

DESCRIPTION

- WASH & WAX is a top-of-the-line hard surface detergent that cuts through greasy soil and road film while polishing in one-step.
- It provides thick, stable foam even after cleaning greasy cars, trucks, equipment and other hard surfaces
- WASH & WAX brings new luster to dull paint.
 It is highly concentrated, high-foaming, fast-rinsing and quick drying.
- It eliminates water spotting and is safe on all surfaces not harmed by water. It's biodegradable, too.
- WASH & WAX can be used on cars, trucks, vans, busses and motor homes by hand or pressure washing. It works great on windows leaving them clean and sparkling.

DIRECTIONS

Cars, trucks, painted and hard surfaces:

Rinse off gross solls. Wash with a 1 ounce solution of WASH & WAX per gallon of water. For extremely greasy soils, add 1 ounce of TSP to each gallon of solution, Rinse with water.

Floors:

Sweep the floor to remove all loose dirt and trash. Dilute 1 ounce of WASH & WAX per gallon of water in a bucket. Mop floor. Change the solution often. Rinse floor and clean again if any residue is present. No further rinsing is required.

Tools and Other Greasy Items:

Dilute WASH & WAX according to the following conditions in a sink with hot water.

Light grease:

Dilute 1 ounce per 5 gallons of water.

Heavy grease:

Dilute 2 ounces per 5 gallons of water.

For heavier soils other than windows:

Dilute 2 ounces per 5 gallons of water. Add 1 ounce of TSP per 5 gallons of water.

Soak Items for 5 minutes. Scrub as necessary with a brush. Rinse with water and let air dry.

DIRECTIONS Large Area Window Cleaning:

Add 1 capful per gallon of water. Use more for dirty windows, even less for lightly solled windows. The amount you will need varies, depending on job conditions, water hardness, temperature, squeegee rubber and personal preference. Always put the water in the bucket

first, then add WASH & WAX.

Oftentimes you can obtain excellent results without using a squeegee; on French windows, for example. Brush on and hose off. Let air dry.

Dilute WASH & WAX into a bucket. Apply with a scrubber or similar applicator one section at a time. A fight scrubbing should be enough if there is only dust and dirt on the glass. To remove bird doo, concrete, silicone residue and water spots, use medium course steel wool (oo).

Never use a green dishwashing pad. This is a sure way to scratch the glass. Remove the solution of WASH & WAX and the soil with a squeegee, making sure to wipe the excess from the rubber blade, window frames and ledges with a clean cloth. Repeat if necessary.

CAUTION

EYE IRRITANT -Contains nonyiphenol polyethylene ethoxylate. Avoid contact with skin and eyes. Do not ingest.

FIRST AID

EYES: Flush with water for 20 minutes. Seek medical attention.

SKIN: Flood with water for 15 minutes, if irritation persists, seek medical attention.

INGESTION: Induce vomiting. Give large quantities of water. If vomiting occurs, keep airways clear and give fluids again. Seek medical attention

KEEP OUT OF REACH OF CHILDREN

FORMULAS THAT MEET THE CHALLENGE janitorial-restaurant-laundry-auto-industrial HAYWARD, CA 94544 • 510-324-4567

MATERIAL SAFETY DATA SHEET

EMERGENCY: (800) 535-5053

Product Name: Wash & Wax Manufactured by: EXSL/Ultra Labs, Inc. Product Code: A2103 Effective Date: 11/30/04 Proper Shipping Name: Not applicable. This is a non-regulated material. Supersedes: 07/13/01 **HAZARDOUS INGREDIENTS** CAS# PCNT% TWA STEL SARA III PROP 65 Carcinogen Dodecylbenzene Sulfonic Acid 27176-87-0 6.40 None None No Nο Nο PHYSICAL DATA Boiling Point: 212° F pH: (Conc.) 8.5 Viscosity: @20° F 800 cps Vapor Pressure: Not Avail. Specific Gravity: 1.032 Evaporation Rate: 1.0 Solubility: Complete Vapor Density: 1.0 Appearance & Odor: Thick Amber Liquid, No Fragrance Reactivity in Water: None Melting Point: Not App. Volatiles: 75% FIRE & EXPLOSION DATA NFPA 704 Hazard Rating Health: 0 ... None Flash Point: None (Cleveland Open Cup) Fire: 0 ... Will Not Burn 4 = Extreme, 3 = High, 2 = Moderate Reactivity: 0 ... Stable 1 = Slight, 0 = Minimal Flammability Levels (LEL/UEL): Not App. Extinguishing Media: This product is not combustible. Use water spray, foam, carbon dioxide, or dry chemical. Fire & Explosion Hazard:... None Conditions to Avoid: Open flames, welding arcs or other high temperature sources that induce thermal decomposition, which produce toxic fumes **REACTIVITY DATA** Materials to Avoid: None. Hazardous Decomposition Products: None Stability: Stable Hazardous Polymerization: Will not occur **HEALTH HAZARDS** Eye Contact: Causes moderate to severe irritation. Prolonged and repeated contact can cause redness and tearing. Skin Contact: May cause dryness with prolonged contact. Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Inhalation: Spray or mist can be irritating to the upper respiratory tract. FIRST AID to minimizing eye damage. Hold eyelids apart to ensure flushing of the entire surface. . Wash with water. If imitation persists, seek medical attention. Ingestion: Never give anything to an unconscious person. If swallowed, induce vomiting. Give large quantities of water or milk. If vomiting occurs, keep airways clear. Seek medical attention. Inhalation: ... Move person to fresh air and away from exposure. If breathing is difficult, administer oxygen and seek medical attention. Give artificial respiration if victim is not breathing.

SPILL OR LEAK PROCEDURES

Steps to Contain:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leaks if you can do it without risk. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing (rubber boots and gloves). Contain spills with dry earth, sand or other non-combustible material and transfer to containers. Sweep up powder spills and transfer to containers. DO NOT GET WATER INSIDE CONTAINERS.

Recommended Waste Disposal Method:

The materials resulting from the clean up may be hazardous waste and, therefore, subject to specific regulations. Package, store, transport, and dispose all clean-up materials and any contaminated equipment in accordance with all applicable federal, state, and local health environmental regulations. Shipments of waste materials are subject to manifesting requirements per applicable regulations. Ensure that all responsible federal, state, and local agencies receive proper notification of spills and disposal methods.

SPECIAL PROTECTION & PRECAUTIONS	
Respiratory: None under normal use conditions.	Clothing: None under normal use conditions.
Eye:None under normal use conditions.	Comments: None under normal use conditions.
Storage:Keep in a cool, dry place.	Handling: Do not stack or palletize over three high.
User's Responsibility	

It is the user's responsibility to provide a safe workplace. He or she should consider the health hazard and safety information contained herein as a guide and take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.